INCH-POUND

MIL-F-50253A (AR)
AMENDMENT 3
26 December 1992
SUPERSEDING
AMENDMENT 2
12 May 1982

MILITARY SPECIFICATION

FUZES, ROCKET, M423, M427 AND M433
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-50252A (AR), dated 10 November 1978, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1: Delete
"9260701 - Fuze, Rocket, M433 with Booster and Booster Lead"
and substitute
"9260701 - Fuze, Rocket, M433".

* Add
"9329860-3 - M433/M439 Fuze Continuity Test Set".

PAGE 3

* 3.7: Add "NOTE: THIS ELECTRICAL CHARACTERISTIC IS AN ELECTRICAL INTERFACE CHARACTERISTIC AND SHALL NOT BE ALTERED OR CHANGED WITHOUT AN APPROVED GOVERNMENT DEV/WAV OR ECP.".

PAGE 4

4.3.1: Delete "Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "Fuze, Rocket, M433".

PAGE 5

TABLE I: Delete "with Booster and Booster Lead".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:18Z
Check the source to verify that this is the current version before use.

PAGE 6

TABLE I: In two places, Delete "with Booster and Booster Lead".

PAGE 7

4.4.1: Delete
"a. One metal parts lot from one manufacturer" and substitute "Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of boostered fuzes shall contain:

a. Fuzes bearing the same metal parts lot interfix number from one metal parts manufacturer".

PAGE 9

4.4.2.2, Major 105: Delete "0.40%" and substitute "100%".

PAGE 10

* 4.5.2: Delete in its entirety and substitute:

"Umbilical Continuity Test. Each fuze umbilical shall be connected to an Umbilical Test Set (9329860-3). Each umbilical must meet the acceptance requirements. Any umbilical that does not meet the acceptance requirements shall be classed as defective and removed from the lot.

PAGE 11

4.5.3.2, line 8: Delete "functional" and substitute "functioned".

4.5.3.3: Delete in its entirety and substitute:

"M433 Fuze. Live boosters will be assembled into a government-approved simulated M433 fuze, an M423 Fuze Assembly or an M427 Fuze Assembly. When a simulated M433 fuze is used, the test fixture must simulate an M433 explosive train in the armed condition. Functional (electrical) energy of not less than 750 ergs shall be applied to the detonator electrical contacts in the simulated test fixture. High order detonation shall be determined by a 0.25 inch minimum dent in a cylindrical witness block (1.5 inch minimum height by 2.0 inch minimum diameter of 2011-T3 aluminum). When M423/427 Fuze Assemblies are used, the test procedure of 4.5.3.2 applies.

"WARNING: This test is dangerous and must be performed behind a suitable barricade."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

PAGE 12

4.5.4.2, Line 10, After "needed." Add

"Rounds containing M433 Fuzes shall be set to the superquick mode with a government approved setter design that represents the helicopter setter system."

PAGE 13

* 6.3: Delete "DRDAR-QAR-I: and substitute "SMCAR-QAF-I".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army

Preparing activity:
Army-AR

(Project 1340-A878)

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:18Z
Check the source to verify that this is the current version before use.