INCH-POUND

MIL-M-49240A(CR)
AMENDMENT 1
2 October 1992

MILITARY SPECIFICATION
MULTIPLEXER, TD-1235(P)/TTC

This amendment forms part of MIL-M-49240A(CR), dated 21 April 1987, is approved for use by the Communications-Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 22

In Table I First Article Inspection replace current note (1) with the following:

"One time only first article test not to be performed during Group C production lot testing."

PAGE 44

4.7.5.1.g, line 2: Delete "20 dB" and substitute "26 dB".

PAGE 47

4.7.5.8.2.c,h: Delete the output voltage V1 "+6dBm" and substitute "+6dB".

PAGE 48

4.7.5.9.c, line 2: Delete the oscillator output "+10dBm" and substitute "+10dB".

PAGE 50

4.7.7h: Add a note to read as follow:Threshold level of the squelch input at steps g. and h. might occurs between 0.8 to 2.0 V.

PAGE 52

4.7.8.3.c: Delete and substitute the following: "C. Set the error inserter for 20% BER random bursts interspersed with 0.1% BER random error intervals."

AMSC No. N/A FSC 5820
DISTRIBUTION STATEMENT A. Approved for release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:57Z
Check the source to verify that this is the current version before use.

PAGE 53

4.7.9.e.(3): Delete the oscillator output "-11dBm" and substitute "-11dB". Add under NOTE the following formula: "Gain=20LOG(Vchout/0.220)+6 (dB)"

PAGE 56

4.7.11.5.c: Under NOTE add the following formula "Gain=20LOG(Vchout/0.220)+6 (dB)"

PAGE 58

Para 4.7.12.5.b: Under NOTE add the following formula "Gain=20LOG(Vchout/0.220)+6 (dB)"

PAGE 60

4.8.7: Delete and substitute with the following:

"4.8.7 Vibration - The equipment shall be subjected to test of MIL-STD-810C, Method 514.2, Procedure X (Curve AW), Part II, as specified below. Perform a Unit Performance Electrical Test and Visual Inspection.

Vibration in each of the three (3) principal axes shall be performed in the following sequence.

Install the unit equipment mounting brackets on the UUT and install the unit on the vibration exciter in the vertical axis (top to bottom). Install the control accelerometers on the vibration fixture.

SINUSOIDAL VIBRATION PROFILE

TEST LEVEL:	1.5g
FREQUENCY RANGE:	5.0 Hz to 200 Hz to 5.0 Hz
SWEEP RATE:	5.0 Hz to 200 Hz to 5.0 Hz in twelve (12) minutes.
TIME DURATION:	84 Minutes per axis

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:57Z
Check the source to verify that this is the current version before use.

Subject the unit to the vibration levels specified in the vibration profile from 5Hz to 200 Hz over a period of six (6) minutes, while monitoring the control accelerometer(s). Verify that the monitored response of the control accelerometer(s) is within 10 percent of the specified 1.5g input thru the entire frequency range of 5.0 Hz to 200 Hz.

Cycle the unit in accordance with the vibration profile. Vary the frequency at the sinusoidal rate from 5.0 Hz to 200 Hz to 5.0 Hz within 12 minutes. (This constitutes one (1) cycle.) Subject the unit to 7 cycles of vibration for a total test time of 84 minutes. (This includes the 6 minutes recorded previously).

Repeat Steps with the unit oriented in side-to-side and front-to-back axes.

Perform a Unit Electrical Performance Test and Visual Inspection."

PAGE 101

In Figure 34: Delete at the Universal Counter the stop connection to test point 6 "TP6 (Frame Maintenance)" and substitute "I/O 48 (Frame Maintenance)."

PREPARING ACTIVITY:
Army-CR
Project 5820-A947

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:57Z
Check the source to verify that this is the current version before use.