INCH-POUND

MIL-P-70596B (AR)
AMENDMENT 1
8 December 1992

MILITARY SPECIFICATION

POWER BOARD: 9361073

This amendment forms a part of MIL-P-70596B (AR), dated 23 January 1991, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering and Electronic Assemblies"

2.1.2: Delete the following drawing:

"10545465 - Isolator"

Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

"3.3.1 Vibration. The power board shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:46Z
Check the source to verify that this is the current version before use.

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.3 Altitude operating. The power board shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 6

3.7: Delete in its entirety and substitute the following:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 11

Table VI: Delete last item number and description, i.e., "6. Isolator 10545465".

PAGE 12

Figure 1: Delete "AR1-6" and substitute "AR1-1".

Correct wiring of switch S1:

Switch setting "AZ COMM", P1-H position: Delete "AR2-1" and substitute "Board Input".

Switch setting "EL COMM", P1-(D) position: Delete "AR2-1" and substitute "Board Input".

PAGE 13

4.7.1.1: Delete first sentence and substitute the following:

"4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.3: Delete in its entirety and substitute the following:

"4.7.1.3 Altitude operating. This test shall be performed as specified in Procedure II, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:46Z
Check the source to verify that this is the current version before use.

PAGE 14

4.7.3a, line 4: Delete "The bias at pin shall.... Set R11 at midpoint" and substitute: "The bias at pin 3 shall be between -9 and -15 mV. Set R31 at midpoint. Measure the bias on pin 5 of U1. The bias shall be between -9 and -15 mV. Rotate R11 fully counterclockwise and measure the bias on pin 5. The bias shall read between +9 and +15 mV. Set R11 at midpoint."

4.8: Delete in its entirety and substitute the following:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

PAGE 18

Figure 5, title: Delete "Azimuth gain" and substitute "Azimuth phase".

PAGE 19

Figure 6, title: Delete "Azimuth phase" and substitute "Azimuth gain".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A870)

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:46Z
Check the source to verify that this is the currentversion before use.