INCH-POUND

MIL-S-48755A(AR)
AMENDMENT 4
26 June 1989
SUPERSEDING
AMENDMENT 3
2 August 1988

MILITARY SPECIFICATION

SENSOR, TRIPLINE: EXTENDED RANGE

This Amendment forms a part of Military Specification MIL-S-48755A(AR) dated 6 December 1983 and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3, add the following at end of paragraph:

"Breakwire continuity shall be maintained as specified in paragraph 3.8".

PAGE 6

* 4.4.2.1, Delete Major 106 in its entirety and substitute the following:

"Major 106, Hardness, 5-0-1, 2/, 3.2, Test ASTMD 2240"

* Delete Note 2 and substitute:

"2/ Five samples to be tested from every cycle of 5000."

PAGE 12

Delete Note 1 and substitute the following:

"1/ Ten samples to be tested at start of each 8 hour shift, Accept 0, Reject 1."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the currentversion before use.

PAGE 17

4.4.2.11, Release Mechanism & Case Assembly.

Add Major 103 Clearance between diaphragm and nozzle below min. .040% 3.2 Gage

PAGE 18

* 4.4.2.12, Delete Major 102 and Major 108 in their entirety.

* Add Major 112:

"Major 112, Length of post from post end flange to bottom of breadkwire notch, 1/, 0.40%, 3.2, Gage"

* Add Major 113:

"Major 113: Rib(s) on bobbin and post flange(s) missing, incomplete, or damaged, 1/, 0.40%, 3.2, Visual"

PAGE 20

4.4.2.13: Thread, Polyester.

Change Drawing number from "9298274" to "9378274".

PAGE 23

4.4.2.16 Wire, Magnet, electrical (Breakwire) change Drawing Number from "9298576" to "12624765".

PAGE 29

4.4.2.22, Tripline Sensor, Extended Range (Prior to Assembly of Cover, Post)

Add the following Major defect 103:

"103 Breakwire soldered improperly 0.40% 3.11 Visual (Before application of Adhesive)"

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the currentversion before use.

PAGE 34

4.5.1.3, Change first sentence to read as follows:

"... in accordance with 4.5.1.2.1 and 4.5.1.2.2 and with the sensor ..."

4.5.1.3c, Change from "... 30° and 45°." to "... 45° max."

4.5.1.4, Change first sentence to read as follows:

"... accordance with 4.5.1.1, 4.5.1.2.1, 4.5.1.2.2 and 4.5.1.3 ..."

PAGE 35

4.5.1.5, Change first sentence to read as follows:

"... accordance with 4.5.1.1, 4.5.1.2.1, 4.5.1.2.2, 4.5.1.3, and 4.5.1.4 and with ..."

PAGE 36

5.1, Preservation and Packaging, Add to end of paragraph:

"Type I, Class E, Style 1, Specification MIL-B-117, may be used as alternate barrier bag."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A532)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.