MIL-A-13488C(AT)
AMENDMENT 1
12 May 1978

MILITARY SPECIFICATION

AIR CLEANER, ENGINE: HEAVY DUTY,
OIL BATH TYPE (FOR INTERNAL COMBUSTION ENGINES)

This amendment forms a part of Military Specification MIL-A-13488C(AT), dated 15 May 1973.

PAGE 1

2.1, add:

"MIL-B-5924 - Batting, Insulation Glass Fibers."

PAGE 2

2.1, delete "MIL-L-10295" in its entirety and substitute:

"MIL-L-46167 - Lubricating Oil, Internal-combustion Engine, Arctic."

3.2, line 5: Add "(see 6.5)."

PAGE 3

3.2.3, line 2: Add "(see 4.5.2.3)."

PAGE 4

3.4, Table I, line 3: Delete "MIL-L-10295" and "0° to -65°F" and substitute:

"MIL-L-46167" and "+40°F to -65°F".

PAGE 6

4.1, line 2: Delete "or purchase order". Change "supplier" to "contractor".

line 4: Change "supplier" to "contractor", and delete words "or order".

FSC 2940

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:42Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.1.2, line 2: Delete the word, "standard".

4.3.1.3, line 2 and 3: Delete words, "the appendix to standard".

PAGE 8

4.3.4, change title from "Inspection of preparation of delivery" to "Inspection of packaging".

4.4.3, line 2: Delete "refust" and substitute "refuse".

PAGE 9

4.5.2.3, delete in its entirety and substitute:

"4.5.2.3 Absolute filter. The absolute filter shall consist of one layer of 10-ounce canton flannel and one layer of 1/2 inch fiber glass batting conforming to MIL-B-5924. The canton flannel shall be the final filtering media. The master filter medias shall be installed in a suitable housing with the nap side of the fiber glass batting facing up stream. The master filter housing shall be of sufficient size to limit the air flow face velocity to a maximum of 200 cubic feet per minute. A new absolute filter batting shall be installed if, during the dust capacity test, the air pressure drop across the absolute filter increases 10 inches of water above its original restrication. A manometer shall be located in the test set-up to measure the pressure drop across the absolute filter."

PAGE 10

4.5.2.3.1, delete in its entirety and substitute:

"4.5.2.3.1 Preparation of absolute filter. The fiber glass batting and canton flannel shall be hung in an air oven and dried at a temperature of 200°F to 240°F. The batting and flannel shall be considered completely dry if there is no change in oven weighings of the material for three consecutive weighings at 10 minute intervals. This drying and weighing procedure shall be observed before and after each test involving dust feeding."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:42Z
Check the source to verify that this is the current version before use.

PAGE 13

5., delete: "PREPARATION FOR DELIVERY" and substitute "PACKAGING".

5.1, delete paragraph in its entirety and substitute with the following:

"5.1 Preservation, packaging, packing and marking. Preservation, packaging, packing and marking shall be in accordance with the applicable packaging standard or packaging data sheet as furnished at time of invitation for bid, for the level(s) of preservation packing specified by the procuring activity (see 6.2)."

PAGE 14

6.2, line (g): Delete in its entirety and substitute:

"(g) Selection of applicable level of packaging, and level of packing (see 5.1).".

line (h), add: "(see 6.3)."

6.3, line 2 and 3: Delete "U.S. Army Tank Automotive Command, ATTN: AMSTA-RKA, Warren, Michigan 48090", and substitute, "US Army Tank-Automotive Materiel Readiness Command, ATTN: DRSTA-QI, Warren, MI 48090".

6.5, Add:

"6.5 Recycled Materials. The use of recycled materials which meet the requirements of the applicable material specifications without jeopardizing the intended use of the item shall be encouraged (see 3.2)."

Custodian:
Army - AT

Reviewer:
DSA - CS

Preparing activity:
Army - AT

Project 2940-A101

International interest (see sect. 6)

*U.S. GOVERNMENT PRINTING OFFICE: 1978—703-122/2675

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:42Z
Check the source to verify that this is the current version before use.