INCH-POUND
MS25267J
12 March 2024
SUPERSEDING
MS25267H
27 November 2003

DETAIL SPECIFICATION SHEET

RELAY, ELECTROMAGNETIC, 5 AMPERES, 4 PDT, TYPE I, SOLDER HOOK, HERMETICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 29 FEBRUARY 2000. NO SUPERSEDING DOCUMENT. FOR NEW DESIGN USE MIL-PRF-83536/5 OR MIL-PRF-83536/6.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
0.001	0.03	0.375	9.53
0.003	0.08	0.593	15.06
0.005	0.13	0.687	17.45
0.040	1.02	0.750	19.05
0.062	1.57	0.812	20.62
0.138	3.51	1.130	28.70
0.152	3.86	1.187	30.15
0.235	5.97	1.531	38.89
0.343	8.71	1.750	44.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±0.010 (0.25 mm).
4. Terminal numbers need not appear on relay headers provided there is affixed to the relay a suitable legible circuit diagram that permanently and positively identifies each terminal location specified herein.
5. The use of diodes on ac relays is optional. Actual application must be shown on label.
6. In the event of conflict between the text of this standard and the references cited herein, the text of this specification shall take precedence.
7. Referenced Government documents of the issue listed in that issue of the Acquisition Streamlining and Standardization Information System (ASSIST) specified in the solicitation forms a part of this standard to the extent specified herein.

TABLE I. Dash numbers and characteristics.

Dash number MS25267-	Type	Coil	Terminal type	Mounting or mating socket	Max weight in pounds
D1	I	dc	Solder hook	Stud	0.32
A1	I	ac	Solder hook	Stud	0.32

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.

TABLE II. Operating characteristics.

PIN MS25267-	Coil data											Time - milliseconds max					
	Coil	Rated			Max		1/ Max pick-up voltage			Drop out voltage 3/	Hold voltage 3/	Operate 4/	Release 5/	Contact Bounce			
														Main		Aux	
		Volts 1/	Freq Hz	Ω Res ±10%	Volts	Amp	Normal 3/	High temp test	Cont current test					NO	NC	NO	NC
D1	X1, X2	28	dc	248	29	0.15	18	19.8	22.5	1.5	7.0	20	20	2	2	N/A	N/A
A1	X1, X2	115	400 2/	N/A	122	0.05	90	95	103	5.0	30	25	50	2	2	N/A	N/A

1/ CAUTION: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.
2/ MS25267-A1 may be used on 60 Hz if maximum ambient temperature is limited to 85°C, maximum current will be 0.044 ampere.
3/ Over the temperature range.
4/ With nominal coil voltage.
5/ From nominal coil voltage.

TABLE III Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appropriate notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	
Resistive	100	5	5			5	4							
Inductive	100													
Inductive	20	3	3			3	2							
Motor	100	1.5	1.5			1.5	1							
Lamp	100	0.8	0.8			0.8	0.6							
Transfer load														2/
Mechanical life reduced current	400	1.25	1.25			1.25	1			12.5				
Mixed loads	Applicable per specification													

1/ Absence of value indicates relay is not rated for 3-phase application.
2/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

Environmental characteristics.

Temperature range	-70°C to +125°C
Max altitude rating	80,000 ft
Shock G-level	50 g's
Duration	11 ms
Max duration contact opening	10μs
Vibration - sinusoidal	
G-level	10 g's
Frequency range	5-1,500 Hz

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.

Vibration - random	
Applicable spec	N/A
Power spectral density	N/A
RMS G min	N/A
Frequency range	N/A
Curve	N/A
High shock	N/A
Acceleration	15 g's

Electrical characteristics.

Minimum insulation resistance, initial	100 megohms.
After life or environmental tests	50 megohms.

Dielectric strength (sea level).

	Initial	After life tests
Coil to case	1,050 V rms	1,000 V rms
Aux contacts		N/A
All other points	1,050 V rms	1,000 V rms

Dielectric strength (altitude).

	80,000 ft
Coil to case	1,000 V rms
Aux contacts	
All other points	1,000 V rms

Max contact drop initial	0.150 volt.
After life test	0.175 volt.
Overload current	20 amperes.
Rupture current	25 amperes.
Duty rating	Continuous.
RFI specification	MIL-STD-461

(Applicable to coil circuits of ac operated relays).

Conformance inspection.

Performance of groups B and C tests are not applicable.

Group A acceptance reports shall be submitted to the preparing activity every 36 months in order to retain qualification for this military specification sheet.

Group B and Group C inspections may be suspended at the discretion of the qualifying activity.

Qualification by similarity: See MIL-PRF-6106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.

NOTES

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced document. In addition to MIL-PRF-6106, this document references the following:
MIL-STD-461

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2024-013)

Review activities:
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.