INCH-POUND
MIL-DTL-24704B(SH)
4 October 2011
SUPERSEDING
MIL-F-24704A(SH)
23 March 1992

DETAIL SPECIFICATION

FLANGES, FOUR BOLT SQUARE, HYDRAULIC GENERAL SPECIFICATION FOR

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirement for a 4-bolt, square flange for use in 3000 pounds per square inch (lb/in^2) hydraulic systems.

1.2 Classification. Flanges are designated by part identification number, as specified on the applicable specification sheet (see 6.2).

1.2.1 Material requirement. The material requirement is designated by a letter. The material is designated in the applicable specification sheet.

1.2.2 Vent requirement. The vent requirement is designated by a letter. The letter designation and location for the vent port on a given flange should be in accordance with the applicable specification sheet.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-24704/1	-	Flanges, Four Bolt Square, Socket Weld for Hydraulic Systems
MIL-F-24704/2	-	Flanges, Four Bolt Square, Butt Weld for Hydraulic Systems
MIL-F-24704/4	-	Flanges, Four Bolt Square, Blind for Hydraulic Systems

Comments, suggestions, or questions on this document should be addressed to: Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line “Document Comment”. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

MIL-F-24704/5 - Flanges, Four Bolt, Insert Rings for Hydraulic Systems

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or https://assist.daps.dla.mil.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASME INTERNATIONAL

ASME B46.1 - Surface Texture, Surface Roughness, Waviness and Lay

(Copies of this document are available from ASME International, 2 Law Drive, P.O. Box 2900, Fairfield, NJ 07007-2900 or online at www.asme.org.)

ASTM INTERNATIONAL

ASTM E1282 - Standard Guide for Specifying the Chemical Compositions and Selecting Sampling Practices and Quantitative Analysis Methods for Metals, Ores, and Related Materials

(Copies of this document are available from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959 or online at www.astm.org.)

SAE INTERNATIONAL

SAE-AMS-QQ-S-763 - Steel Bars, Wire, Shapes, and Forgings; Corrosion Resistant

(Copies of this document are available from SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001 or online at www.sae.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheet. In the event of any conflict between the requirements of this specification and the specification sheet, the latter shall govern.

3.2 Materials. Flanges shall be manufactured from materials designated in the applicable specification sheet.

3.2.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.2.2 Material composition. When specified (see 6.2), a chemical analysis shall be performed in accordance with ASTM E1282 for verification of material composition. Materials not in accordance with this specification or the applicable specification sheets shall be cause for rejection.

3.3 Machining. The flange shall be machined to the configuration and dimensions as specified herein and on the applicable specification sheet (see Appendix A).

3.4 Surface finish. Unless otherwise specified (see 6.2), surface roughness shall not exceed 125 microinches (see 4.1.3 for surface finish inspection method). Surface finish for sealing surface shall be in accordance with the applicable specification sheet. Machined surfaces shall have no burrs. Sharp edges and corners shall be rounded to a radius of 0.005 inch, minimum. Non-machined surfaces, such as forged surfaces and bar stock flats, shall have no fins, cracks, or spongy areas.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

3.5 Identification marking. Each flange shall be clearly and permanently marked with the following information:

a. Part identification number (see 1.2).

b. Manufacturer's name, trademark, or logo.

c. Manufacturer's part number (optional).

d. Pressure rating.

3.6 Workmanship. Flanges shall be free from detrimental grooving, indentations, flaws, cracks, lamination, surface pitting, inclusions, and slivers which would interfere in their use and shall be free from dirt, corrosion, and other extraneous material.

4. VERIFICATION

4.1 Conformance inspection. Conformance inspection shall consist of the examination as specified in 4.1.2.

4.1.1 Sampling. Unless otherwise specified (see 6.2), sampling for conformance inspection shall be as specified in 4.1.1.1 through 4.1.1.3.

4.1.1.1 Inspection lot. A lot shall consist of finished flanges which are of the same material, type, size, fabricated by the same process, and produced as one continuous run or order, or part thereof, and submitted for acceptance inspection at the same time.

4.1.1.2 Sampling for examination. A random sample of flanges shall be selected from each lot and inspected in accordance with table I. The sampling plans in table II shall be utilized in accordance with the classification of defects in table I.

TABLE I. Classification of defects.

Categories	Defects	Inspection method
Major		
101	Surface finish not as specified on sealing face (see 3.4)	4.1.3
102	Flange size not as specified (see 3.3)	SIE 1/
103	Sealing face not machined as specified (see 3.3)	SIE
104	Bore dimensions not as specified (see 3.3)	SIE
105	Bolt holes not located or drilled properly (see 3.3)	SIE
106	Vent location not as specified (see 3.3)	SIE
107	Material composition not as specified (see 3.2)	ASTM E1282
108	Flange style not as specified (see 3.3)	SIE
109	Workmanship defects (see 3.6)	Visual
Minor		
201	Surface finish not as specified (not including sealing face) (see 3.4)	4.1.3
202	Flange not properly marked (see 3.5)	Visual

NOTE:

1/ Standard inspection equipment (SIE).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling plan for major and minor defects.

Lot size	Sample size	Accept	Reject
1 to 13	Entire lot	0	1
14 to 150	13	0	1
151 to 280	20	0	1
281 to 500	29	0	1
501 to 1200	34	0	1
1201 to 3200	42	0	1

NOTES:
1. All defective items shall be replaced with acceptable items prior to lot acceptance.
2. Stop inspecting samples when reject criteria is reached.

4.1.1.3 Rejection. Any flange in the sample which contains 1 or more defects shall be rejected. If the number of defective flanges in any sample exceeds the acceptance number for that sample, the entire lot shall be rejected.

4.1.2 Examination. Each flange taken as specified (see 4.1.1.2) shall be examined as specified in table I to verify conformance to this specification.

4.1.3. Surface finish inspection method. Surface roughness shall be identified in accordance with ASME B46.1. The determination of surface finishes shall be made with a profilometer, comparator brush analyzer, or other comparison equipment with an accuracy of ±15 percent at the level being measured. Surface finishes on sealing finish not in accordance with this specification or the applicable specification sheet shall be cause for rejection.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Flanges covered by this specification are intended for use in 3000 lb/in² hydraulic systems that operate under conditions that impose mechanically induced shock on system piping and components.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Title, number, and date of applicable specification sheet.
c. Specification sheet part number required (see 1.2).
d. If material verification by analysis is required (see 3.2.2).
e. If surface roughness measurements are other than specified (see 3.4).
f. If conformance sampling is other than specified (see 4.1.1).
g. Level of preservation, level of packing, and other packaging acquisitioning options required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

6.3 Subject term (key word) listing.

Flange, right angle

Flange, straight

Flange style, pipe

Flange style, tube

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

FLANGE INTERFACE AND ASSEMBLY INSTRUCTIONS

A.1. SCOPE

A.1.1 Scope. This Appendix details the interface machining configuration for the 4-bolt flange and the assembly instructions. This Appendix is not a mandatory part of the specification. The information contained herein is intended for guidance only.

A.2. APPLICABLE DOCUMENTS

A.2.1 General. The documents listed in this section are specified in sections 3 or 4 of this appendix. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 or 4 of this appendix, whether or not they are listed.

A.2.2 Government documents.

A.2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

COMMERCIAL ITEM DESCRIPTIONS

A-A-59004	-	Anti-Galling Compound, Thread Lubricating, Seizing Resistant, and Calcium Hydroxide Containing

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-F-24704/5	-	Flanged, Four Bolt, Insert Sleeves for Hydraulic Systems
MIL-I-45932	-	Inserts, Screw Thread Thin Wall, Locked In

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or https://assist.daps.dla.mil.)

A.2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

NAS1351	-	Screw, Cap, Socket Head, Undrilled and Drilled, Plain and Self-Locking, Alloy Steel, Corrosion-Resistant Steel and Heat-Resistant Steel, UNRF-3A
NASM7838	-	Bolt, Internal Wrenching, 160 KSI, FTU
NASM8846	-	Inserts, Screw Thread, Helical Coil

(Copies of these documents are available from Aerospace Industries Association, 1000 Wilson Boulevard, Suite 1700, Arlington, VA 22209-3901 or online at www.aia-aerospace.org.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

SAE INTERNATIONAL

SAE-AMS7276	-	Rings, Sealing, Fluorocarbon (FKM) Rubber High-Temperature-Fluid Resistant Low Compression Set 70 to 80
SAE-AS3209	-	Packing, Preformed-AMS 7276, 'O' Ring

(Copies of these documents are available from SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001 or online at www.sae.org.)

A.2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

A.3. INTERFACE CONNECTION

A.3.1 Interface connection. The interface configurations or cavities for the flanges covered by this specification are identified on figure A-1.




FIGURE A-1. Machining dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.

Unless otherwise specified herein:

- Surface roughness should not exceed 125 microinches.
- Tolerances should be:

  .XXX ±0.015

  .XX ±0.03

- Break edges and corners to 0.005 radius max.
- Threaded hole ("H" diameter) should have a 90-degree lead-in chamfer countersunk to "H" thread root diameter.

Flange code	Flange size (Sq)	A +0.002 -0.000	B +0.001 -0.001	C +0.010 -0.000	D +0.003 -0.003	E	F	G Max	H Thread size	J Min	K +0.005 -0.005
A	1.50	0.488	0.279	0.251	0.118	0.469	0.938	0.215	0.250-28UNF	0.500	0.010
B	1.75	0.688	0.439	0.251	0.153	0.562	1.125	0.375	0.312-24UNF	0.500	0.010
C	2.00	1.000	0.689	0.314	0.184	0.656	1.312	0.625	0.375-24UNF	0.500	0.010
D	2.25	1.188	0.876	0.314	0.184	0.750	1.500	0.812	0.438-20UNF	0.750	0.010
E	2.75	1.438	1.064	0.377	0.247	0.938	1.875	1.000	0.438-20UNF	0.750	0.010
F	3.50	2.125	1.564	0.502	0.311	1.250	2.500	1.500	0.500-20UNF	1.250	0.010
G	4.25	2.375	1.814	0.502	0.311	1.531	3.062	1.688	0.625-18UNF	1.625	0.010

FIGURE A-1. Machining dimensions – Continued.

A.3.1.1 Bolt thread engagement for steel. The recommended bolt thread engagement for steel-based materials that do not require threaded inserts is approximately 1.5 times the bolt diameter unless otherwise required by engineering analysis or applicable specification.


A.3.1.2 Bolt thread engagement for aluminum. Guidance for determining bolt thread engagement for aluminum alloy based materials that require threaded inserts is provided by NASM8846 for standard inserts or MIL-I-45932 for thin-wall-inserts. However, if lower torque values can be utilized because the full tensile strength of the fastener is not required for a specific application, it is not necessary to use the longer length threaded inserts that would be required for use with the higher tensile strength and higher torque values. As a minimum, the insert length selected should not result in tensile failure in parent or tapped material assuming a tensile load that is 135 percent of the worst case in-service load on the insert. The in-service load on the insert may be due to a combination of (1) the fastener being tightened to an applicable assembly drawing torque value and (2) the application of system pressure or other external loading on the flange.

A.4. ASSEMBLY INSTRUCTIONS

A.4.1 Assembly instructions. Assembly should be as shown on figure A-2. The selection of the O-ring and sleeve should be made from figure A-2.

A.4.2 Fasteners. The recommended fasteners are socket head cap screws in accordance with Heat-Resistant Steel (UNS S66286) in accordance with NAS1351 or internal wrenching bolts in accordance with NASM7838. The length of the cap screw is determined by adding the thickness of the flange and washer (if required) to the minimum thread engagement as determined in A.3.1.1 or A.3.1.2 then selecting the nearest standard cap screw size. Fasteners should be safety wired or lock wired and lubricated using a general purpose thread lubricant, such as A-A-59004.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.



Flange code [1/]	Flange size	O-ring SAE-AS3209	Sleeve code [2/]
A	1.50	AS3209-012	A
B	1.75	AS3209-112	B
C	2.00	AS3209-210	C
D	2.25	AS3209-213	D
E	2.75	AS3209-217	E
F	3.50	AS3209-327	F
G	4.25	AS3209-392	G

NOTES:
[1/] From figure A-1
[2/] From MIL-F-24704/5

FIGURE A-2. O-ring and sleeve selection guide.

Preparing Activity:
Navy – SH
(Project 4810-2011-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:08Z
Check the source to verify that this is the current version before use.