INCH-POUND

MIL-D-24693(SH)
AMENDMENT 1
2 April 1993

MILITARY SPECIFICATION

DEHYDRATOR, CONDENSER-FILTER, LOW PRESSURE AIR,
FOR SPECIAL APPLICATIONS

This amendment forms a part of MIL-D-24693, dated 23 November 1987, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Add the following specifications:

"MIL-L-3661	- Lampholders, Indicator Lights, Indicator-Light Housings, and Indicator-Light Lenses, General Specification for.
MIL-L-3661/65	- Lampholder, Lights, Indicator (Housing), Style LH98.
MIL-T-55164	- Terminal Boards, Molded, Barrier Screw and Stud Types, and Associated Accessories, General Specification for."

Delete the following specification:

"MIL-C-2212	- Contactors and Controllers, Electric Motor AC or DC, and Associated Switching Devices."

PAGE 3

2.1.2: Delete "9000-S6202-F-73907 - Light, Indicator, Switchboard 2 Lamp, SPF, Types B-27A through B-27G."

PAGE 6

3.6.3.1, Line 2: After "Air" insert "and water".

PAGE 7

3.6.6.4, Line 2: Delete "MIL-C-2212" and substitute "MIL-T-55164".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:01Z
Check the source to verify that this is the current version before use.

PAGE 8

3.6.7.3, Line 3: Delete "in accordance with type B27A of Drawing 9000-S6202-F-73907" and substitute "style LH98 in accordance with MIL-L-3661 and MIL-L-3661/65".

PAGE 9

3.6.8: Delete sub-elements "(a)" and "(b)" entirely.

3.6.9, Line 8: Delete "maximum".

3.6.9, Line 9: Delete "during dehydrator startup" and substitute "each time an alarm condition is reached".

3.6.9: Delete last sentence entirely.

3.6.10(d): Delete "Alarm interlock disconnect switch" (two places) and substitute "Compressor interlock switch".

3.6.10(e): Delete and substitute:

"(e) Audible alarm switch: The audible alarm switch shall silence the audible high discharge air temperature alarm when in the "OFF" position."

3.6.10(f): Delete sub-element "(f)" entirely.

PAGE 12

3.8.4: Delete and substitute:

"3.8.4 Piping connections. Air union connections shall be 1½ inch IPS pipe size and water union connections shall be ¼ inch IPS pipe size. Connections shall be located as specified (see 6.2.1)."

PAGE 15

4.7, Line 2: Delete "4.7.7" and substitute "4.7.8".

4.7.3, Line 2: Delete "3000" and substitute "1000".

Review activity:
DLA - CS

Preparing activity:
NAVY - SH
(Project 4440-N064)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:01Z
Check the source to verify that this is the current version before use.