
FED SUP CLASS
5930




Ⓓ Denotes changes

APPROVED 16 Dec 1969 REVISED Ⓐ 15 Sep 1970 Ⓑ 15 May 1972 Ⓒ 25 Apr 1975 Ⓓ 28 Sep 1987

User activity: Air Force - 11

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

| | | | |
|---|---|---|---|
| P A<br>Air Force - 85<br>Other Cust<br>Army - ER<br>Navy - AS | International interest | TITLE<br>SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED, SOLDER TERMINAL | MILITARY STANDARD<br>MS27736 |
| Procurement Specification<br>MIL-S-3950 | | SUPERSEDES | PAGE 1 OF 3 |

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5930-1358-16

AMSC N/A

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.

| Inches | mm | Inches | mm |
|---|---|---|---|
| .008 | 0.20 | .37 | 9.4 |
| .012 | 0.30 | .38 | 9.7 |
| .015 | 0.38 | .432 | 10.97 |
| .03 | 0.8 | .469 | 11.91 |
| .076 | 1.93 | .47 | 11.9 |
| .090 | 2.29 | .69 | 17.5 |
| .130 | 3.30 | 1.340 | 34.04 |
| .19 | 4.8 | 1.370 | 34.80 |
| .240 | 6.10 | 1.660 | 42.16 |
| .25 | 6.4 | | |

NOTES:
1. Dimensions are inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.020 (0.51 mm) for two place decimals and ±.005 (0.13 mm) for three place decimals.
(D) 4. For hardware detail specifications, see appendix of MIL-S-3950.
5. All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever.
6. Maximum weight is 0.20 pound.
(D) 7. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
(D) 8 Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

For change see page 2

APPROVED 16 Dec 1969 REVISED (D)

User activity: Air Force - 11

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

| | | | |
|---|---|---|---|
| P A<br>Air Force - 85<br>Other Cust<br>Army - ER<br>Navy - AS | International interest | TITLE<br>SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED, SOLDER TERMINAL | MILITARY STANDARD<br>MS27736 |
| Procurement Specification<br>MIL-S-3950 | | SUPERSEDES | PAGE 2 OF 3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

User activity: Air Force - 11

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Procurement Specification MIL-S-3950

SUPERSEDES

P A
Air Force - 85
Other Cust
Army - ER
Navy - AS

International Interest

TITLE
SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED, SOLDER TERMINAL

MILITARY STANDARD
MS27736

PAGE 3 OF 3

FED SUP CLASS 5930

Detail requirements:

| MS part number | Circuit with toggle lever in | | | Current capacity (amperes) 28 volts dc | | | Current capacity (amperes) 115 volts, 60 and 400 hertz ac | | |
|---|---|---|---|---|---|---|---|---|---|
| | Keying side | Center | Opposite keying side | Lamp-load circuit | Resistive circuit | Inductive circuit | Lamp-load circuit | Resistive circuit | Inductive circuit |
| MS27736-1 | 1-2 4-5<br>7-8 On 10-11 | 2-3 4-5<br>7-8 On 11-12 | 2-3 5-6<br>8-9 On 11-12 | 5 | 20 | 12 | 4 | 15 | 15 |
| MS27736-2 | 1-2 Mom. 4-5<br>7-8 on 10-11 | 2-3 4-5<br>7-8 On 11-12 | 2-3 5-6<br>8-9 On 11-12 | | | | | | |
| MS27736-3 | 1-2 Mom. 4-5<br>7-8 on 10-11 | 2-3 4-5<br>7-8 On 11-12 | 2-3 Mom. 5-6<br>8-9 on 11-12 | 4 | 18 | 10 | 2 | 11 | 8 |
| MS27736-21 | 1-2 7-8<br>4-5 On 10-11 | Off | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-22 | Off | None | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-23 | 1-2 7-8<br>4-5 On 10-11 | None | 2-3 8-9<br>5-6 On 11-12 | 5 | 20 | 12 | 4 | 15 | 15 |
| MS27736-24 | None | Off | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-25 | None | Mom. off | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-26 | 1-2 Mom. 7-8<br>4-5 on 10-11 | None | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-27 | 1-2 Mom 7-8<br>4-5 on 10-11 | Off | 2-3 Mom. 8-9<br>5-6 on 11-12 | | | | | | |
| MS27736-28 | 1-2 Mom. 7-8<br>4-5 on 10-11 | Off | None | | | | | | |
| MS27736-29 | Mom. off | None | 2-3 8-9<br>5-6 On 11-12 | 4 | 18 | 10 | 2 | 11 | 8 |
| MS27736-30 | 1-2 Mom. 7-8<br>4-5 on 10-11 | None | Off | | | | | | |
| MS27736-31 | 1-2 Mom. 7-8<br>4-5 on 10-11 | Off | 2-3 8-9<br>5-6 On 11-12 | | | | | | |
| MS27736-32 | None | 1-2 7-8<br>4-5 On 10-11 | 2-3 Mom. 8-9<br>5-6 on 11-12 | | | | | | |
| MS27736-33 | None | 1-2 7-8<br>4-5 On 10-11 | 2-3 8-9<br>5-6 On 11-12 | 5 | 20 | 12 | 4 | 15 | 15 |

APPROVED 16 Dec 1969 REVISED (D) For change see page 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.