INCH-POUND


MS51525D
30 September 2021
SUPERSEDING
MS51525C
w/AMENDMENT 1
16 December 2019

DETAIL SPECIFICATION SHEET

FITTINGS, HYDRAULIC TUBE, FLARED 37 DEGREE AND FLARELESS, STEEL; ADAPTER, STRAIGHT, TUBE TO BOSS, O-RING, 37 DEGREE FLARED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-18866.



See notes at end of figure.

FIGURE 1. Adapter, tube to boss, O-ring, flared.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

Suffix designator		Tube OD nom.	A (See Note 10)	B (See Note 10)	C_1 Hex flat Nom. (see note 8)
Assembly	Body (see note 6)				
A2	B2	.1250 (3.175)	.3125-24 UNF-2A	.3125-24 UNF-2A	7/16
A3	B3	.1875 (4.763)	.3750-24 UNF-2A	.3750-24 UNF-2A	1/2
A4	B4	.2500 (6.350)	.4375-20 UNF-2A	.4375-20 UNF-2A	9/16
A4-5	B4-5	.2500 (6.350)	.5000-20 UNF-2A	.4375-20 UNF-2A	5/8
A4-6	B4-6	.2500 (6.350)	.5625-18 UNF-2A	.4375-20 UNF-2A	11/16
A5	B5	.3125 (7.938)	.5000-20 UNF-2A	.5000-20 UNF-2A	5/8
A6	B6	.3750 (9.525)	.5625-18 UNF-2A	.5625-18 UNF-2A	11/16
A6-8	B6-8	.3750 (9.525)	.7500-16 UNF-2A	.5625-18 UNF-2A	7/8
A8	B8	.5000 (12.700)	.7500-16 UNF-2A	.7500-16 UNF-2A	7/8
A8-10	B8-10	.5000 (12.700)	.8750-14 UNF-2A	.7500-16 UNF-2A	1
A8-12	B8-12	.5000 (12.700)	1.0625-12 UN-2A	.7500-16 UNF-2A	1 1/4
A10	B10	.6250 (15.875)	.8750-14 UNF-2A	.8750-14 UNF-2A	1
A10-12	B10-12	.6250 (15.875)	1.0625-12 UN-2A	.8750-14 UNF-2A	1 1/4
A12	B12	.7500 (19.050)	1.0625-12 UN-2A	1.0625-12 UN-2A	1 1/4
A12-16	B12-16	.7500 (19.050)	1.3125-12 UN-2A	1.0625-12 UN-2A	1 1/2
A14	B14	.8750 (22.225)	1.1875-12 UN-2A	1.1875-12 UN-2A	1 3/8
A14-16	B14-16	.8750 (22.225)	1.3125-12 UN-2A	1.1875-12 UN-2A	1 1/2
A16	B16	1.0000 (25.400)	1.3125-12 UN-2A	1.3125-12 UN-2A	1 1/2
A16-12	B16-12	1.0000 (25.400)	1.0625-12 UN-2A	1.3125-12 UN-2A	1 3/8
A16-20	B16-20	1.0000 (25.400)	1.6250-12 UN-2A	1.3125-12 UN-2A	1 7/8
A20	B20	1.2500 (31.750)	1.6250-12 UN-2A	1.6250-12 UN-2A	1 7/8
A24	B24	1.5000 (31.750)	1.8750-12 UN-2A	1.8750-12 UN-2A	2 1/8
A32	B32	2.0000 (50.800)	2.500-12 UN-2A	2.500-12 UN-2A	2 3/4

See notes at end of figure.

FIGURE 1. Adapter, tube to boss, O-ring, flared - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

Suffix designator		D diameter		I ±.005 (0.13) inches (mm)	L ±.020 (0.51) inches (mm)
Assembly	Body (see note 6)	Basic inches (mm)	Tolerance inches (mm)		
A2	B2	.062 (1.57)	±.003 (0.08)	.297 (7.54)	1.060 (26.92)
A3	B3	.125 (3.18)		.297 (7.54)	1.100 (27.94)
A4	B4	.172 (4.37)		.360 (9.14)	1.230 (31.24)
A4-5	B4-5	.172 (4.37)		.360 (9.14)	1.230 (31.24)
A4-6	B4-6	.172 (4.37)		.391 (9.93)	1.290 (32.77)
A5	B5	.234 (5.94)		.360 (9.14)	1.230 (31.24)
A6	B6	.297 (7.54)	±.004 (0.10)	.391 (9.93)	1.300 (33.02)
A6-8	B6-8	.297 (7.54)		.438 (11.13)	1.380 (35.05)
A8	B8	.391 (9.93)		.438 (11.13)	1.480 (37.59)
A8-10	B8-10	.391 (9.93)		.500 (12.70)	1.600 (40.64)
A8-12	B8-12	.391 (9.93)		.594 (15.09)	1.760 (44.70)
A10	B10	.484 (12.29)		.500 (12.70)	1.700 (43.18)
A10-12	B10-12	.484 (12.29)		.594 (15.09)	1.860 (47.24)
A12	B12	.609 (15.47)	±.005 (0.13)	.594 (15.09)	1.970 (50.04)
A12-16	B12-16	.609 (15.47)		.594 (15.09)	1.990 (50.55)
A14	B14	.718 (18.24)		.594 (15.09)	1.990 (50.55)
A14-16	B14-16	.718 (18.24)		.594 (15.09)	2.020 (51.31)
A16	B16	.844 (21.44)	+.007 -.005 (0.18 - .013)	.594 (15.09)	2.040 (51.82)
A16-12	B16-12	.844 (21.44)		.594 (15.09)	2.040 (51.82)
A16-20	B16-20	.844 (21.44)		.594 (15.09)	2.120 (53.85)
A20	B20	1.078 (27.38)	+.008 -.005 (+0.20 -0.13)	.594 (15.09)	2.170 (55.12)
A24	B24	1.312 (33.32)		.594 (15.09)	2.370 (60.20)
A32	B32	1.781 (45.24)	+.010 -.005 (+0.25 -.013)	.594 (15.09)	2.780 (70.61)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Break all sharp edges; remove all burrs and slivers.
4. Dimensions and tolerances not shown shall be in accordance with SAE-J514 for 37° flared fittings.
5. The drawing is for identification purposes only and is not intended to restrict designs and shapes not dimensioned.
6. Assemblies are only furnished to this specification (body, nuts, and sleeves). Bodies are not to be stocked, stored, or issued.
7. Procure O-ring separately and install before installation of the fittings.
8. Across flat widths shall fit standard wrench openings, see ASME B18.2.2.
9. Outer Diameter is abbreviated as (OD).
10. ASME B1.1 - Unified Inch Screw Threads (UN and UNR Thread Forms)

FIGURE 1. Adapter, tube to boss, O-ring, flared – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Fittings shall be as specified on figure 1.

O-rings shall not be furnished with the fittings (See Note 7).


Materials shall be in accordance with MIL-DTL-18866

Finish and finish designators shall be in accordance with MIL-DTL-18866.

Unless otherwise specified in MIL-DTL-18866, all plating's shall be capable of meeting 96-hour salt spray test in accordance with ASTM B117. The fittings shall show no evidence of red corrosion after 96 hours of salt spray. Fluid passages, other openings, and internal threads shall not be subject to the plating thickness requirement and may have bare areas provided they are protected with a light film of oil.

Maximum operating pressure shall be in accordance with SAE-J514.

PIN: The PIN consists of the letters "MS", the specification number, a letter and number for adapter size, and a letter for material finish designator.



PIN example: MS51525A10N indicates an adapter, tube to boss, .6250 inch (15.875 mm), high-chromium nickel alloy.

Marking shall be in accordance with MIL-DTL-18866.

Class I and II ozone depleting substances (ODS) shall not be used in MS51525 or any referenced procedures.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

NOTE: The following restrictions do not apply to manufacturers of the fittings and is applicable only to OEM's and users.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Army and Marine ground forces zinc plating's. PIN codes FC, FD, Z, and ZC finishes have a chromate conversion coating which includes hexavalent chromium and are not recommended for Army and Marine ground systems. The use of coatings depositing hexavalent chromium for Army vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement. For new designs PIN codes FC, FD, Z, and ZC are not to be supplied to Army and Marine ground forces. MIL-PRF-32647 Type KA is intended as a hazardous free plating material and is a direct replacement for zinc plating with a hexavalent chromium conversion coating. KA has an equivalent torque/tension as the plating's replaced.

Army and Marine ground vehicles. The use of cadmium plating for Army and Marine ground vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement.

Army ground vehicle applications cadmium plating. Pin code J or KB may be substituted for cadmium ("Blank" PIN code) for Army ground vehicle applications. MIL-PRF-32647 Type KB is intended as a hazardous free plating material and is a direct replacement for cadmium plating ("Blank" PIN code). KB has an equivalent torque/tension as cadmium.

NAVSEA shipboard owned equipment. Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-18866, this document references the following:

MIL-PRF-32647	ASME B18.2.2
MS51531	ASTM B117
MS51533	SAE-J514
ASME B1.1	T9070-AL-DPC-020/077-2

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 71
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2021-026)

Review activities:
Army - AR, MI
Navy - AS, CG, MC, SA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.