
This military standard is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FED. SUP CLASS
2320



NOTES:
1. DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR ENGINEERING REFERENCE ONLY.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
3. THIS VEHICLE SHALL BE IN ACCORDANCE WITH REFERENCED ENGINEERING DRAWINGS, COPIES WHICH MAY BE OBTAINED FROM: US ARMY TANK-AUTOMOTIVE COMMAND, WARREN, MICH. 48090.

APPROVED 8 MAY 85 REVISED

MS PART NO.	ENGINEERING DRAWING NO.	DESCRIPTION
MS 52165-1	8736905	LESS WINCH

P.A. ARMY-AT Other Cust	TITLE TRUCK, UTILITY, 1/4 TON 4x4, M151A2	MILITARY STANDARD MS52165(AT)
PROCUREMENT SPECIFICATION MIL-T-45331	SUPERSEDES:	SHEET 1 OF 2

DD FORM 672-1 LIMITED COORDINATION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:21Z
Check the source to verify that this is the current version before use.

VEHICLE CHARACTERISTICS

FED. SUP CLASS 2320

WEIGHT, CURB FULLY EQUIPPED, LESS PAYLOAD AND PERSONNEL:
FRONT AXLE 1362 LBS
REAR AXLE 1078 LBS
TOTAL 2440 LBS
NOTE: ADD 400 LBS FOR TWO MAN CREW

GROSS LOAD, LOADED: 800 LBS

TOWED LOAD ALLOWANCE, LOADED: 1070 LBS

SHIPPING DIMENSIONS:
CU. FT. 350.0 REDUCIBLE TO 260.0
SQ. FT. 59.0
LENGTH 132-11/16 IN.
WIDTH 64-5/16 IN.
HEIGHT 71 IN. REDUCIBLE TO 52-1/2IN.

CENTER OF GRAVITY (AT CURB WEIGHT):
ABOVE GROUND - 23-15/16 IN.
REAR OF CENTERLINE OF FRONT AXLE - 37-1/2 IN.

CENTER OF GRAVITY (W/PAYLOAD):
ABOVE GROUND - 25-5/8 IN.
REAR OF CENTERLINE OF FRONT AXLE - 48-1/2 IN.

TREAD: FRONT 53 IN., REAR 53 IN.

CAB TO REAR AXLE N.A.: 20-7/16 IN.

MINIMUM GROUND CLEARANCE: REAR AXLE 11-3/8 IN.*UNDER CHASSIS 9-7/16 IN. **
*AT FULL PAYLOAD WEIGHT **AT REAR SHOCK BRACKET

ANGLE OF APPROACH: 66°

ANGLE OF DEPARTURE: 37°

RAMP BREAKOVER ANGLE: 43°

MINIMUM TURNING DIA: LEFT 38-1/2 FT.
(WALL TO WALL) RIGHT 38-1/2 FT.
*OUTERMOST POINT - FRONT FENDER

FORDING DEPTH: WITH KIT 60 IN.
LESS KIT 21 IN.

ENGINE: TYPE-GASOLINE, LIQUID COOLED OHV; DISPLACEMENT - 141.5 CU. IN., BORE AND STROKE - 3-7/8 X 3.00; COMPRESSION RATIO-7.5:1; FUEL - REGULAR GRADE, 91 RON MINIMUM (REASEARCH OCTANE NUMBER); LUBRICATION - WET SUMP; CRANKCASE CAP. - 5 QTS. DRY - 4 QTS. REFILL; GOVERNOR- NONE, COOLING SYSTEM CAP. - 9 QTS. PUMP DRIVE V-BELT. (PRE-EMISSION) 11660425
HORSEPOWER - MAX. GROSS 71 @ 4000 RPM; MAX. NET 61 @ 3600 RPM.
TORQUE MAX. GROSS 128 LB-FT@ 1800 RPM; MAX. NET 119 LB-FT @ 1700 RPM.
11613729
-73/74 EMISSION ENGINE
HORSEPOWER - MAX. GROSS 65 @ 4000 RPM; MAX. NET 55 @ 3600 RPM.
TORQUE MAX. GROSS 113 LB-FT@ 1800 RPM; MAX NET 104 LB-FT. @ 2000 RPM.

STEERING: 11639799
TYPE - WORM & DOUBLE ROLLER; RATIO - 16.4 TO 1; POWER ASSIST - NONE.

ELECTRICAL SYSTEM: WATERPROOF - YES; RADIO SUPPRESSED PER MIL-STD-461; POTENTIAL - 24 VOLT; STARTING MOTOR - 7017646
ALTERNATOR 10929868
RATING - 60 AMPERES; DRIVE - V-BELT;
BATTERY - MS35000-1;
TYPE -2HN; QUANTITY - 2; COIL 11663066

PINTLE HOOK: CAPACITY 8380198 2000 LBS

ACCESSORY KITS: 12302575

BASIC ISSUE ITEMS DRAWING NO. 12300877-5

SERVICE BRAKES: TYPE - DUO-SERVO SINGLE ANCHOR; DRUM SIZE - 9-1/8 X 2 IN. FRONT & REAR; EFFECTIVE AREA - 115 SQ. IN. FRONT & REAR; ACTUATION - HYDRAULIC; SINGLE BRAKE LINES; 60% FRONT - 40% REAR.

PERFORMANCE: MI. PER GAL - 19.1 WITH 800 LB PAYLOAD SPEED - 56 MPH; GRADEABILITY - 4TH GEAR 6.5% FOR GVW OF 3240 LBS
1ST GEAR 60% FOR GVW AT 3240 LBS
CRUISING RANGE 300 MI

WINCH: NONE

TIEDOWNS: NO. -4; LOCATION - 2 @ FRONT BUMPER; 2 @ REAR SILL.

FUEL SYSTEM: CARBURETOR (EMISSION CARB.) 11681709
TYPE - SIDE DRAFT; FUEL PUMP - 11640994
TYPE - MECHANICAL; FUEL CAPACITY 15.8 GALS

CLUTCH: 11669136
TYPE - SINGLE DRY DISC.; DIA. - 8-7/16 IN.
EFFECTIVE AREA - 68.11 SQ. IN.

TRANSMISSION: 7536199
NO OF SPEEDS -4 FWD. & 1 REV.; RATIOS - 1ST 5.172, 2ND 3.179 3RD 1.674 4TH 1.0, REV. 7.497: PTO OPENINGS - NONE; LUBRICANT CAPACITY - 5.5 PTS. INCLUDING TRANSFER CASE.

TRANSFER CASE: 10885542
(INTEGRAL WITH TRANSMISSION): SINGLE SPEED RATIO - 1:1, CONTROL OF FRONT AXLE DRIVE SPLINED COLLAR WITH SPRING LOADED FORK; LUBRICANT CAPACITY - (SEE TRANSMISSION) PTS.

FRONT & REAR DIFFERENTIAL: 7536140
TYPE - SUSPENDED CARRIER WITH CARDAN JOINTS; RATIO - 4.86 : LUBRICANT CAPACITY- 1 QT.

FRAME: TYPE - UNIT BODY & FRAME; NO OF CROSSMEMBERS - 4; SECTION MODULUS - VARIABLE; DIMENSIONS - MAIN RAIL 7-7/8 X 1-3/4 X 1/16 IN.; REINFORCED - YES.

FRONT SUSPENSION: TYPE - COIL SPRING: 5/8 WIRE; 4 IN DIA., 11 IN. FREE LENGTH; NO. COILS - 8: RATE - 513 ± 16 LB/IN.; SHOCK ABSORBERS - TELESCOPIC.

REAR SUSPENSION: TYPE - COIL SPRING; 9/16 WIRE; 3-13/16 IN. DIA., 12-7/8 IN. FREE LENGTH NO. COILS - 9-1/8 ; RATE - 337 ± 15 LB IN.; SHOCK ABSORBERS - TELESCOPIC:

WHEELS: 10921860
TYPE - DROP CENTER; DIA. - 16 IN.; BEAD - LOCK - HUMP TYPE; SINGLE REAR - YES: RIM SIZE - 5-1/2 IN.

TIRES: TYPE - LIGHT TRUCK; SIZE - 7.00 X 16; PLY - 4 (6 PLY RATING); LOAD RANGE C; TREAD - NON-DIRECTIONAL, CROSS COUNTRY; NO. SPARES - 1.

PARKING BRAKES: 8754237
TYPE - EXTERNAL BAND ON TRANSMISSION OUTPUT SHAFT; DRUM SIZE - 6 IN. DIA. X 1 IN. WIDE; EFFECTIVE AREA - 15.6 SQ. IN.

LIGHTING: HEADLAMPS - 8741462
B.O. DRIVING LAMP - 8747988
TRAILER COUPLING SOCKET - 8712356
COMPOSITE LIGHT, FRONT - 11614156
COMPOSITE LIGHT, TAIL - 11614157
TURN SIGNALS, FLASHER TYPE; CONTROL UNIT 11613532
FLASHER 11613631

OVE DRAWING NO. 12300998-4

MS PART NO.	ENGINEERING DRAWING NO.
MS 52165-1	8736905

APPROVED 8 MAY 85 REVISED

P.A. ARMY-AT Other Cust	TITLE TRUCK, UTILITY, 1/4 TON 4x4, M151A2	MILITARY STANDARD MS52165(AT)
PROCUREMENT SPECIFICATION MIL-T-45331	SUPERSEDES:	SHEET 2 OF 2

DD FORM 1 SEP 87 672-1 LIMITED COORDINATION

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:21Z
Check the source to verify that this is the current version before use.