MILITARY SPECIFICATION

BALLISTICS COMPUTER SUBASSEMBLY: 8635273 (CONTROL UNIT)

This amendment forms a part of Military Specification MIL-B-60119(MU), dated 28 May 1964.

Paragraph 2.1, specifications: Delete "MIL-I-45208, Inspection System Requirements".

* Paragraph 3.4.1: Delete last sentence.

Paragraph 3.4.3: Delete and substitute:

"3.4.3 Sealing.- When pressurized to an internal pressure of 5 ± 0.1 psig, the control unit shall not exhibit a pressure drop greater than 0.2 psig for a period of at least 2 minutes."

Add the following paragraph:

"3.4.4 Storage temperature.- The unit shall show no evidence of physical failure and shall meet all requirements of this specification at standard ambient temperature of 60° to 90°F after having been exposed to and thermally stabilized at ambient temperature of -80°F and +160°F."

Paragraph 3.5.2: Delete "plus twice the rated voltage".

Paragraph 4.4.1 "General provisions": Delete and substitute:

"4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109."

Add new paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2 as follows:

* 4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) control units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.2.2, Table I: Add the following characteristics:

| | | | |
|---|---|---|---|
| "105. | Sealing | 3.4.3 | 4.5.1.3 |
| 106. | Dielectric strength | 3.5.2 | 4.5.3 |
| 107. | Insulation resistance | 3.5.3 | 4.5.4" |

* Paragraph 4.3: Delete "control tests" and substitute "special sampling".

* Paragraph 4.3.1, last sentence: Delete "control"; in the tabulation heading delete "Control test" and substitute "Characteristic".

* Paragraph 4.3.2: Delete second sentence and substitute: "Each sample shall meet the following requirements and tests, and shall then meet the requirements and tests in Table I; Delete tabulation and substitute:

| "Characteristic | | Requirement | Test Procedure |
|---|---|---|---|
| 304. | Storage temperature (-80°F and +160°F) | 3.4.4 | 4.5.1.4 |
| 305. | Switch operation | 3.4.1, 3.6.1 | 4.5.1.1, 4.5.5.1 |
| 306. | Switch lens illumination | 3.4.1, 3.6.2 | 4.5.1.1, 4.5.5.2 |

NOTE: The tests for Characteristics 305 and 306 shall be conducted at -40° and +150°F."

* Paragraph 4.3.3: Delete and substitute:

"4.3.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and resubmitted items have been approved (see 4.2.3)."

Paragraph 4.4, first sentence: Delete "Measuring and Test Equipment of Specification MIL-I-45208 and all".

* Paragraph 4.5.1.2: Delete last sentence and substitute:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

"The control unit shall then be subjected to the tests specified in Table I to determine conformance with the applicable requirement referenced therein."

Paragraph 4.5.1.3: Delete and substitute:

"4.5.1.3 Sealing.- The pressure test equipment utilized for this test shall be capable of internally pressurizing the control unit to the psig value specified. The pressure gauge of the test equipment shall permit measuring any variation in the internal pressure in increments of 0.1 psig. Remove the Plug MS-49005-1 from the side of the control unit and replace it with an air valve containing a spring loaded valve stem. The pressure shall be applied to the control unit through this valve. Pressurize the control unit with clean dry air to the psig value specified in 3.4.3. The applied pressure shall be retained for a minimum of 2 minutes. Any evidence of leakage in the control unit at the end of the 2 minute time period shall not exceed the tolerance specified in 3.4.3, as measured on the pressure gauge of the testing equipment. Upon completion of this test, remove the air valve and replace the Plug MS-49005-1 in the control unit."

Add the following paragraph:

"4.5.1.4 Storage temperature.- The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.4.4. The control unit shall be exposed to each temperature extreme specified in 3.4.4 for a minimum of 5 hours. After each temperature exposure the control unit shall be stabilized in an ambient temperature between 60° and 90°F and subjected to a visual, tactile and audible examination for evidence of physical failure. The control unit shall then be subjected to the tests in 4.5.1.1 through 4.5.5.2 inclusive to determine conformance to 3.4.4. Caution shall be exercised during the temperature cycling to avoid subjecting the control unit to thermal shock."

Paragraph 4.5.2: Delete "Drawing D8635307" and substitute "Drawing C8635249".

Paragraph 4.5.4: Delete "MIL-STD-102" and substitute "MIL-STD-202".

*The outside margins have been marked to indicate where additions to the privious amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A085



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.