INCH-POUND

MIL-K-63185 (AR)
AMENDMENT 2
10 September 1989
SUPERSEDING
AMENDMENT 1
27 May 1986

MILITARY SPECIFICATION

KIT, CONVERSION
H4277/H4272 EXTRACTOR TOOL
M753 PROJECTILE

This amendment forms a part of Military Specification MIL-K-63185 (AR) dated 25 June 1982, and is approved for use within the US Army Armament, Munition and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

*2.1.1, Under Standards, Military:

Add: "MIL-STD-1949 Inspection, Magnetic Particle"

PAGE 3

*2.2 Delete: "ASTM E138 Method for Wet Magnetic Particle Inspection"

PAGE 4

3.4.1 Delete entirely and substitute:

"3.4.1 Life cycle tensile strength. With the forcing cone end of the extraction tool subassembly restrained, the extraction tool subassembly shall withstand a tensile force of 54,000 lb ± 10% on the opposite rod end for 25 cycles at 70° ± 20°F without breakage, cracking, distortion or any other evidence of physical damage. Testing shall be performed in accordance with the applicable conditions of 4.5.2."

PAGE 14

* 4.4.2.3 Change as follows:

Major CD 138, Delete: "ASTM E138"
Substitute: "MIL-STD-1949"

AMSC N/A FSC 1110
DISTRIBUTION STATEMENT A. Approved for public release; distibution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:23Z
Check the source to verify that this is the currenversion before use.

PAGE 23

4.5.2 Delete entirely and substitute:

"4.5.2 Tensile strength (see 3.4). Dwg. 9312672 illustrates the actual use of the extraction tool subassembly. However, for test purposes the tensile strength test may be performed horizontally or vertically. The forcing cone end of the extraction tool subassembly shall be fully expanded in an approved and restrained test fixture simulating the internal dimensional characteristics of an M753 rocket motor boattail (see dwg. 9299050). In assembling the extractor tool subassembly into the fixture care should be exercised to assure that the bearing plate force of the subassembly presses tightly and evenly around the face of the test fixture and the jaws press evenly against the internal simulated boattail taper without tilting or cocking as the extraction tool subassembly jaws are expanded. The boattail simulation test fixture shall be designed by the contractor to withstand all the tensile forces required by this specification at the loads specified. The boattail simulation fixture or parts thereof may be expendable but the contractor shall provide sufficient test fixtures to perform all of the tensile strength test required at the specified loads (first article and quality conformance tensile strength screening test). Approval by the Government of the contractor designed and furnished test fixtures (AIE) shall not relieve the contractor of responsibility for successfully complying with all the requirements of this specification and providing tooling and fixtures capable of fully and successfully performing all the test required herein. An H4277 mating rod (dwg. 9312541) furnished by the acquiring activity shall be threaded onto the forward rod end of the subassembly and secured with a retaining bolt. An approved forcing mechanism shall be secured to the mating rod. With the test fixture and the forcing cone end of the extraction tool subassembly restrained, the applicable tensile force indicated below shall be exerted on the mating rod end, retained for ten seconds minimum, and released. The tensile load shall be repeated for the number of cycles indicated. After being subjected to the required number of cycles, the H4272 extraction tool subassembly shall be visually examined for the deficiencies cited in 3.4.1 and for evidence of physical damage, including inspection of the H4272 rod thread with approved thread gages."

First Article Life Cycle Test:
54000 lb ± 10% at 70° ± 20°F (25 cycles)

Quality conformance Tensile Strength Screening:
45000 lb ± 10% at 70° ± 20°F (3 cycles)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.

PAGE 25

* 6.3 Delete and substitute:

"6.3 Equipment design approval. Submit equipment designs, as required, to Commander U.S. Army Armament, Munitions and Chemical Command, ATTN: AMSMC-QAN-I(D), Picatinny Arsenal, NJ 07806-5000."

* NOTE: The margins of this amendment are marked with an asterisk or verticle lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army-AR

(Project 1110-A180)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:23Z
Check the source to verify that this is the current version before use.