INCH-POUND

MIL-PRF-55365/11B
23 October 2006
SUPERSEDING
MIL-PRF-55365/11A
3 November 2003

PERFORMANCE SPECIFICATION SHEET

*

CAPACITORS, CHIP, FIXED, TANTALUM, POLARIZED ESTABLISHED RELIABILITY, NON-ESTABLISHED RELIABILITY AND HIGH RELIABILITY, STYLES CWR19 AND CWR29

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-55365.




FIGURE 1. Style CWR19 and CWR29 (molded) capacitors.

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Case size	L ± .015 (0.38)	W ±.015 (0.38)	H ±.015 (0.38)	P +.010 (0.25) -.005 (0.13)	W_2	H_2 min
A	.100 (2.54)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±0.13)	.030 (0.76)
B	.150 (3.81)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±0.13)	.030 (0.76)
C	.200 (5.08)	.050 (1.27)	.050 (1.27)	.030 (0.76)	.050 ±.005 (1.27±0.13)	.030 (0.76)
D	.150 (3.81)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095+.005,-.010 (2.41+0.13, -0.25)	.030 (0.76)
E	.200 (5.08)	.100 (2.54)	.050 (1.27)	.030 (0.76)	.095+.005,-.010 (2.41+0.13, -0.25)	.030 (0.76)
F	.220 (5.59)	.135 (3.43)	.070 (1.78)	.030 (0.76)	.130±.005 (3.30±0.13)	.040 (1.02)
G	.265 (6.73)	.110 (2.79)	.110 (2.79)	.050 (1.27)	.105±.005 (2.67±0.13)	.060 (1.52)
H	.285 (7.24)	.150 (3.81)	.110 (2.79)	.050 (1.27)	.145+.005. -.020 (3.68+0.13, -0.51)	.060 (1.52)
X	.273 (6.93)	.213 (5.41)	.108 (2.74)	.047 (1.19)	.120 ± .005 (3.05 ± 0.13)	.048 (1.22)

NOTES:
1. Dimensions are in inches. Metric (millimeter) equivalents are given in parenthesis for general information only.
2. These capacitors are designed for mounting by dip soldering, thermo-compression bonding, reflow soldering, or other conventional means.
3. The anode (+) terminal shall be identified by a marking on the case.
4. The termination width (W_2) shall be maintained to the top of the solderable area.
5. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.
6. When solder coated terminations are required, add an additional .015 inch (0.38 mm) to the above listed tolerances for “L”, “W”, “H”, “P”, “W_2”, and H_2 for each case size.

FIGURE 1. Style CWR19 and CWR29 (molded) capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Termination finish: In accordance with termination finishes B, C, H, or K of MIL-PRF-55365.

DC rated voltage: See table I or table II. Above +85°C, voltage derating is required (see MIL-PRF-55365).

Operating temperature range: -55°C to +125°C.

Product level designator: In accordance with MIL-PRF-55365.

DC leakage (DCL): See table I or table II.

Capacitance: See table I or table II.

Capacitance tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I or table II.

Equivalent series resistance (ESR) at 100 kHz: In accordance with MIL-PRF-55365 (see table I or table II).

Resistance to soldering heat: In accordance with MIL-PRF-55365.

Stability at low and high temperatures: In accordance with MIL-PRF-55365.

Step 1 (+25°C):	DCL	-	See table I or table II.
	Capacitance	-	Shall not exceed tolerance of table I or table II value.
	DF	-	See table I or table II.
Step 2 (-55°C):	ΔCapacitance	-	Shall not exceed ±10 percent of initial measurement.
	DF	-	See table I or table II.
Step 3 (+25°C):	DCL	-	See table I or table II.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial +25°C measurement.
	DF	-	See table I or table II.
Step 4 (+85°C):	DCL	-	See table I or table II.
	ΔCapacitance	-	Shall not exceed ±10 percent of initial +25°C measurement.
	DF	-	See table I or table II.
Step 5 (+125°C):	DCL	-	See table I or table II.
	ΔCapacitance	-	Shall not exceed ±15 percent of initial +25°C measurement.
	DF	-	See table I or table II.
Step 6 (+25°C):	DCL	-	See table I or table II.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial +25°C measurement.
	DF	-	See table I or table II.

Surge voltage: In accordance with MIL-PRF-55365.

DCL	-	See table I or table II.
ΔCapacitance	-	Within ±5 percent of initial value.
DF	-	See table I or table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Life: Method 108 of MIL-STD-202.

2,000 hours:

At 25°C:	DCL	-	See table I or table II.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial measured value.
	DF	-	See table I or table II.
At 85°C:	DCL	-	See table I or table II.
At 125°C:	DCL	-	See table I or table II.

10,000 hours:

At 25°C:	DCL	-	200 percent of initial requirement.
	ΔCapacitance	-	Shall not exceed ±5 percent of initial measured value.
	DF	-	See table I or table II.
At 85°C:	DCL	-	200 percent of initial requirement.
At 125°C:	DCL	-	200 percent of initial requirement

Solderability will be in accordance with MIL-PRF-55365 except that following steam aging test samples may have a 30 minute bake out at 150°C prior to solder dipping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR19 characteristics.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR19C-335--A-	4	3.3	1	10	12	6	8	8	12	A
CWR19C-475--A-	4	4.7	1	10	12	6	8	8	12	A
CWR19C-685--A-	4	6.8	1	10	12	6	8	8	12	A
CWR19C-106--B-	4	10	1	10	12	8	10	10	8	B
CWR19C-156--B-	4	15	1	10	12	8	10	10	8	B
CWR19C-226--B-	4	22	1	10	12	8	10	10	8	B
CWR19C-226--D-	4	22	1	10	12	8	10	12	4	D
CWR19C-336--D-	4	33	2	20	24	8	10	12	4	D
CWR19C-336--E-	4	33	2	20	24	8	10	12	3	E
CWR19C-476--E-	4	47	2	20	24	8	10	12	3	E
CWR19C-686--E-	4	68	3	30	36	8	10	12	3	E
CWR19C-107--F-	4	100	4	40	48	10	12	12	2	F
CWR19C-157--G-	4	150	6	60	72	10	12	12	1	G
CWR19C-227--H-	4	220	8	80	96	10	12	12	1	H
CWR19C-337--H-	4	330	10	100	120	10	12	12	0.9	H
CWR19D-335--A-	6	3.3	1	10	12	6	8	8	12	A
CWR19D-475--A-	6	4.7	1	10	12	6	8	8	12	A
CWR19D-685--B-	6	6.8	1	10	12	6	8	8	8	B
CWR19D-106--B-	6	10	1	10	12	6	8	8	8	B
CWR19D-156--B-	6	15	1	10	12	8	10	10	8	B
CWR19D-156--D-	6	15	1	10	12	8	10	12	5	D
CWR19D-156--E-	6	15	1	10	12	8	10	12	3	E
CWR19D-226--D-	6	22	1	10	12	6	8	8	5	D
CWR19D-226--E-	6	22	2	20	24	8	10	12	3.5	E
CWR19D-336--E-	6	33	2	20	24	6	8	8	3.5	E
CWR19D-476--F-	6	47	3	30	36	8	10	12	3.5	F
CWR19D-686--F-	6	68	4	40	48	10	12	12	1.5	F
CWR19D-686--G-	6	68	4	40	48	10	12	12	1	G
CWR19D-107--G-	6	100	6	60	72	10	12	12	1.1	G
CWR19D-157--G-	6	150	10	100	120	10	12	12	1.1	G
CWR19D-227--H-	6	220	10	100	120	10	12	12	0.9	H
CWR19D-337--H-	6	330	20	200	240	10	12	12	0.9	H
CWR19F-225--A-	10	2.2	1	10	12	6	8	8	12	A
CWR19F-335--A-	10	3.3	1	10	12	6	8	8	12	A
CWR19F-475--B-	10	4.7	1	10	12	6	8	8	8	B
CWR19F-475--C-	10	4.7	1	10	12	6	8	8	5.5	C
CWR19F-685--B-	10	6.8	1	10	12	6	8	8	8	B
CWR19F-685--C-	10	6.8	1	10	12	6	8	8	5.5	C
CWR19F-685--D-	10	6.8	1	10	12	6	8	8	5	D
CWR19F-106--B-	10	10	1	10	12	8	10	10	8	B
CWR19F-106--C-	10	10	1	10	12	6	8	8	5.5	C
CWR19F-106--D-	10	10	1	10	12	6	8	8	4	D
CWR19F-106--E-	10	10	1	10	12	6	8	8	3.5	E
CWR19F-156--D-	10	15	2	20	24	6	8	8	5	D
CWR19F-156--E-	10	15	2	20	24	8	10	10	3	E
CWR19F-226--E-	10	22	3	30	36	8	10	10	2	E
CWR19F-336--F-	10	33	3	30	36	8	10	10	1.5	F
CWR19F-476--F-	10	47	4	40	48	10	12	12	1.5	F
CWR19F-476--G-	10	47	4	40	48	10	12	12	1	G
CWR19F-686--G-	10	68	6	60	72	10	12	12	1.1	G
CWR19F-107--G-	10	100	10	100	120	10	12	12	1.1	G

See footnote at the end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR19 characteristics - Continued.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR19F-107--H-	10	100	10	100	120	10	12	12	0.9	H
CWR19F-157--H-	10	150	15	150	180	10	12	12	0.9	H
CWR19F-157--X-	10	150	15	150	180	10	12	12	0.9	X
CWR19F-227--H-	10	220	20	200	240	10	12	12	0.9	H
CWR19H-105--A-	15	1	1	10	12	6	8	8	15	A
CWR19H-155--A-	15	1.5	1	10	12	6	8	8	15	A
CWR19H-225--A-	15	2.2	1	10	12	6	8	8	15	A
CWR19H-335--B-	15	3.3	1	10	12	6	8	8	9	B
CWR19H-475--B-	15	4.7	1	10	12	6	8	8	5	B
CWR19H-475--C-	15	4.7	1	10	12	6	8	8	5.5	C
CWR19H-475--D-	15	4.7	1	10	12	6	8	8	6	D
CWR19H-685--D-	15	6.8	1	10	12	6	8	8	6	D
CWR19H-685--E-	15	6.8	1	10	12	8	10	12	3	E
CWR19H-106--D-	15	10	2	20	24	6	8	8	6	D
CWR19H-106--E-	15	10	2	20	24	6	8	8	4	E
CWR19H-156--E-	15	15	2	20	24	6	8	8	4	E
CWR19H-156--F-	15	15	2	20	24	8	10	10	3	F
CWR19H-226--F-	15	22	3	30	36	8	10	10	3	F
CWR19H-336--F-	15	33	5	50	60	6	8	8	3	F
CWR19H-336--G-	15	33	6	60	72	8	10	10	1.1	G
CWR19H-476--G-	15	47	10	100	120	8	10	10	1.1	G
CWR19H-476--H-	15	47	10	100	120	8	10	10	0.9	H
CWR19H-686--G-	15	68	10	100	120	8	10	10	1.1	G
CWR19H-686--H-	15	68	10	100	120	8	10	10	0.9	H
CWR19H-107--H-	15	100	15	150	180	10	12	12	0.9	H
CWR19J-684--A-	20	0.68	1	10	12	6	8	8	15	A
CWR19J-105--A-	20	1	1	10	12	6	8	8	15	A
CWR19J-155--B-	20	1.5	1	10	12	6	8	8	9	B
CWR19J-225--B-	20	2.2	1	10	12	6	8	8	9	B
CWR19J-335--D-	20	3.3	1	10	12	6	8	8	6	D
CWR19J-475--E-	20	4.7	1	10	12	6	8	8	6	E
CWR19J-685--E-	20	6.8	2	20	24	6	8	8	5	E
CWR19J-106--E-	20	10	2	20	24	6	8	8	5	E
CWR19J-106--F-	20	10	2	20	24	6	8	8	3	F
CWR19J-156--F-	20	15	3	30	36	6	8	8	3	F
CWR19J-226--G-	20	22	4	40	48	6	8	8	2.5	G
CWR19J-336--H-	20	33	6	60	72	8	10	10	0.9	H
CWR19J-476--H-	20	47	10	100	120	8	10	10	0.9	H
CWR19J-476--X-	20	47	10	100	120	8	10	10	0.9	X
CWR19K-474--A-	25	0.47	1	10	12	6	8	8	15	A
CWR19K-105--B-	25	1	1	10	12	6	8	8	10	B
CWR19K-225--D-	25	2.2	1	10	12	6	8	8	6	D
CWR19K-335--E-	25	3.3	1	10	12	6	8	8	4	E
CWR19K-685--F-	25	6.8	2	20	24	6	8	8	3	F
CWR19K-156--G-	25	15	4	40	48	6	8	8	1.4	G
CWR19K-226--G-	25	22	6	60	72	6	8	8	1.4	G
CWR19K-226--H-	25	22	6	60	72	6	8	8	0.9	H
CWR19K-226--X-	25	22	6	60	72	6	8	8	0.9	X
CWR19K-336--H-	25	33	10	100	120	8	10	10	0.9	H
CWR19K-336--X-	25	33	10	100	120	8	10	10	0.9	X

See footnote at the end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR19 characteristics - Continued.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR19M-334--A-	35	0.33	1	10	12	6	8	8	22	A
CWR19M-685--G-	35	6.8	3	30	36	6	8	8	1.5	G
CWR19M-106--H-	35	10	4	40	48	8	10	10	0.9	H
CWR19M-156--X-	35	15	6	60	72	6	8	8	0.9	X

1/ Complete Part or Identifying Number (PIN) shall include additional symbols to indicate termination finish, capacitance tolerance, product level designator, and surge current option letter. If surge current is not required, the last dash shall be replaced with the letter Z.

TABLE II. Style CWR29 characteristics.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR29C-225--A-	4	2.2	1	10	12	6	8	8	4	A
CWR29C-335--A-	4	3.3	1	10	12	6	8	8	6	A
CWR29C-475--A-	4	4.7	1	10	12	6	8	8	6	A
CWR29C-475--B-	4	4.7	1	10	12	6	8	8	3.2	B
CWR29C-685--A-	4	6.8	1	10	12	6	8	8	6	A
CWR29C-685--C-	4	6.8	1	10	12	6	8	8	2.2	C
CWR29C-106--B-	4	10	1	10	12	8	10	10	3.2	B
CWR29C-106--D-	4	10	1	10	12	8	8	10	1.3	D
CWR29C-156--B-	4	15	1	10	12	8	10	10	3.2	B
CWR29C-156--E-	4	15	1	10	12	8	10	12	1	E
CWR29C-226--B-	4	22	1	10	12	8	10	10	3.2	B
CWR29C-226--D-	4	22	1	10	12	8	10	12	1.3	D
CWR29C-336--D-	4	33	2	20	24	8	10	12	1.3	D
CWR29C-336--E-	4	33	2	20	24	8	10	12	0.9	E
CWR29C-336--F-	4	33	2	20	24	8	10	12	0.6	F
CWR29C-476--E-	4	47	2	20	24	8	10	12	0.9	E
CWR29C-686--E-	4	68	3	30	36	8	10	12	0.9	E
CWR29C-686--G-	4	68	3	30	36	10	12	12	0.275	G
CWR29C-107--F-	4	100	4	40	48	10	12	12	0.550	F
CWR29C-107--H-	4	100	4	40	48	10	12	12	0.180	H
CWR29C-157--G-	4	150	6	60	72	10	12	12	0.250	G
CWR29C-227--H-	4	220	8	80	96	10	12	12	0.200	H
CWR29C-337--H-	4	330	10	100	120	10	12	12	0.180	H
CWR29D-155--A-	6	1.5	1	10	12	6	8	8	4	A
CWR29D-335--A-	6	3.3	1	10	12	6	8	8	6	A
CWR29D-335--B-	6	3.3	1	10	12	6	8	8	3.2	B
CWR29D-475--A-	6	4.7	1	10	12	6	8	8	6	A
CWR29D-475--C-	6	4.7	1	10	12	6	8	8	2.2	C
CWR29D-685--B-	6	6.8	1	10	12	6	8	8	3.2	B
CWR29D-685--D-	6	6.8	1	10	12	6	8	8	1.5	D
CWR29D-106--B-	6	10	1	10	12	6	8	8	3.2	B
CWR29D-106--E-	6	10	1	10	12	8	10	12	1	E
CWR29D-156--B-	6	15	1	10	12	8	10	10	3.2	B

See footnote at the end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE II. Style CWR29 characteristics - Continued.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR29D-156--D-	6	15	1	10	12	8	10	12	1.7	D
CWR29D-156--E-	6	15	1	10	12	8	10	12	0.9	E
CWR29D-226--D-	6	22	1	10	12	6	8	8	1.7	D
CWR29D-226--E-	6	22	2	20	24	8	10	12	1	E
CWR29D-226--F-	6	22	2	20	24	8	10	12	0.6	F
CWR29D-336--E-	6	33	2	20	24	6	8	8	1	E
CWR29D-476--F-	6	47	3	30	36	8	10	12	1	F
CWR29D-476--G-	6	47	3	30	36	10	12	12	0.275	G
CWR29D-686--F-	6	68	4	40	48	10	12	12	0.400	F
CWR29D-686--G-	6	68	4	40	48	10	12	12	0.25	G
CWR29D-686--H-	6	68	4	40	48	10	12	12	0.180	H
CWR29D-107--G-	6	100	6	60	72	10	12	12	0.275	G
CWR29D-157--G-	6	150	10	100	120	10	12	12	0.275	G
CWR29D-227--H-	6	220	10	100	120	10	12	12	0.180	H
CWR29D-337--H-	6	330	20	200	240	10	12	12	0.18	H
CWR29F-105--A-	10	1	1	10	12	6	8	8	5	A
CWR29F-225--A-	10	2.2	1	10	12	6	8	8	6	A
CWR29F-225--B-	10	2.2	1	10	12	6	8	8	3.2	B
CWR29F-335--A-	10	3.3	1	10	12	6	8	8	6	A
CWR29F-335--C-	10	3.3	1	10	12	6	8	8	2.2	C
CWR29F-475--B-	10	4.7	1	10	12	6	8	8	3.2	B
CWR29F-475--C-	10	4.7	1	10	12	6	8	8	2.2	C
CWR29F-475--D-	10	4.7	1	10	12	6	8	8	1.5	D
CWR29F-685--B-	10	6.8	1	10	12	6	8	8	3.2	B
CWR29F-685--C-	10	6.8	1	10	12	6	8	8	2.2	C
CWR29F-685--D-	10	6.8	1	10	12	6	8	8	1.7	D
CWR29F-685--E-	10	6.8	1	10	12	6	8	8	1	E
CWR29F-106--B-	10	10	1	10	12	8	10	10	3.2	B
CWR29F-106--C-	10	10	1	10	12	6	8	8	2.2	C
CWR29F-106--D-	10	10	1	10	12	6	8	8	1.3	D
CWR29F-106--E-	10	10	1	10	12	6	8	8	1	E
CWR29F-156--D-	10	15	2	20	24	6	8	8	1.7	D
CWR29F-156--E-	10	15	2	20	24	8	10	10	0.9	E
CWR29F-156--F-	10	15	2	20	24	8	8	10	0.7	F
CWR29F-226--E-	10	22	3	30	36	8	10	10	0.6	E
CWR29F-336--F-	10	33	3	30	36	8	10	10	0.4	F
CWR29F-336--G-	10	33	3	30	36	10	12	12	0.275	G
CWR29F-476--F-	10	47	4	40	48	10	12	12	0.4	F
CWR29F-476--G-	10	47	4	40	48	10	12	12	0.25	G
CWR29F-476--H-	10	47	5	50	60	10	12	12	0.180	H
CWR29F-686--G-	10	68	6	60	72	10	12	12	0.275	G
CWR29F-107--G-	10	100	10	100	120	10	12	12	0.275	G
CWR29F-107--H-	10	100	10	100	120	10	12	12	0.180	H
CWR29F-157--H-	10	150	15	150	180	10	12	12	0.180	H
CWR29F-157--X-	10	150	15	150	180	10	12	12	0.065	X
CWR29F-227--H-	10	220	20	200	240	10	12	12	0.180	H
CWR29H-684--A-	15	0.68	1	10	12	6	8	8	6.	A
CWR29H-105--A-	15	1	1	10	12	6	8	8	7.5	A
CWR29H-155--A-	15	1.5	1	10	12	6	8	8	7.5	A
CWR29H-155--B-	15	1.5	1	10	12	6	8	8	3.2	B
CWR29H-225--A-	15	2.2	1	10	12	6	8	8	7.5	A
CWR29H-225--C-	15	2.2	1	10	12	6	8	8	2.2	C
CWR29H-335--B-	15	3.3	1	10	12	6	8	8	3.6	B
CWR29H-335--D-	15	3.3	1	10	12	6	8	8	1.7	D

See footnote at the end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE II. Style CWR29 characteristics - Continued.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR29H-475--B-	15	4.7	1	10	12	6	8	8	2.	B
CWR29H-475--C-	15	4.7	1	10	12	6	8	8	2.2	C
CWR29H-475--D-	15	4.7	1	10	12	6	8	8	2	D
CWR29H-475--E-	15	4.7	1	10	12	6	8	8	1.2	E
CWR29H-685--D-	15	6.8	1	10	12	6	8	8	2	D
CWR29H-685--E-	15	6.8	1	10	12	8	10	12	0.9	E
CWR29H-106--D-	15	10	2	20	24	6	8	8	2	D
CWR29H-106--E-	15	10	2	20	24	6	8	8	1.2	E
CWR29H-106--F-	15	10	2	20	24	6	8	8	0.667	F
CWR29H-156--E-	15	15	2	20	24	6	8	8	1.2	E
CWR29H-156--F-	15	15	2	20	24	8	10	10	0.8	F
CWR29H-226--F-	15	22	3	30	36	8	10	10	0.8	F
CWR29H-226--G-	15	22	4	40	48	6	8	8	0.275	G
CWR29H-336--F-	15	33	5	50	60	6	8	8	0.8	F
CWR29H-336--G-	15	33	6	60	72	8	10	10	0.275	G
CWR29H-336--H-	15	33	5	50	60	8	8	10	0.18	H
CWR29H-476--G	15	47	10	100	120	8	10	10	0.275	G
CWR29H-476--H-	15	47	10	100	120	8	10	10	0.18	H
CWR29H-686--G-	15	68	10	100	120	8	10	10	0.275	G
CWR29H-686--H-	15	68	10	100	120	8	10	10	0.18	H
CWR29H-107--H-	15	100	15	150	180	10	12	12	0.18	H
CWR29J-474--A-	20	0.47	1	10	12	8	8	10	7.5	A
CWR29J-684--A-	20	0.68	1	10	12	6	8	8	7.5	A
CWR29J-684--B-	20	0.68	1	10	12	6	8	8	5.6	B
CWR29J-105--A-	20	1	1	10	12	6	8	8	7.5	A
CWR29J-105--B-	20	1	1	10	12	6	8	8	4.8	B
CWR29J-155--B-	20	1.5	1	10	12	6	8	8	3.6	B
CWR29J-155--C-	20	1.5	1	10	12	6	8	8	2.4	C
CWR29J-225--B-	20	2.2	1	10	12	6	8	8	3.6	B
CWR29J-225--D-	20	2.2	1	10	12	6	8	8	1.7	D
CWR29J-335--D-	20	3.3	1	10	12	6	8	8	2	D
CWR29J-335--E-	20	3.3	1	10	12	6	8	8	1.2	E
CWR29J-475--E-	20	4.7	1	10	12	6	8	8	1.7	E
CWR29J-685--E-	20	6.8	2	20	24	6	8	8	1.5	E
CWR29J-685--F-	20	6.8	2	20	24	6	8	8	0.7	F
CWR29J-106--E-	20	10	2	20	24	6	8	8	1.5	E
CWR29J-106--F-	20	10	2	20	24	6	8	8	0.8	F
CWR29J-156--F-	20	15	3	30	36	6	8	8	0.8	F
CWR29J-156--G-	20	15	3	30	36	6	8	8	0.275	G
CWR29J-226--G-	20	22	4	40	48	6	8	8	0.625	G
CWR29J-226--H-	20	22	4	40	48	6	8	8	0.18	H
CWR29J-336--H-	20	33	6	60	72	8	10	10	0.18	H
CWR29J-476--H-	20	47	10	100	120	8	10	10	0.18	H
CWR29J-476--X-	20	47	10	100	120	8	10	10	0.11	X
CWR29K-334--A-	25	0.33	1	10	12	6	8	8	7.5	A
CWR29K-474--A-	25	0.47	1	10	12	6	8	8	7.5	A
CWR29K-684--B-	25	0.68	1	10	12	6	8	8	4	B
CWR29K-105--B-	25	1	1	10	12	6	8	8	4	B
CWR29K-105--C-	25	1	1	10	12	6	8	8	2.6	C
CWR29K-155--D-	25	1.5	1	10	12	6	8	8	1.7	D
CWR29K-225--D-	25	2.2	1	10	12	6	8	8	2	D
CWR29K-225--E-	25	2.2	1	10	12	6	8	8	1	E
CWR29K-335--E-	25	3.3	1	10	12	6	8	8	1.2	E
CWR29K-475--F-	25	4.7	2	20	24	6	8	8	0.7	F

See footnote at the end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE II. Style CWR29 characteristics - Continued.

PIN 1/	DC rated voltage (+85°C) (Volts)	Cap. (nom) (µF)	DC Leakage (max) (µA)			Dissipation factor (max) (percent)			Max ESR 100 kHz +25°C (Ohms)	Case size
			+25°C	+85°C	+125°C	+25°C	+85°C +125°C	-55°C		
CWR29K-685--F-	25	6.8	2	20	24	6	8	8	0.8	F
CWR29K-685--G-	25	6.8	2	20	24	6	8	8	0.3	G
CWR29K-106--G-	25	10	3	30	36	6	8	8	0.35	G
CWR29K-156--G-	25	15	4	40	48	6	8	8	0.35	G
CWR29K-156--H-	25	15	4	40	48	6	8	8	0.2	H
CWR29K-226--G-	25	22	6	60	72	6	8	8	0.35	G
CWR29K-226--H-	25	22	6	60	72	6	8	8	0.18	H
CWR29K-226--X-	25	22	6	60	72	6	8	8	0.16	X
CWR29K-336--H-	25	33	10	100	120	8	10	10	0.18	H
CWR29K-336--X-	25	33	10	100	120	8	10	10	0.13	X
CWR29M-224--A-	35	0.22	1	10	12	6	8	8	12	A
CWR29M-334--A-	35	0.33	1	10	12	6	8	8	12	A
CWR29M-474--B-	35	0.47	1	10	12	6	8	8	6.8	B
CWR29M-684--C-	35	0.68	1	10	12	6	8	8	4	C
CWR29M-105--D-	35	1	1	10	12	6	8	8	2.2	D
CWR29M-155--E-	35	1.5	1	10	12	6	8	8	1.3	E
CWR29M-335--F-	35	3.3	1	10	12	6	8	8	0.7	F
CWR29M-475--G-	35	4.7	2	20	24	6	8	8	0.375	G
CWR29M-685--G-	35	6.8	3	30	36	6	8	8	0.375	G
CWR29M-685--H-	35	6.8	3	30	36	6	8	8	0.5	H
CWR29M-106--H-	35	10	4	40	48	8	10	10	0.5	H
CWR29M-156--X-	35	15	6	60	72	6	8	8	0.19	X
CWR29N-104--A-	50	0.1	1	10	12	6	8	8	12	A
CWR29N-154--A-	50	0.15	1	10	12	6	8	8	12	A
CWR29N-224--B-	50	0.22	1	10	12	6	8	8	6.8	B
CWR29N-334--B-	50	0.33	1	10	12	6	8	8	4.8	B
CWR29N-474--C-	50	0.47	1	10	12	6	8	8	3.2	C
CWR29N-684--D-	50	0.68	1	10	12	6	8	8	2.3	D
CWR29N-105--E-	50	1	1	10	12	6	8	8	1.7	E
CWR29N-155--F-	50	1.5	1	10	12	6	8	8	1.1	F
CWR29N-225--F-	50	2.2	2	20	24	6	8	8	0.7	F
CWR29N-335--G-	50	3.3	2	20	24	6	8	8	0.5	G
CWR29N-475--H-	50	4.7	3	30	36	6	8	8	0.5	H

1/ Complete PIN shall include additional symbols to indicate termination finish, capacitance tolerance, product level designator, and surge current option letter. If surge current is not required, the last dash shall be replaced with the letter Z.

NOTES:

Reference documents. In addition to MIL-PRF-55365, this specification sheet references the following documents.

MIL-STD-202

(Copies of these documents are available online at http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

* Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA – NA

Preparing activity:
Army - CR

Agent:

DLA - CC

(Project 5910-2006 031)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.