INCH-POUND

MIL-S-58112
14 August 1989

MILITARY SPECIFICATION

SLING, MULTI-LEG, HELICOPTER, EXTERNAL CARGO

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification established the design, test. manufacture and acceptance requirements for a 5,000 kilogram (11,000 pound) and a 15,000 kilogram (33,000 pound) capacity helicopter external cargo sling and their components.

1.2 Classification

5,000 kg capacity sling, P/N 38850-00001-43M
15,000 kg capacity sling, P/N 38850-00001-44M

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. The following specifications and. standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specification and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletIons) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Aviation Systems Command, ATTN: AMSAV-EDS, 4300 Goodfellow Blvd., St. Louis, Missouri 63220-2798, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by Letter.

FSC 1670

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-636	Box, Shipping Fiberboard
QQ-P-416	Plating, Cadmium (Electrodeposited)

MILITARY

MIL-P-116	Preservation, Methods of
MIL-I-6868	Inspection Process, Magnetic Particle
MIL-A-8625	Anodic Coatings, For Aluminum and Aluminum Alloys
MIL-R-24050	Rope, Nylon, Double-Braided
MIL-K-41835	Kit Bag, Flyer's

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables For Inspection By Attributes
MIL-STD-129	Marking For Shipment and Storage
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-6866	Inspection, Liquid Penetrant

2.1.2 Other Government drawings, and publications. The following other Government drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitations.

Drawings

USAAVSCOM	38850-00001	Sling Assembly
	38850-00004	Apex Fitting Assembly
	38850-00008	Pin, sling
	38850-00009	Rope Assembly
	38850-00011	Grab Hook Assembly
	38850-00053	Chain

Publications

AA-STD-1	(AVSCOM)	Quality Acceptance Criteria for Magnetic Particle Inspection
AA-STD-2	(AVSCOM)	Quality Acceptance Criteria for Penetrant Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards drawings, publications, and other Government documents required by contractor in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publication. The following document form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS are the issue of the document cited in the solicitation (see 6.2).

Splicing Manual-Braided Rope,

(Application for copies should be addressed to: Samson Ocean Systems, Inc., 99 Righ Street, Boston, MA 02110)

I The Splicing Book

(Application for copies should be addressed to: Wellington Puritan Mills, Inc l , Madison, GA 30650)

ASTM D3951	Packing Commercial
ASTM-E8M	Materials, Metallic, (Metric) Tension Testing Of

(Application for copies should be addressed to the American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103.)

(Non government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.).

2.3 Order of precedence. In the event of 8 conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets of MS Standards), the text of this specification shall take precedence. Nothing in this specification; however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contravct or purchase order, a sample shall be subject to first article inspection (see 4.3 and 6.2d).
3.2 Materials. Materials shall be as specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:02Z
Check the source to verify that this is the current version before use.

3.3. Design and Construction. Each sling shall consist of an apex fitting and four sling legs which are adjustable in length from 3.-8 to 5 meters (12 to 16 feet). Each sling leg shall consist of a 3.8 meter (12 foot) long nylon rope assembly, a grab hook assembly and an 2.5 meter (8 foot) length of steel chain. The sling shall be fabricated, assembled and stowed in accordance with Drawing No. 33850-00001 and subordinate drawings.

3.3.1 Apex fitting. The apex fitting shall consist of a clevis with a removable pin and an aluminum spacer secured with a safety bolt, slotted nut and cotter pin. The clevis shall be made from an aluminim forging for the 5,000 kg capacity apex fitting and an alloy steel forging for the 15,000 kg apex. The apex fitting shall be manufactured and assembled in accordance with Drawing No. 38850-00004 and subordinate drawings.

3.3.2 Sling rope assembly. The sling rope assembly shall consist of double-braided, nylon rope conforming to MIL-R-24050 and shall be fabricated in accordance with Drawing No. 38850-00009. A standard eye splice shall be provided at each end. The strength member at the rope eye shall be protected with a polyurethane coated thimble and a cone shaped polyurethane potted joint. General guidance for standard eye splicing is contained in the Splicing Manual-Braided Rope and The Splicing Book. The assembled rope shall be provided with two coats of an abrasion resistant coating as specified on Drawing No. 38850-00009. The finished rope assembly, P/N 38850-00009-55M shall lay unrestrained in coils not exceeding 38 centimeters {15 inches) in diameter and P/N 38850-OO009-56M shall lay unrestrained in coils not exceeding 45 centimeters (18 inches) in diameter.

3.3.3 Grab hook assembly. The grab hook shall consist of an alloy steel forging incorporating a clevis for connection to the rope assemble at one end and a chain grab hook and a coupling link for attachment of the chain at the other end. An alloy steel pin and an aluminum spacer shall be secured in the clevis using a snap ring. A sheet metal keeper and spring shall be provided to retain the chain in the grab hook. The keeper and spring shall be secured to the grab hook using a bolt and locknut. The grab hook assembly shall be manufactured in accordance with Drawing No l 38850-00011 and subordinate drawings.

3.3.4 Pins. Alloy steel pins used with the apex fitting and grab hook assemblies shall be manufactured in accordance with Drawing No. 38850-00008.

3.3.5 Chain assembly. The chain assembly provides adjustment in the length of each leg by passing through the load slinging provision back to the grab hook. The chain shall be manufactured in accordance with Drawing No l 38850-00053.

3.3.6 Unit Pack. Each complete sling assembly shall be stowed in a kit bag conforming to MIL-K-41835.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:02Z
Check the source to verify that this is the currentversion before use.

3.4 PERFORMANCE CHARACTERISTICS

3.4.1 Maximum working load. A complete four leg sling assembly, when rigged with sling legs at an angle up to 30 degrees from vertical, shall be capable of transporting the following maximum working loads:

P/N 38850-10001-43M 5,000 Kilograms (KGS), 11,000 Pounds (LBS)
P/N 38850-00001-44M 15,000 Kilograms (KGS), 33,000 Pounds (LBS)

3.4.2. Strength of components. Component assemblies shall sustain the static loads specified in Table I. Rope assemblies shall sustain the additional dynamic loads specified in Table II.

TABLE I STATIC LOAD

COMPONENTS	P/N	PROOF		ULTIMATE	
Sling P/N 38850-0001-43M(5KG)		KGS	IJBS	KC%	- LBS
Apex Fitting Pin	38850-00004-45M 38850-00008-101	16,000	35,300	24,000	52,900
Grab hook Pin Chain	38850-00011-41M 38850-00008-103 38850-00053-101	5,100	11,300	9,000	19,800
Reps Assembly	38850-00008-55M	5>100	11,300	9,500	20,900
Sling P/N 33850-00001-44M(15KG)					
Apex Fitting Pin	38850-00004-46M 38850-00004-102	34,500	76,100	51,800	114,200
Grab Hook Pin Chain	38850-00011-46M 38850-00008-104 38850--00053--102	11,100	24,400	17,600	38,800
Rope	38850-00009-56M	11,100	24,400	18,700	41,300

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:02Z
Check the source to verify that this is the current version before use.

TABLE II CYCLIC LOADS

COMPONENT	P/N	LOAD				FREQUENCY
		MAX		MIN		
		KGS	LBs	KGS	LBS	Hz
Rope	38850-00009-55M	2700	6000	900	2000	4
Rope	38850-00009-5 6M	5800 ,	12800	2000	440(5	4

3.5 Dust. The sling rope assembly shall be capable of meeting the dust requirements as specified in 4.5.4.

3.6 Solar radiation. The sling rope assembly shall be capable of meeting the solar radiation requirements as specified in 4.5.5.

3.7 Weight. The weight of a complete sling shallnot exceed 25 kilograms (55 pounds) for the 5,000 kilogram capacity sling and 53 kilograms (117 pounds) for the 15,000 kilogram capacity sling.

3.8 Marking. The sling and major components shall be marked for identification and maximum working load as shown on applicable drawings.

3.9 Assembly. Each sling shall be assembled so that the maximum variation in length among the four nylon rope assemblies of each sling shall not exceed 8 centimeters (3.0 inch).

3.10 Workmanship. The slings shall conform to the quality established by this specification and documents referenced. All metal components shall be free from burrs and sharp edges and by visual inspection shall not contain foreign matter on the material surfaces.

LEFT BLANK INTENTIONALLY

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:02Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISION

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for h the performance of all inspection requirements. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deamed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First Article (see 4.3).

b. Quality Conformance (see 4.4).

4.2.1 Inspection Lots. An inspection lot is defined as a collection of 100 slings or sling components which are alike in construction and place of manufacture

4.3 First article inspection. When required (see 6.2d), inspection of the first article shall be made of one completely fabricated item for all provisions of the applicable drawings, provisions of this specification and the test specified in 4.5. Failure of the sling or any sling component to pass any of the inspections or tests shall be cause for rejection of the first article. Further production of slings prior to approval of the first article shall be at the manufacturer's risk.

4.4. Quality conformance. Selection of samples for quality conformance inspections and testing shall be as specified in 4.11 except for the proof load test of 4.6.1 and the non-destructive examination specified in 4.9 which shall apply to all sling components offered for acceptance. Random samples selected for each inspection lot shall be examined as specified in 4.10. One rope assembly examined and accepted under the production sampling of each inspection lot will be subjected to the testing specified in 4.6.2. Failure of sling or any component of sling to pass the examination or any testing specified in 4.6 shall cause acceptance to be withheld for the failed sling and the inspection lot from which it was drawn, until the following have been completed:

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:02Z
Check the source to verify that this is the currenversion before use.

a. Determine the cause of the failure.

b. Take the necessary action, with the concurrence of the procuring activity, to correct or eliminate the failure from all units in the inspection lot and, if so directed by the procuring activity, from those units previously shipped.

c. Submit to the procuring activity for approval, the proposed corrective action to prevent recurrence of the failure.

d. Retest in accordance with 4.6.4.

4.5 First article test. All loads shall be applied in the manner prescribed on the applicable component drawing.

4.5.1. Proof load test. Each component of the first article samples shall be pulled to the proof loads indicated in Table 1. The load shall be relaxed and the part under test examined for defects prior to application of ultimate loads. Evidence of permanent set, tears, distortion or separation is cause for rejection of the first article.

4.5.2 Ultimate load test. This test shall be performed on the same first article samples which have previously been subjected to proof load testing as required by paragraph 4.5.1. Each component of the first test article samples shall be pull tested to the ultimate loads indicated in table I.

4.5.3 Cyclic load test. This test shall be performed on a rope assembly which was previously subjected to the proof load test as required in paragraph 4.5.1. One of each size rope assembly shall be subjected to the cyclic loads indicated in Table II for an accumulative time of not less than one (1) hour. The required time at specified loads and frequencies may be accumulated by translationing to reduced load and frequency levels to prevent overheating of the rope. External cooling using air at a minimum temperature of 20 degrees C (68 degrees F) is allowed only during these reduced load, cool-down periods. No more than 15 cool-down periods shall be allowed in accumulating the one (1) hour of cyclic load testing under the specified conditions. The cyclic load shall approximate a sine wave (load versus time). The maximum and minimum loads shall be within +300 Kgs (660 pounds) of the values specified in Table II. Momentary non-compliance with these values in excess of ten seconds over a five minute period shall invalidate that increment of the load test since the last transition. At conclusion of cyclic testing, the rope assembly shall be subjected to the proof loads as specified in Table I. Any evidence of disengagement of splicing, separation of the potting from the strength member or the thimble while under the post-cyclic load shall be grounds for rejection.

4.5.4 Dust test. Dust test shall be performed as specified in MIL-STD-810, Method 510.1/1. This test shall be performed on a rope assembly which was previously subjected to the proof load test. After the dust test, the rope assembly shall satisfactorily complete the ultimate load test of paragraph 4.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

4.5.5. Solar radiation test. Solar radiation test shall be performed as specified in MIL-STD-810, Method 510.1-/11. This test shall be performed on a rope assembly which was previously subjected to the proof load test. After the solar radiation test, the rope assemblies shall satisfactorily sustain 95 percent of the ultimate load specified in Table I.

4.6 Production testing. All loads shall be applied in the manner prescribed on the applicable component drawing.

4.6.1 Proof test load. Each component of each sling set produced shall be pulled to the proof loads indicated in Table I. The load shall be relaxed and the part uder test examined for defects. Evidence of permanent set, tears, distortion or separation is cause for rejection.

4.6.2 Ultimate load test. One rope assembly shall be selected at random from examined samples in each inspection lot and pulled to the ultimate load specified in Table I. Successsful completion of this test (no breakage or separation below ultimate load) is required before acceptance of the inspection lot.

4.6.3 Cyclic load test. One rope assembly shall be selected at random from examined samples from the first inspection lot and subjected to the cyclic load test specified in paragraph 4.5.3.

4.6.4 Retest. If any sling component fails to successfully complete any production load testing, production shall be halted pending isolation of failure causes. The Government will select, at its option, three additional samples of the failed component from the applicable inspection lot for retest. If the failure occurred on application of the proof load test as specified in paragraph 4.6.1, the additional samples shall also be subjected to the ultimate load test as specified in paragraph 4.6.2. All samples shall successfully complete retesting of the failed test and ultimate load testing, as applicable prior to resumption of production.

4.7 Records and documentation of eye splice. If the contractor elects to use splicing methods other than those identified in paragraph 3.3.2, such methods and inspection procedures must be documented and inspection records maintained and available for evaluation by Government inspectors. Conformance to either the recommended splicing practices or those of the contractor’s design does not of itself assure acceptability of the rope assemblies. Government acceptance of rope assemblies will depend upon successful completion of all tests in accordance with the requirements of this specification.

4.8 Inspection of materials and components. The contractor is responsible for insuring that materials and components used were manufactured and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

4.8.1 Forging Integrity. One forging from each heat treat lot shall be sectioned for the purpose of preparing tensile test specimens by the supplier. At least two specimens shall be taken and machined to conform to the largest types described in ASTM E8M, Figure 8, which can be accommodated. The supplier shall identify the location on the parent forging from which the marked specimens are taken in a sketch. One specimen shall be parallel to forging flow direction and second at another identifiable angle. Conformance to strength requirements stated in apex fitting and grab hook drawings shall be accomplished in supplier performed tensile tests. Acceptability shall be documented in supplier certiftcation of material composition and strength.

4.8.2 Hardness testing. Samples shall be selected from each lot of steel sling components including shackle forgings, grab book, grab book keepers and sling pins as required in paragraph 4.8 herein and subject to hardness testing after heat treatment in an area to be subsequently removed by machining. Acceptable hardness is stated on the respective detail drawings.

4.9 Non-destructive examination. Each steel shackle, grab hook and sling pin shall be magnetic particle prior to cadmium plating using methods of MIL-I-6868 and acceptance criteria of AA-STD-1. Each aluminum alloy shackle shall be fluorescent penetrant inspected prior to anodizing using methods of MIL-STD-6866 and acceptance criteria of AA-STD-2. Failure to satisfy these criteria shall result in single part rejection.

4.10 Examination of end item. The sample unit for the examination shall be one sling or one sling component. The classification of defects shall be as set forth in Table III.

4.11 Inspection levels and acceptable quality levels (AQLs) for end item examination. Inspection Level II shall be in accordance with MIL-STD-105. AQLs, expressed in defects per 100 units, shall be as follows:

a. For major defects indicated in Table III except for prof loads tests, AQL = 1.0.

b. For minor defects indicated in Table III, AQL = 4.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

TABLE III

Examine	Defect	Classification Major	Minor
Materials	Any components not fabricated of specified kind of material	X	
Design	Any characteristic not in accordance with requirements	X	
Cleaniness	Dirt, grease, oil or foreign matter	X	
Workmanship	Burrs, sharp edges, surface roughness, frayed rope assemblies	X	
Assembly	Component missing, not assembled or joined as specified	X	
	Operation omitted or not performed	X	
	Variation length of nylon rope assemblies in sling assembly exceeds 8 centimetes (3.1 inches)	X	
Component Dimensions	Perpendicularity, parallelism or concentricity out of tolerance		X
Cadmium Plating	Evidence of hydrogen embrittlement or unable to document specified baking after plating per QQ-P-416	X	
Anodizing	Not as specified (MIL-A-8625)	X	
Keeper Spring Torque	Out of tolerance at specified angular positions	X	
Proof Load Tests	Evidence of permanent set, distoration, elongation, tears or separation when proof loads are applied	X	
Identification	Not as specified		X
Nylon Polyamide Coating of Ropes	Wrong compound, color or number of coats		X
Hardness Test	Not within range specified	X	

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:02Z
Check the source to verify that this is the current version before use.

4.12 Packaging inspection. An examination shall be made to determine compliance with the preservation, packing and marking requirements specified in Section 5. Defects shall be scored as specified below. Lots submitted for examination shall be fully packaged, with the exception that containers shall not be palletized and need not be sealed or closed. The inspection level shall be S-2 and the AQL shall be 6.5 defects per 100 units l

Examine	Defects
Marking	Omitted, incorrect, illegible, of improper size; location, sequence or method of application.
Material	Any component missing, damaged, defective or not of specified material.
Workmanship	Inadequate coiling, folding, or tying of the end item; bulging or distortion of containers, or contents loose or not snug fitting-

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-P-116, PPP-B-601 and PPP-B-636 for level A, B, or Commercial as specified in (6.2).

5.1.1. Level A. Each complete unit shall be packaged in accordance with Method III of MIL-P-116 in a close fitting box conforming to PPP-B-601, overseas type, style I.

5.1.2 Level B.

5.1.2.1 Sling assembly, 5,000 kilogram capacity. Each complete unit shall be packaged in accordance with Method III of MIL-P-116 in a close fitting box conforming to PPP-B-636, W5S or W5C. Closure shall be in accordance with Method V of the box specification appendix.

5.1.2.2. Sling Assembly, 15,000 Kilogram Capacity. Each component unit shall be packaged in accordance with Method III of MIL-P-116 in a close fitting box conforming to PPP-B-636, V13c. Closure shall be in accordance with Method V of the box specification appendix.

5.1.3 Commercial. Each complete unit shall be packaged in accordance with ASTM D3951.

5.2 Packing. Not required. The unit container shall serve as the shipping container

5.3 Marking. Military levels of protection shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:02Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory)

6.1 Intended use. The helicopter external cargo slings are intended for use in transporting attachable cargo beneath suitably equipped helicopters. Various number of lifting legs may be configured to converge to single hooks or be separated in various ways between fore, aft, and center helicopter hooks.

6.2 Acquisition requirements. Procurement documents shall specify:

a. Title, number and date of this specification.

b. Quantities and identity of components or total assemblies being procured.

c. Timeframe required for production deliveries.

d. Whether or not a pre-production First Article Test is required for any component or assembly.

e. Whether or not the Government will conduct any or all of the First Article Test.

f. Timeframe required for pre-production models.

g. Level of packaging required.

6.3 First article. When the first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first production items, a standard production item from the contractor's current inventory (see 3.1), and the number of items to be tested as specified in 4.3. The contacting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles.

Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspections to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such produts, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:02Z
Check the source to verify that this is the current version before use.

6.4. Subject term (key word) listings

Cargo, External, Helicopter
External Cargo, Helicopter
Cargo, Sling, Helicopter
Helicopter, Cargo, External sling
Multi-Leg Sling
Helicopter, Cargo Sling
Helicopter, Sling
Sling, Cargo Multi-Leg

6.5 Definitions.

a. Proof load. The maximum force applied in testing components or assemblies to demonstrate that these load levels cause no permanent deformation or yielding. For nylon rope assemblies, the deformation after proof load may be residual up to 24 hours after test. Following this time, no deviation will be acceptable for Section 3 requirements.

b. Ultimate load. The maximum force applied in testing components or assemblies in order to demonstrate a margin of safety above proof loads. Permanent deformation, tearing, and bending is allowed. Complete breakage or separation is not allowed.

c. Cyclic Load. This is a cyclic load applied as with an ultimate load, to demonstrate a margin of safety but under the dynamic loading conditions to be expected in actual helicopter external load operations Complete breakage or separation is unacceptable.

d. Maximum or working load. The load capacity of the complete four leg sling assembly shall be defined as the maximum or working load. This sling assembly shall be capable of transporting this load when properly rigged and attached to a helicopter.

When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations. Identified below are the specific paragraphs numbers and the international standardization agreements applicable to this specification:

International standardization agreement.

STANAG	2949
QSTAG	767

CUSTODIAN
Navy - AS
Air Force - 99

REVIEW ACTIVITIES
Air Force - 82
Amy - GL

PREPARING ACTIVITY
Army - AV

Project No. 1670-0666

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.