MIL-T-52944A
INTERIM AMENDMENT 1(ME)
27 June 1985

MILITARY SPECIFICATION

TRUCK, FIREFIGHTING; DRY CHEMICAL AND AFFF

4 BY 4 COMMERCIAL

This interim amendment is approved for use by the US Army Belvoir Research and Development Center, Department of the Army, with MIL-T-52944A, dated 22 February 1982.

PAGE 4

3.3.1, delete in its entirety and substitute:

"3.3.1 Treatment and painting. The portions of the truck normally painted internally and externally shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable. Unless otherwise specified (see 6.2), top coat shall be gloss-lime-yellow, color no. 13670, of FED-STD-595."

PAGE 7

3.7.4.4, line 4, after "watt" add "minimum".

PAGE 8

3.7.4.5, line 3, delete "vertical".

3.7.10, line 6, delete "on the front wheels."

PAGE 9

3.7.15, lines 2 and 3, delete "designed for use with 30 minutes air pack."

PAGE 10

3.8, (c), delete in its entirety and substitute:

(c) "All doors shall be of box type reinforced construction having continuous heavy duty corrosion resistant hinges with stainless steel hinge pins and insert sockets. All doors shall be equipped with recessed "D" ring type door handles, two point slam action catches, and hold open devices. Horizontal doors shall be hinged at the top. Doors shall be locked open at not less than 30 degrees above the horizontal position when held open by the hold open device. Vertical doors shall be hinged to the front of the truck."

FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.

PAGE 11

3.8.1, (e), line 4, add "One or more compartments shall be equipped to hold and store the rescue tool."

3.8.1, (f), line 2, add "The tops of all compartments shall be constructed of safety tread plate."

PAGE 12

3.9.1, line 13, delete "212°" and substitute "207°".

PAGE 13

3.9.3, line 1, after "after each use." add "Piping to the nitrogen gas cylinder(s) shall incorporate flexible piping to allow for minor misalignment."

PAGE 17

4.5.1, add:

"126. Treatment and painting not as specified.
127. Paint color not as specified."

PAGE 21

6.2, add "(f) Color required when other than as specified (see 3.3.1)."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4210-A200

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.