INCH-POUND

MIL-W-48856B (AR)
AMENDMENT 3
11 May 1989
SUPERSEDING
AMENDMENT 2
2 October 1987

MILITARY SPECIFICATION

WARHEAD SECTIONS, GUIDED MISSILE, H.E.
M258E6 LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-W-48856B (AR) dated 7 August 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Department and Agencies of the Department of Defense.

PAGE 4

3.4 change:

From: The warhead cable and connector shall meet the following continuity requirements after machining of explosives:

To: The warhead cable and connector shall meet the following continuity requirements prior to loading of explosives and after machining of explosives:

Page 6

* 3.5.6 add the following in the appropriate columns:

"6(+)	8	0.25uA	≥ 950K ** "

Page 7

3.6.2 change:

	RESISTANCE BETWEEN ALL PINS AND WARHEAD CASE	RESISTANCE (OHMS)
From:	All pins + DC	= 10 MEG OHMS
	All pins - DC	= 10 MEG OHMS
To:	All pins + DC	≥ 10 MEG OHMS
	All pins - DC	≥ 10 MEG OHMS

AMSC N/A FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

Page 13

4.4.2.2 change Major Characteristics 101, 109, 110 to read under the appropriate columns as follows:

Category Major	Exam or Test	AQL or 100%	Reg Para	Para ref/ Insp Meth
101	Continuity does not conform to requirements prior to loading.	100%	3.4	4.5.3/ 4.5.5/ Gage
109	J1 connector damaged, not secure 1/, or misaligned prior to loading.	100%	3.2	Visual/ Manual/ Gage
110	P3 connector damaged prior to loading	100%	3.2	Visual/ Manual

4.4.2.2 add new major categories in the appropriate columns as follows:

Category Major	Exam or Test	AQL or 100%	Reg Para	Para ref/ Insp. Meth
111	Continuity does not conform to requirements after loading	100%	3.4	4.5.3/ 4.5.5/ Gage
112	P3 connector damaged after loading	100%	3.2	Visual/ Manual

Page 16

4.4.2.5: Major Categories:

Major 109: In column "AQL or 100%" delete "100%" and substitute "2/".

Major 110: In column "AQL or 100%" delete "100%" and substitute "2/".

Add new note 2/ as follows:

"2/ The units shall be sampled in accordance with paragraph 4.5.8."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

Add new paragraph 4.5.8 as follows:

"4.5.8 Center of gravity and roll unbalance. These tests shall be conducted 100% until 1000 consecutive defect-free units have been tested. After 1000 consecutive defect-free units have been tested, the sampling frequency shall be reduced to 1 in 25 units. If a defect is encountered in the reduced sample, the previous 50 units and the next 250 units shall be inspected 100%. If no defects are found during the screening, then the sampling shall be reduced to 1 in 25 units.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contents irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A594)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.