INCH-POUND
MIL-DTL-24231/12E(SH)
26 April 2013
SUPERSEDING
MIL-C-24231/12D(SH)
w/AMENDMENT 1
2 March 1992
MIL-C-24231/12D(SH)
15 May 1987

DETAIL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, MULTI-PIN, TYPE V, THREE-, FOUR-, AND FIVE-CONDUCTOR

This specification is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24231.

REQUIREMENTS:

1. Dimensions and configuration: see figures 1 through 4.
2. Unless otherwise specified (see figure 4), all dimensions are in inches.
3. Tolerances shall be as follows, or as stated:

a. Decimals – ±0.005 inch.
b. Fractions – ±1/64 inch.
c. Angular dimensions – ±½degree.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector, multi-pin receptacle – typical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.




FIGURE 2. Receptacle, body – M24231/12-010. (5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.





FIGURE 3. Cap – M24231/12-011. (16)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.



CONNECTIONS FOR M24231/12-020	
PIN NO.	COND. COLOR
1	BLACK
2	WHITE
3	SHIELD

FIGURE 4. Assembly, insert, molded – M24231/12-020. 6

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.

TABLE I. Parts list.

Item no. 1/	Description 2/	Quantity for M24231/12- 3/				Material/specification	Remarks
		001	002	003	004		
1	Receptacle assembly, 3-conductor, symbol no. 737	1				-----	See figure 1.
2	Receptacle assembly, 2-conductor, symbol no. 737.4		1			-----	See figure 1.
3	Receptacle assembly, 4-conductor, symbol no. 737.7			1		-----	See figure 1.
4	Receptacle assembly, 5-conductor				1	-----	See figure 1.
5	Body, receptacle	1	1	1	1	Ni-Cu, Class A QQ-N-281	See figure 2.
6	Insert assembly, molded 2-conductor		1			See items 15, 17, and 18	See figure 4.
7	Insert assembly, molded 3-conductor	1				M24231/5-010	See figure 1.
8	Insert assembly, molded 4-conductor			1		M24231/5-020	See figure 1.
9	Insert assembly, molded 5-conductor				1	M24231/5-067	See figure 1.
10	Insert	1	1	1	1	M24231/5-077	See figure 1.
11	Gasket, O-ring	1	1	1	1	SAE-AS28775-115 4/	Lubricate with silicone compound, SAE-AS8660; see figure 1.
12	Gasket, O-ring	1	1	1	1	SAE-AS28775-215 4/	See item 11 remarks.
13	Ring, retaining	1	1	1	1	M24231/5-073	See figure 1.
14	Pin, guide, 0.092 diameter length as required	1	1	1	1	Ni-Cu, Class A, QQ-N-281	See figure 1.
15	Pin, contact	3	3	4	5	MIL-DTL-24231	See figure 1 and figure 4.
16	Cap, pressure-proof	1	1	1	1	Ni-Al-BRZ, ASTM B150/B150M 5/	See figure 3.
17	Cable, LS2SWU-1, 15-ft.		1			MIL-DTL-24643/33	See figure 4.
18	Epoxy resin, molded	As required				Cast epoxy resin compound 6/	See figure 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.

TABLE I. Parts list – Continued.

NOTES:

1/ Item numbers are the same as encircled numbers shown on figures.

2/ See applicable figure or table listed in remarks column for part numbers and dimensions.

3/ Quantity is for one complete assembly of each size.

4/ Nitrile (Buna N); Parker Hannifin Corporation (part number N0756-75), O-ring Division, 2360 Palumbo Drive, Lexington, KY 40509, CAGE 02697, or equal.

5/ May be high impact plastic, PVC, commercial when pressure-proof cap is not specified (see requirement for pressure-proof caps in MIL-DTL-24231).

6/ Arco Set 200, M.M. Reif and Co., Ivyland, PA, or PR610-TCF (Chockfast Orange), ITW Philadelphia Resins Corp., Montgomeryville, PA, or equal.

CHANGES FROM PREVIOUS ISSUE. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Preparing activity:
Navy – SH
(Project 5935-2011-061)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:14Z
Check the source to verify that this is the current version before use.