INCH-POUND
MIL-DTL-24231/17E(SH)
26 April 2013
SUPERSEDING
MIL-C-24231/17D(SH)
15 May 1987

DETAIL SPECIFICATION SHEET

CONNECTOR, ADAPTER, FOR MOLDED PLUG, TYPE II, NINE-CONDUCTOR

This specification is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24231.

REQUIREMENTS:

1. Dimensions and configuration: see figures 1 through 3.

2. Material for adapter body shall be manufactured from nickel-copper alloy in accordance with Class A, Form 1, hot-finished condition of QQ-N-281 with a minimum yield strength of 40,000 lbf/in^2 at 0.2 percent offset, or nickel-copper alloy in accordance with Class A, Form 1, cold-drawn condition of QQ-N-281 with a minimum yield strength of 50,000 lbf/in^2 at 0.2 percent offset.

3. RG-264/U cable used for insert shall have the outer jacket removed. Shields and wires shall be soldered to pins as shown in the appendix of MIL-DTL-24231.

4. All dimensions are in inches.

5. Tolerances shall be as follows, or as stated:

a. Decimals – ±0.005 inch.

b. Fractions – ±1/64 inch.

c. Angular dimensions – ±½degree.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector, adapter. (1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.





FIGURE 2. Assembly, adapter body – M24231/17-010. (2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.



EACH PIN SHALL BE CONNECTED TO ITS
MATCHING PIN NO. ON OPPOSITE END.

FIGURE 3. Assembly, insert, molded – M24231/17-020. (7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.

TABLE I. Parts list.

Item no. [1/]	Description [2/]	Quantity for M24231/17- [3/]	Material/specification	Remarks
		001		
1	Connector, adapter, 9-conductor, symbol no. 1116.1	1	------	See figure 1.
2	Body, adapter	1	Ni-Cu, Class A, QQ-N-281	See figure 2 and requirement 2.
3	Cap, pressure-proof	2	M24231/13-011	See figure 1.
4	Gasket, O-ring	2	SAE-AS28775-213 [4/]	Lubricate with silicone compound, SAE-AS8660; see figure 1.
5	Gasket, O-ring	2	SAE-AS28775-220 [4/]	See item 4.
6	Insert	2	Nylon, M24231/5-077	See figure 1.
7	Insert assembly, molded	1	See items 10 and 11 or 12 and 13.	See figure 3.
8	Ring, retaining	1	M24231/7-041	See figure 1.
9	Pin, driv-lok, 1/16 diameter by 3/8 long	1	Type A3, CRES 416, coml	See figure 2.
10	Pin, contact	18	MIL-DTL-24231	See figure 3.
11	Cable, RG-264 C/U	As required		See figure 3 and requirement 3.
12	Cable, RG-264 A/U	As required		See figure 3 and requirement 3.
13	Epoxy resin, molded	As required	Cast epoxy resin compound [5/]	

NOTES:

1/ Item numbers are the same as encircled numbers shown on figures.

2/ See applicable figure or table listed in remarks column for part numbers and dimensions.

3/ Quantity is for one complete assembly of each size.

4/ Nitrile (Buna N); Parker Hannifin Corporation (part number N0756-75), O-ring Division, 2360 Palumbo Drive, Lexington, KY 40509, CAGE 02697, or equal.

5/ Arco Set 200, M.M. Reif and Co., Ivyland, PA, or PR610-TCF (Chockfast Orange), ITW Philadelphia Resins Corp., Montgomeryville, PA, or equal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Preparing activity:
Navy – SH
(Project 5935-2011-066)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:16Z
Check the source to verify that this is the current version before use.