MIL-C-18653B
1 March 1961
SUPERSEDING
MIL-C-18653A(NOrd)
5 March 1958

MILITARY SPECIFICATION

CARTRIDGE, ONE-INCH, MARK 1 AND MARK 2 ALL MODS (BOMB-EJECTOR)

This specification has been approved by the Department of Defense and is mandatory for the use by Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 Scope. This specification covers procurement requirements for 1-Inch Cartridge (Bomb-Ejector) Mark 1 all Mods and Mark 2 all Mods.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitations for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-Q-9858—Quality Control System Requirements.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129—Marking for Shipment and Storage.

MIL-STD-414—Sampling Procedures and Tables for Inspection by Variables for percent defective.

DRAWINGS

NAVY DEPARTMENT

BUORD LD. NO. 166557—1 Inch Cartridge (Bomb Ejector) Mark I Mod 2

BUORD LD NO. 255610—1 Inch Cartridge (Bomb Ejector) Mark 2 Mod 0

BUORD LD NO. 276296—1 Inch Cartridge (Bomb Ejector) Mark 1 Mod 3

BUORD LD NO. 276297—1 Inch Cartridge (Bomb Ejector) Mark 2 Mod 1

BUORD DWG. NO. 516986—1 Inch Cartridge (Bomb Ejector) Mark 1 and Mods Cartridge Container

And all drawings and documents listed on the above LD's.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specified procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-90—Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

(The Interstate Commerce Commission regulations are now a part of the Code of Federal Regulations (Revised 1956) available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Orders for the above publication should cite "49 CFR 71-90 (Rev. 1956").

3. REQUIREMENTS

3.1 General.

3.1.1 The One Inch Cartridges (Bomb Ejector) Mark 1 Mod 2, Mark 1 Mod 3, Mark 2 Mod 0, and Mark 2 Mod 1 covered by this specification shall be manufactured in accordance with LD 166557, LD 276296, LD 255610, and LD 276297, respectively.

3.1.2 *Preproduction sample.* Unless otherwise specified in the contract or order (see 6.2), a preproduction sample of loaders shall be manufactured by the contractor using the methods and processes he proposes to use for the production of this item. This sample will be inspected as specified in 4.4.1, and is for the purpose of determining that the contractor's production methods and processes are capable of producing items that comply with the requirements of this specification.

3.2 **Insulation resistance.** Prior to assembly of bridge wires in the ignition element assembly, the insulation resistance between the center electrode and the ignition cup shall not be less than 50 megohms when measured with an imposed EMF (Electromotive force) of 500 volts D. C. and at a relative humidity of less than 80 percent.

3.3 **Bridge wire.** The bridge wire shall be soldered to the ignition cup and center electrode. The solder shall be as specified on the applicable drawing. Resin flux shall be used in the soldering operation. Particular care shall be taken to insure thorough soldering and absence of "cold joints" or other defective conditions.

3.4 **Bridge wire subassembly, continuity.** Before assembling the bridge wire subassembly into the ignition element subassembly, it shall be thoroughly cleaned to remove solder flux and contamination. After cleaning, the bridge wire shall be flashed by application of an electric current to assure continuity of both legs of the bridge wire. The current shall be regulated to produce a visible red glow of the bridges. An Electromotive Force (EMF) of approximately 1.5 volts alternating current (ac) or (dc) direct current may be used with a suitable series resistor to adapt the generator characteristics to the primer resistance. Flashing is a necessary manufacturing operation and shall be conducted on each subassembly. Subassemblies which fail to glow in both legs of the bridge shall be screened from acceptable material in the process. The discarded subassemblies may be reworked by replacement of the bridge.

3.5 **Bridge wire resistance.** Each completely assembled and loaded cartridge shall be tested electrically as specified in 4.6.1. The bridge wire resistance of each cartridge shall not be less than 0.11 ohm nor more than 0.18 ohm. The cartridges shall be 100 percent inspected for conformance with this requirement.

3.6 **Priming composition.** The priming composition shall be compounded by a method which maintains the weight composition of non-volatile constituents as specified on the applicable drawings. The finished composition when ready for buttering into the ignition element assembly shall be a uniformly mixed slurry in which all particles are wetted. The consistency shall be such that the liquid will not separate from the mixture when the dish is tilted. Adjustment of the consistency may be obtained by the addition of pure butyl acetate or by evaporation of the solvent. Any adjustment shall be followed by thorough remixing. An advisory method for preparation of the primer composition is specified in 6.5.

3.7 **Loading of priming compound.** The technique of wet loading the priming compound shall be such as to avoid damage to the bridge wire. The priming composition, when consolidated to assure freedom from voids, shall be smoothed off flush with the top of the cavity. All priming composition shall be removed from exterior lateral areas of the ignition cup by means of a clean

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

cloth wet with butyl acetate. The igniter shall be dried at a temperature of 120 degrees fahrenheit F° for a minimum period of 16 hours after crimping the ignition element assembly into the bushing assembly. The dried priming composition shall be free from cracks, voids, and separation from the ignition cup. The charge shall entirely cover the bridge wire. The exterior surface of the inner cup shall be free from priming composition. An advisory technique for loading and handling lead styphnate priming composition is specified in 6.4.

3.8 **Powder.** Each cartridge lot shall contain only black powder from a single powder lot. This requirement also applies for the smokeless powder. All powder shall be stored in hermetically sealed containers at all times.

3.9 **Assembly of cartridge.** The cartridge shall be assembled as specified in 3.9.1 through 3.9.3.

3.9.1 In order to prevent cracking of primer mixture, the ignition element shall be assembled with bushing assembly while primer mixture is still moist. This requirement will also reduce the danger of the primer mixture igniting during the assembly operation.

3.9.2 After the igniter has been assembled with bushing assembly, the primer mixture should be thoroughly dried in an oven, the temperature of which shall not exceed 120 degrees F. A suggested temperature and drying time is 110 degrees F for 12 hours.

3.9.3 When securing booster cup in place, the quantity of shellac paste utilized should be limited to the amount which will dry before other parts are assembled.

3.10 **Cartridge weight.** The weight of the cartridge shall not vary more than plus or minus 3.0 standard deviations from the average weight of the first 100 cartridges manufactured. (See 4.6.2).

3.11 **Ballistics and functioning.** The cartridges when fired using the test assembly described in 4.6.3.1 shall have a hook opening time no greater than 100 milliseconds and the average horizontal velocity imparted to the bomb shall not be less than 6.4 feet per second. (See 4.6.3.1, 4.6.3.2, and 4.6.3.3.)

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4.1 **Supplier's responsibility.** The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplier and services conform to prescribed requirements.

4.2 **Sampling.** Unless otherwise specified (see 3.5) and when applicable, the sampling plans and procedures used by the Government inspector in the determination of the acceptability of products submitted by a supplier for Government inspection will be in accordance with the provisions of Standard MIL–STD–105.

4.2.1 *Lot.* As applied to the Government inspection of units of product, the term "lot" shall mean "inspection lot", i.e., a collection of units of the product used as a basis for Government inspection. "A lot shall consist only of cartridges of one mark and mod manufactured under essentially the same conditions and submitted for inspection at the same time." Unless otherwise specified, the number of units of product in "inspection lots" shall be as determined by the Government inspector, and may differ from the quantity designated in the contract or order as a lot for production, shipment, or other purpose.

4.2.2 *Production lot.* For procurement purposes the production lot shall consist of not less than 1301 or more than 20,000 completely loaded cartridges of one Mark and

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

Mod plus those required for all test purposes. Unless otherwise stated (see 6.2), all units for test purposes shall be provided at the expense of the contractor. The production lot should not be confused with the lot for inspection purposes as defined in 4.2.1.

4.3 Preproduction sample. Before entering into quantity production, a preproduction sample of 150 completely loaded cartridges of the specified Mark and Mod shall be delivered by the contractor for test to an agency designated by the procuring activity. The number of units subjected to each test shall be determined on the basis of a lot size of 1301 units. These cartridges shall be manufactured by the same procedures and processes and at the same location proposed by the contractor for the execution of the contract. Prior to submission of the preproduction sample for acceptance, the cartridges shall have received the same degree of component and assembly inspection as that which will be employed on production lots. When a preproduction sample is received which complies with all the quality assurance requirements of this specification, the contractor will be notified and will be authorized by the procuring activity to proceed with the submission of the product for acceptance. Accepted samples will become the property of the procuring activity and will be included in the number called for in the contract schedule.

4.3.1 *Preproduction sample for a subsequent contract.* The necessity for a preproduction sample will be determined by the procuring activity when production under a new contract by the same contractor at the same location follows the manufacture of satisfactory material as covered by this specification. (See 6.2.)

4.4 Government inspection. Government inspection and acceptance of supplies furnished hereunder will be in accordance with the contract or order and this specification.

4.4.1 *Preproduction inspection.* Unless otherwise specified in the contract or order (see 6.2), the Government will be responsible for the performance of the preproduction inspection. The samples specified in 4.3 will be examined and tested to determine compliance with the requirements specified herein. Government approval of the results of the preproduction inspection will be based on compliance of the samples with the specified requirements.

4.5 Quality control system. Except as otherwise specified herein, the contractor shall establish and maintain a system for the control of the quality of material offered for Government acceptance. Quality control systems so established shall be in accordance with Section 3, Requirements, of Specification MIL–Q–9858.

4.6 Test procedures.

4.6.1 *Bridge wire resistance.* Conformance with the bridge circuit resistance requirement of 3.5 shall be ascertained by means of a test circuit which limits the bridge current to 50 millamperes, maximum. A safety chamber with an interlock switch shall be used to protect the operator during application of the current. A suitable bridge which is known to be accurate within 0.005 ohm in the range of resistance specified shall be utilized to determine whether or not the resistance requirement is being met.

4.6.2 *Cartridge weight test.* After completion of the assembly and loading, cartridges shall be selected for weighing from each lot in accordance with MIL–STD–105, Inspection Level I, AQL of 1.0 percent defective. A cartridge having weight, which varies more than plus or minus 3.0 standard deviations from the average weight of the first 100 cartridges manufactured shall be classed as defective. Disposition of the lot shall be in accordance with the sampling plan given above.

4.6.2.1 *Computation of standard deviation.* The standard deviation(s) of the weights of the first 100 cartridges manufactured shall be computed as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:47Z
Check the source to verify that this is the current version before use.

$$S=\sqrt{\frac{\Sigma x^2-(\Sigma x)^2}{n-1\ n\ (n-1)}}$$

x= cartridge weight
n= 100
Σx^2= summation of the squares of individual cartridge weights
Σx= summation of individual cartridge weights
$(\Sigma x)^2$= square of summation of individual cartridge weights

4.6.3 *Ballistics and functioning tests.*

4.6.3.1 *Assembly for test.* For test firing the Mk 1 and Mods cartridges, a 2000 pound general purpose shall be mounted in a standard bomb ejector; for the Mk 2 and Mods cartridges, a 250 pound general purpose bomb shall be used. Both bombs shall be inertly loaded to service weight. The position of the ejector shall be such that when a bomb is mounted in the ejector nose down, axis vertical, its nose shall be held seven (7) feet six (6) inches from the ground. A type K–2 intervalometer with a 20 Volt dc release circuit of 2.0 +0.2 ohms resistance shall be used in firing cartridges. Normally, the intervalometer shall be calibrated and fired at control position No. 21. Suitable instrumentation for determining the time from the closing of the firing circuit to the opening of one of the bomb ejector hooks shall be installed and shall be accurate within plus or minus 1.0 millisecond.

4.6.3.2 *Ballistics test.* Cartridges shall be selected and tested from each lot in accordance with MIL–STD–414, Inspection Level I, AQL 0.10 percent defective. The cartridges shall be fired using the test assembly prescribed in 4.6.3.1. The hook opening time and horizontal travel of the bomb (d) shall be observed for each cartridge. The single upper acceptance limit for the hook opening time shall be 100 milliseconds and the single lower acceptance limit for the horizontal velocity (v) shall be 6.4 feet per second where:

$v=d\sqrt{\frac{g}{2h}}=1.465d$—individual velocity at ejection, in feet per second.

Additionally, all the cartridges tested shall fire on the first pulse of the intervalometer. Acceptance of the lot on the basis of hook opening time and also on the basis of horizontal velocity measurements shall be in accordance with the sampling plan given above. In addition any single observation exceeding the applicable upper or lower acceptance limit shall automatically result in the rejection of the lot represented.

4.6.3.3 *Functioning test.* A sample of cartridges shall be randomly selected from each lot for subjection to the functioning test. Sample size shall be determined in accordance with MIL–STD–105, Inspection Level II. The sample selected and ballistically tested in accordance with 4.6.3.2 may be included as a portion of the functioning test sample. The functioning failure of one or more cartridges on the first impulse of the intervalometer shall result in rejection of the lot represented.

4.7 **Inspection of preparation for delivery.** The preservation, packaging, packing, and marking of the cartridges shall be examined and tested to determine conformance with the requirements of Section 5 of this specification. Inspection lots and sampling shall be in accordance with Standard MIL–STD–105, Inspection Level L–7, and a AQL of 4.0 percent defective.

5. PREPARATION FOR DELIVERY

5.1 **Packaging.**

5.1.1 *Level A.*

5.1.1.1 Twenty-six (26) cartridges of one mark and mod shall be packaged in hermetically sealed containers as specified on Bureau of Ordnance Drawing No. 561986.

5.1.2 *Level C.*

5.1.2.1 Twenty-five (25) cartridges, of one mark and mod shall be packaged in a manner which will afford adequate protection from deterioration and physical damage during shipment from the contractor or supply source to the first receiving activity for immediate use.

5.2 **Packing.**

5.2.1 *Level A.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

5.2.1.1 Five hundred and twenty (520) cartridges of one mark and mod, packaged as specified in 5.1.1.1 shall be packed in a nailed wood box as specified on Bureau of Ordnance Drawing No. 561986.

5.2.2 *Level C.*

5.2.2.1 Five hundred (500) cartridges of one mark and mod, packaged as specified in 5.1.2.1 shall be packed in a manner which will provide protection from damage during direct shipment from the contractor or supply source to the first receiving activity for immediate use. The type of containers used shall conform to the Code of Federal Regulations 49CFR71–90.

5.3 **Marking.**

5.3.1 In addition to any special marking required (see 6.2) all marking shall be in accordance with Military Standard MIL–STD–129 and Code of Federal Regulations 49CFR71–90.

6. NOTES

6.1 **Intended use.** The cartridges covered by this specification are intended to be used for releasing and ejecting bombs and other stores from aircraft bomb racks and launchers.

6.2 **Ordering data.** Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Mark and mod of required cartridge (Bomb Ejector) (see 1.1).
c. Whether or not preproduction sample is required (see 4.3.1).
d. Who shall furnish units for test purposes, if different from 4.2.1.
e. Level of packaging and level of packing (see 5.1 and 5.2) (Level C shall not be specified unless it is definitely known that the cartridges will be used immediately upon receipt.)
f. Special marking if required (see 5.3.1).

6.3 **General safety precautions.** The loading, assembly, and handling of explosives, ammunition, ammunition components, fuzes, detonators, primers, tracers, boosters, pyrotechnics, etc., and subassemblies thereof, involve hazardous operations and therefore require suitable explosives safety precautions. Use of this specification shall not be construed as to relieve the contractor or manufacturer of responsibility for the safety of his operations. Listed below are the minimum provisions which a contractor or manufacturer (loader) of the above items should observe in order to fulfill his responsibility for safety. In government plants, these provisions are mandatory. Such other warnings and precautions, pertinent to the operational effectiveness or safety during use or loading of the specified item, are included in the detail provisions of the specification.

6.3.1 All loading operations should be conducted in a neat and orderly manner.

6.3.2 Safe equipment and methods should be utilized for transporting and handling explosives and loaded parts. Where required, remote control barricaded handling equipment shall be used for explosives operations, such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.3.3 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which effect functioning, should in so far as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from prespiration or other contaminating deposits.

6.3.4 The exposure of explosive materials and related parts should be controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.3.5 All explosives and completely or partially loaded items should be stored in suitable storage magazines located in accordance with the American Table of Distances (A T D) or other applicable safety stand-

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:47Z
Check the source to verify that this is the current version before use.

ards; and, while in process, in safety lockers and chests if in loading rooms, or in adequate ready or service magazines located in accordance with Intraplant distances when outside of loading rooms. For government explosives loading plants, the provisions of the Armed Services Explosives Safety Board covering quantity-distance relations for explosives, shall apply.

6.3.6 Proper care should be exercised at all times to protect personnel from accidents, fires or explosives, and to limit damage to equipment and loading areas. In this connection, the following precautionary measures should be observed:

6.3.6.1 Employ properly proportioned and properly located protective barricades, screens, or shields at all required points.

6.3.6.2 Keep only minimum limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.3.6.3 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out of or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges.

6.3.6.4 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches, and table, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges should be employed. Fabrics such as silk and nylon, which promote static generation should be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low-energy type electric primers, detonators, and squibs. The latter types of items should have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapper in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blasts, also electrical shielding of these items from induced electric currents generated by sources such as lightning, static, radiations from communications apparatus, radar, or high frequency heating apparatus, etc. Where necessary for safety, humidity (see paragraph 6.3.4) of work rooms should be increased, as required to lessen electrostatic effects without excessive moisture absorption.

6.3.6.5 Protect all explosive operations from effects of electric current originating from equipment such as soldering irons, heaters, switches, wiring, motors, lights, test instruments, etc., by suitable insulation, grounding, separation, or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or due to completing an electric circuit through an electric primer, detonator, or squib. Circuits may be inadvertently completed, for example, from a defective electric soldering iron through a grounded contact. All electric type primers, detonators or squibs provided with wire leads should have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Where practicable, removable short circuiting clips, or other devices should be employed during manufacturing operations involving electric primers, detonators, or squibs.

6.3.6.6 Enforce, where necessary, the wearing of suitable footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning, and associated industrial hazards.

6.3.6.7 Allow no fires or exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling, and storage spaces. Enforce

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

proper "Match" and "No Smoking" rules where necessary.

6.3.6.8 Enforce good housekeeping and maintain effective policing, inspection, and supervisory methods throughout the loading area and surroundings. Employ effective cleaning methods periodically to minimize the accumulation of explosive dust and other contamination upon, and assure its removal from floors, walls, ceilings, ledges, tables, benches, piping, and equipment or the items loaded; also, clean up any spilled material immediately.

6.4 Advisory technique for the loading and handling of the priming composition.

6.4.1 The loading room shall have a relative humidity of 70 to 80 percent. The moisture content shall be maintained at all times.

6.4.2 Only approximately two grams of priming composition shall be present at each loading station and only when an operator is present.

6.4.3 Any composition which is spilled shall be cleaned up immediately by means of a cloth wet with butyl acetate; the soiled cloth shall be placed in a special disposal can.

6.4.4 The mixing and loading of the priming composition shall be done behind an approved shield whenever possible.

6.4.5 All fixtures, equipment, benches, floors, etc., shall be properly grounded to prevent accidental ignition due to static discharges, electrical arcing, or sparking.

6.4.6 Butyl acetate confers a degree of resistance to explosion and ignition by impact and friction. However, it is emphasized that the resistance to explosion obtained by wetting with butyl acetate is of a lower order than that obtained by water wetting. Butyl acetate is inflammable and can produce vapors which can ignite at dry house temperatures. Excess inhalation of vapors of butyl acetate should be avoided. Use with adequate ventilation, avoid prolonged or repeated contact with skin.

6.4.7 The loading dish shall be constantly checked to prevent the mixture from becoming too dry, particularly around the edges and on the top of the dish. If necessary, the operator shall add butyl acetate and work the mixture to the proper buttering consistency.

6.4.8 To charge the ignition element assembly with priming compound, convey sufficient composition on a non-sparking spatula to butter one unit. Scrape off, and press the composition into the ignition cup cavity using short strokes downward and outward. Excess composition shall be scraped off flush with the surface of the ignition cup. The bridge wire shall not be visible.

6.4.9 Clean off all excess mixture from the sides of the inner cup using clean muslin wet with butyl acetate.

6.4.10 Lead styphnate is characterized by unusual sensitivity to electrical discharges. Precautions such as grounding and cleanliness of tools and utensils shall be observed.

6.5 Advisory method for the preparation of the priming composition.

6.5.1 A small amount, approximately ten milliliters of water slurry of lead styphnate as received, is placed in a tared conductive rubber dish. The styphnate is allowed to settle and the supernatant water is removed by decantation or siphoning.

6.5.2 Approximately 25 milliliters of ethanol is added and the mixture stirred gently, settled, and siphoned.

6.5.3 An additional 25 milliliters of ethanol is added and the stirring, settling, and siphoning repeated.

6.5.4 The remaining mixture is air-dried at ambient temperature for two hours and then oven-dried for 12 hours at 50 degrees C.

6.5.5 The dry weight of the styphnate is determined.

6.5.6 In a separate container, dry cellulose nitrate equivalent to two percent of the dry weight of the lead styphnate is mixed with butyl acetate to make approximate ½ per-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:47Z
Check the source to verify that this is the current version before use.

cent solution. (A weighed quantity of gravimetrically standardized stock solution of approximately ½ percent cellulose nitrate concentration may be used to obtain the two percent of cellulose nitrate required.)

6.5.7 The solution specified in 6.5.6 is added to the dry styphnate and mixed until the styphnate is thoroughly wetted.

6.6 Attention is directed to the press fit requirement between the Electrode, Electrode Insulator, and the Ignition Cup. Due to the plastic quality of the Electrode Insulator and the changes it undergoes when stores rather than assembled immediately, the manufacturer must by experimentation arrive at the dimensions and tolerances best suited to his methods of manufacture and assembly.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Air Force—Wright Air Development Center

Preparing Activity:
Navy—Bureau of Naval Weapons

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:47Z
Check the source to verify that this is the current version before use.