MIL-F-18680C(MC)
28 February 1985
SUPERSEDING
MIL-F-18680B(MC)
22 September 1970

MILITARY SPECIFICATION

FLY, TENT: FIRE, WATER, WEATHER, AND MILDEW RESISTANT

This specification is approved for use by U. S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for one type and size of tent fly having the following dimensions:

Length of sides - 20 feet 7 inches
Width when laid out flat - 25 feet

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

T-T-871	- Twine, Fibrous Cotton, Wrapping.
V-T-285	- Thread, Polyester.
QQ-S-781	- Strapping, Steel and Seals.
CCC-C-429	- Cloth, Osnaburg, Cotton.
CCC-C-467	- Cloth, Burlap, Jute (Or Kenaf).
DDD-L-20	- Label; For Clothing, Equipage, And Tentage (General Use).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commandant of the Marine Corps, Headquarters, U. S. Marine Corps (Code LMA-1), Washington, DC 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 8340

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1709	- Line, Tent.
MIL-S-1734	- Slip, Tent Line.
MIL-G-16491	- Grommet, Metallic.
MIL-C-43627	- Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Light Dry Finish.

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, And Stitchings.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.
MIL-STD-147	- Palletized Unit Loads.

DRAWING

Marine Corps

P-196	- Fly, Tent; Fire, Water, Weather And Mildew Resistant.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association Inc., Tariff Order Section, 1616 P Street, N. W., Washington, D. C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Guide samples. The guide samples are furnished solely for guidance and information to the contractor (see 6.3). Variation from the specification may appear in the sample, in which case the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a finished fly tent shall be submitted, or made available to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with applicable provisions of the specification. The first article shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

3.3.1 Cloth, cotton, duck. The cloth, before finishing, shall be 9.85 ounce per square yard, conforming to MIL-C-43627. The cotton duck shall be dyed Olive drab 7.

3.3.2 Thread, polyester. The thread shall conform to type I or type II, class 1, subclass B, size E, of V-T-285. The thread shall be dyed Olive drab shade S-1 (Cable No. 66022). The dyed thread shall show good fastness to weathering.

3.3.3 Line, tent. The rope for the lines shall be manila or sisal, 1 inch circumference, 11 feet 6 inches long, conforming to type XIX, class A for manila rope or class B for sisal rope of MIL-L-1709. In lieu of stitching or serging the end of the lines with thread or twine in order to prevent raveling, the end may be bound with brass wire or may be finished with rust-resistant wire clips.

3.3.4 Slips, tent line. The tent line slips shall conform to type II of MIL-S-1734.

3.3.5 Grommets and washers. Grommets and washers shall be brass, black oxide finish, rolled rim grommet, spur washer, conforming to type III, class 3, No. 4 and No. 7 of MIL-G-16491. Grommets and washers for the side edges of the fly shall be No. 4, and for the back and front edges shall be No. 7, as shown in Drawing No. P-196.

3.4 Design and construction. The design and construction shall conform to Drawing No. P-196 and the following.

3.4.1 Stitches, seams, and stitching. The stitch, seam and stitching types specified herein shall conform to FED-STD-751. All panels shall be joined with stitch type 301 or type 401 as follows. The seams forming hems and attaching ridge reinforcement and corner patches shall be accomplished with

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

stitch type 301. All seaming and stitching shall be done with 5 to 6 stitches per inch. Thread ends shall be trimmed to 1/2 inch or less.

3.4.1.1 Type 301 stitching. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched at the ends to prevent raveling, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained properly so that there will be no loose stitching and that the lock will be embedded in the center of the materials sewed.

3.4.1.2 Type 401 stitching. Thread breaks in stitching shall be overstitched not less than 1-1/2 inches at each break. Thread tension shall be maintained properly so that there will be no loose stitching. The looper (underthread) shall be on the underside of the fly.

3.4.2 Panels. Panels shall be full width duck with selvages on both sides, except flies may be pieced out to the size specified on Drawing No. P-196 with split duck. Split duck shall have a selvage on one edge and shall be used for end panels only, with the selvage edge joined to the adjacent panel, and the raw edge hemmed to provide a finished back or front edge for the fly. Panels, other than end panels, may be pieced to the length specified in Drawing No. P-196, except there shall be not more than two pieces in a panel, not more than three pieced panels in a fly, no piecing at the ridge location, and pieced panels shall not be placed adjacent to each other. Panels shall be pieced with seam type LSc-2, stitch type 301 or type 401, with the folded edge of the seam on the upper side of the fly faced away from the ridge area to prevent water being caught in the seam. Panels shall be joined with seam type LSa-2, stitch type 301 or type 401, with selvages lapped 1 inch and double needle stitching 3/4-inch gage.

3.4.3 Corner reinforcement patches. Reinforcement patches for each corner of the fly shall be of basic material. Patches shall be cut 15X15 inches square and then further cut in half diagonally to form two triangular patches. Raw edges of patches, except edges finishing under hems, shall be turned under not less than 1/2 inch and the patches shall be stitched to the underside of the fly with a single row of stitches along the folded edge, with seam type LSd-1, stitch type 301, as shown in Drawing No. P-196.

3.4.4 Ridge reinforcement. The fly shall be reinforced with a 15-inch-wide strip of cotton duck from the front to back edges at the ridge location as shown in Drawing No. P-196. The reinforcement shall be centered on underside and stitched using seam type LSd-1, stitch type 301, with raw edges, except those finishing in front and back hems, turned under not less than 1/2 inch. The selvage edge is not required to be turned under.

3.4.5 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the material or splitting the grommet. The No. 4 grommets and washers shall be placed at the locations and dimensions indicated on each panel, through all the plies of the hems, seams and corner reinforcement patches, as shown in Drawing No. P-196. The No. 7 grommets and washers shall be centered on the hem at the locations indicated at the ridge (one at back

Source: https://assist.dla.mil -- Downloaded: 20260-18T11:48Z
Check the source to verify that this is the current version before use.

edge and one at front edge of fly) through all the plies of the hem and ridge reinforcement, as shown in Drawing No. P-196.

3.4.6 Hems. Ends of panels and front and back edges of the fly shall be hemmed, with hem to finish 2-1/2 inches wide, and raw edge or selvage, as applicable, turned under 1/2 inch, seam type EFb-1, stitch type 301, except width of finished hem at front and back edges of fly, and amount of material turned under the hem, may be increased to 3-1/2 inches to permit fly to be finished to size specified on Drawing No. P-196 without trimming.

3.4.7 Lines and tent slips. Lines and tent slips shall be properly assembled to the fly through each No. 4 grommet.

3.4.8 Stitch identification label. The identification label shall be stitched on all edges to the underside of the fly at the location shown on Drawing No. P-196. One edge of the label may be caught in the hem.

3.5 Finished measurements. The finished fly shall conform to the measurements shown on Drawing No. P-196.

3.6 Identification and marking. Each fly shall have an identification label conforming to type II, class 6 of DDD-L-20 except that a blank space of not less than 1-1/4 inches shall be provided on the bottom of the label for the Department of Defense Inspector's stamp. The nomenclature may be abbreviated to Fly, Tent; FWWMR. The letters "U. S." shall be applied on the upper side of the fly in 4-inch high block letters, in the locations shown in Drawing No. P-196 and shall conform to the requirements for type IV, class 9 labels of DDD-L-20. Fastness of the class 9 labels shall be as specified for class 6 labels.

3.7 Workmanship. The finished flies shall conform to the quality and grade of product established by this specification. Occurrence of defects shall not exceed the applicable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When a certificate of compliance is permitted, the Government reserves the right to check test such items and determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, inspection shall be in accordance with MIL-STD-105.

4.4 First article inspection. The first article, submitted in accordance with 3.2, shall be inspected as specified in 4.5.3.1 and 4.5.3.2 for compliance with design, contruction, workmanship and dimensional requirements of this specification.

4.5 Quality conformance inspection.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable acquisition document.

4.5.2 In-process inspection. Inspection shall be made to assure the following:

(1) That holes punched to receive grommets are in compliance with 3.4.5.

(2) That nonwicking thread is not lubricated by any means prior to or during sewing operations.

4.5.3 Examination of end item. The end item shall be examined for the defects listed in 4.5.3.1 and 4.5.3.2. The applicable inspection levels and AQLs shall be as indicated in 4.5.3.3. The lot size shall be expressed in units of flies. The sample unit shall be one finished fly.

4.5.3.1 General defects. General defects shall be classified as follows:

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
Fabric	a. Holes, cuts or tears, broken or missing yarns, floats or smashes:			
	1. - Seriously affecting serviceability.	X		
	2. - Affecting serviceability, but not seriously.		X	
Hardware	a. Broken or malformed; burrs or sharp edges which may damage the item or cause injury in handling.	X		
	b. Finish omitted or not as specified.		X	

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:48Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
Grommets	a. Size or type not as specified: - seriously affecting serviceability.	X		
	- affecting serviceability, but not seriously.		X	
	b. Improperly set, i.e., clinched loosely, causing grommet to rotate around hole.			X
	c. Clinched excessively tight, cutting fabric, or loosely clinched, i.e., grommet and washer become disengaged.	X		
	d. Eave grommets set off center of panel joining seams by 1/4 inch or more.		X	
	e. Ridge grommets set off center of ridge: - by more than 1/2 inch, but less than 1 inch.		X	
	- by more than 1 inch.	X		
Rope component	a. Cuts or abrasion; eye splice omitted.		X	
	b. Eye splice not as specified; free ends not finished as specified; less than specified length by more than 2 inches; eye on tent lines less than specified by more than 1/2 inch.			X
Seams and stitching	a. Open seams:			
	On stitch type 301: - not more than 1 inch.			X
	- more than 1 inch.		X	
	On stitch type 401, except run-offs.	X		
	b. Run offs on stitch type 401: - more than 1/2 inch, but not more than 1 inch.			X
	- more than 1 inch.		X	

NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more consecutive skipped stitches or runoffs occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
	c. Raw edges: When securely caught in stitching: - more than 1 inch, but not more than 3 inches. - more than 3 inches.		 X	 X
NOTE: Raw edges not securely caught in stitching shall be classified as open seams.				
	d. Runoffs (see open seams).			
	e. Wrong seam or stitch type.	X		
	f. Stitch tension: Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in excessive tightness or puckering of fabric on seams.			X
	g. Stitches per inch: 1. One stitch less than minimum specified. 2. Two or more stitches less than minimum specified. 3. One or more stitches in excess of maximum specified.		 X 	 X X
NOTE: Variation in the number of stitches per inch, caused by the operator's speeding up the machine and pulling fabric in order to sew over heavy seams or heavy places or turning corners, shall be classified as follows: (a) Within the Minor B defect classification - No defect (b) Within the Minor A defect classification - Minor B defect				
	h. Stitch margin: Not as specified.	X		
	i. Stitching gage: Not as specified.	X		
	j. Thread breaks: Overstitched less than 1-1/2 inches on stitch type 401; backstitched less than 1 inch on stitch type 301.		X	
NOTE: Thread breaks not backstitched or not overstitched shall be classified as open seams.				

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
	k. Stitching ends: Not backstitched (except where stitching ends are held down by other stitching or turned under in a hem).		X	
	l. Stitch type 401: Chain portion of stitching shown on outside of fly.		X	
	m. Any required row of stitching omitted.	X		
Components and assembly	a. Any required component or operation omitted (unless otherwise specified herein).	X		
	b. Needle chews expected to develop into a hole.	X		
	c. Seams badly pleated or puckered.			X
Repairs	a. Mends, darns or patches.	X		
	b. Twisted or pleated; less than specified width by more than 1/4 inch.			X
Reinforcements (ridge and corners)	a. Misplaced, failing to reinforce corners or ridge.	X		
	b. Ridge reinforcement set off center of fly by more than 1 inch.		X	
	c. Finished dimension less than specified by more than 1/2 inch.			X
	d. Improperly applied, causing excessive fullness on reinforcements or reinforced parts.			X
	e. Not stitched to reinforced parts on all sides or not caught in seams or stitching of reinforced parts.		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
Panels	a. End panels spliced.	X		
	b. More than 2 pieces per panel.	X		
	c. More than 3 panels spliced.		X	
	d. Adjacent panels spliced.		X	
	e. Panels spliced at ridge location.	X		
Marking	Omitted, incorrect, illegible or misplaced.			X
Cleanness	Noticeable grease or oil stains, thread ends not trimmed throughout			X

4.5.3.2 Dimensional defects. Dimensional defects shall be classified as follows:

Overall dimensions	a. Smaller than nominal dimensions, less the applicable minus tolerance indicated on Drawing No. P-196.	X		
	b. Larger than nominal dimensions and applicable plus tolerance indicated on Drawing No. P-196.		X	

4.5.3.3 Inspection level and acceptable quality levels. Inspection levels and AQL's expressed in defects per 100 units (DHU) shall be as follows:

	AQL	Inspection level
For 4.5.3.1		
Major	15.0 DHU	I of MIL-STD-105
Major and Minor A (combined)	40.0 DHU	I of MIL-STD-105
Total (Major, Minor A and B combined)	100.0 DHU	I of MIL-STD-105
For 4.5.3.2		
One class	2.5 DHU	S-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

4.5.4 Examination of packaging requirements. An examination shall be made to determine compliance with packaging, packing and marking requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one completely wrapped fly fully prepared for delivery. The lot size shall be the number of completely wrapped flies offered for delivery at one time. The inspection level shall be S-2 and the AQL shall be 2.5 DHU.

Examine	Defect
Marking	Omitted; incorrect; illegible; wrong color or improper size, location, sequence or method of application.
Materials	Any component missing.
	Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of cloth wrapping and loose stitching.

5. PACKAGING

5.1 Packaging. Packaging shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each fly, with lines and tent slips completely attached shall be folded in a compact bundle, care being exercised to expel as much air as possible from between the folds during each folding operation. All lines and hardware shall be placed well inside the bundle as near to the center as practicable, in order that the hardware may be cushioned by the canvas. Each fly shall be folded in the same manner, and all bundles shall finish the same size.

5.1.2 Commercial. Each fly shall be packaged in accordance with industry's practice.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. Each fly, packaged as specified in 5.1 shall be wrapped and sewn in cotton, osnaburg cloth conforming to class 2 of CCC-C-429 or burlap cloth conforming to class 3 of CCC-C-467. The wrapping shall be sewn with 16-ply cotton twine conforming to T-T-871, with approximately one stitch to the inch and every third stitch knotted. Five inches of surplus covering shall be gathered together on each of the four corners and securely sewn into ears for handles. Alternatively, the cloth may be packed in a snug fitting tubing form and closed in the manner specified above. Each bundle shall be strapped, girthwise, with four flat steel straps conforming to type I, class B, grade 2 of QQ-S-781, spaced equal distances apart.

5.2.2 Commercial. Each fly, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate. Containers shall be in accordance with Uniform Freight Classification Rules and National Motor Freight Classification or regulations of other carriers applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or purchase order, cloth covered bundles shall be marked in accordance with MIL-STD-129.

5.4 Palletization. When specified (see 6.2), flies packed as specified in 5.2 shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

6. NOTES

6.1 Intended use. The fly is intended to be used for a storage tent and as a covering for outdoor field kitchens.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Whether first article is required (see 3.2).
(c) Applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When palletization is required (see 5.4)

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph no.	Data requirements	Applicable DID no.	Options
(a) 4.2	Inspection System Program Plan	DI-R-4803	- -
(b) 4.4	First Article Inspection Procedure	DI-T-4901	- -
(c) 4.4	First Article Inspection Report	DI-T-4902	- -
(d) 4.5	Failure Report	DI-R-4805	- -

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:48Z
Check the source to verify that this is the currentversion before use.

data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Guide samples. The guide sample may be obtained from the procuring activity or as directed by the contracting officer.

6.4 First article. Examinations, tests and approval shall be as specified by the contracting officer (see 3.2).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - MC
Project No. 8340-N449

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-18680C(MC)	Fly, Tent: Fire, Water, Weather, and Mildew Resistant

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commandant of the Marine Corps
Headquarters, U. S. Marine Corps
Code LMA-1
Washington, D. C. 20380

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:48Z
Check the source to verify that this is the current version before use.