MILITARY SPECIFICATION

FUZE, DETONATING, MARK 27 MOD 0 AND MOD 1
(40 MM)

This amendment forms a part of Military Specification MIL-F-18698(NOrd) 2 June 1955.

Page 6, paragraph 4.5.1, line 2: Change "2" to "5".

Page 7, paragraph 4.5.2, line 1: Change "Two" to "Five".

Page 7, paragraph 4.5.3: Change to read as follows:

"4.5.3 Forty (40) foot drop test.--Six completely live loaded fuzes shall be selected from each production lot. These fuzes shall be installed by a suitable means in six 40 mm. complete rounds which are inertly loaded to weight, and subjected to the 40 foot test prescribed in Standard MIL-STD-352. Two rounds shall be dropped on their nose, two on their side and two on their base. Failure of any of the sample fuzes to pass this test shall cause rejection of the lot."

Page 7, paragraph 4.5.4: Add the following sentence: "Failure of a fuze to comply with the prescribed requirements of that test shall result in the rejection of the lot represented."

Page 7, paragraph 4.6, line 1: Change "Two" to "Five".

Page 7, paragraph 4.6: Ad the following after the second sentence:

"Failure of a fuze to comply with these requirements shall result in the rejection of the lot represented."

Page 7, paragraph 4.7: Change "AQL 1.5 percent, Table I" to "AQL 1.0 percent, Table VI-I".

Page 7, paragraph 4.7.2: Delete in its entirety and insert the following:

"4.7.2 Severity of inspection.--The requirements for the application of normal,reduced or tightened inspection shall be as specified in Standard MIL-STD-105."

Page 8, paragraph 4.8: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 202610-18T11:50Z
Check the source to verify that this is the current version before use.