MILITARY SPECIFICATION

PRIMER MARK 101 MOD 3

This amendment forms a part of Military Specification MIL-P-18612A(OS), dated 3 January 1975.

PAGE 1

At bottom of page add:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Division (611), Indian Head, MD 20640, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 3

3.3: After "percent" insert "by weight".

3.4, last sentence: After "dry storage conditions" insert "(60% relative humidity, maximum)".

PAGE 4

3.5: Delete in its entirety and substitute

"3.5 Primer sensitivity. The primer shall be subjected to the sensitivity test of 4.5.2. The primer's sensitivity to firing pin impact shall be used for process control. Record the 50 percent firing height and the standard deviation on the Ammunition Data Card."

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:45Z
Check the source to verify that this is the current version before use.

3.6: Delete in its entirety and substitute

"3.6 Primer functioning (M103). The primer shall be subjected to the function test of 4.5.3. The primer shall function on firing pin impact."

3.7: Delete "The primers - - - 4.5.4" and substitute "The primer shall be subjected to the simulated delay element function test of 4.5.4. The primer shall function on firing pin impact, without blowback, or rupture of the primer cup."

PAGE 5

4.3: At end of paragraph add new sentence "Two or more failures, during the function tests (see 4.5.3 and 4.5.4), shall cause rejection of the sample."

PAGE 6

4.4: Delete first sentence and substitute "A production lot, for procurement purposes, shall consist of a maximum of 10,000 primers plus the number of primers required for all test purposes."

4.5.1, line 2: Replace "test for each lot of primers and such" with "moisture test on each batch of primer mixture per day plus such". Line 5: change "material being loaded" to "primer mixture". After "28 inches" add: "(711 mm)". After "All weighings shall be accurate to ± 0.5 milligrams." insert "Calculate the loss in weight of the primer mixture as percentage moisture in the sample."

PAGE 7

4.5.2, after "0.50 inch" add: "(12.7 mm)". At end of paragraph add "Deviations in sensitivity from lot to lot shall cause checking materials and processes for compliance with drawings and specification requirements, but shall not directly cause the rejection of a lot."

4.5.3, line 7: Delete "Drop height shall be 9.5 inches." and substitute "Drop height shall be 9 1/2 ± 1/16" (241.3 ± 1.5 mm)."

4.5.4, line 10: Delete "20 inches" and substitute "20 ± 1/16" (508 ± 1.5 mm)".

4.5.4, line 12: Delete remainder of paragraph starting with "The test shall --- " and substitute "Sampling shall be the same as 4.5.3 except; accept lot if zero failures out of first 50 tested."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:45Z
Check the source to verify that this is the current version before use.

PAGE 9

6.2.1b: Delete "(4.2)" and substitute "(4.3)".

6.2.1c: Delete "(4.2.1)" and substitute "(4.3.1)".

GENERAL

Whenever it appears in the specification, change "Naval Ordnance Systems Command" to "Naval Sea Systems Command (Code Ident 10001)" and "NAVORD" to "NAVSEA".

Custodian:
Navy - OS

Preparing Activity:
Navy - OS
Project No. 1390-N211

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:45Z
Check the source to verify that this is the current version before use.