MIL-C-915/74B
18 June 1985
SUPERSEDING
MIL-C-915/74A
9 July 1976

MILITARY SPECIFICATION SHEET

CABLE, ELECTRICAL, 600 VOLTS, TYPE 5SS

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this document and the latest issue of MIL-C-915.

REQUIREMENTS:

Qualification required.

Construction (non-watertight)

First	- Copper conductor, uncoated. AWG size 18, class M stranding, (41/no. 34).
Second	- Separator.
Third	- Synthetic rubber insulation. Nominal thickness 0.032 inch. Identification by method 3; one conductor black, two white, one red and one green.
Fourth	- Braided shield (one white conductor only) of AWG no. 34 tin coated copper. Braid angle of 30 to 35 degrees; minimum coverage of 88 percent.
Fifth	- Shield insulation of one 0.002-inch thick polyester tape applied helically with 50 percent minimum overlap.
Sixth	- The five conductors cabled with a 3.75 ± 0.25-inch right hand lay around a moisture resistant jute center. Cabling sequence shall be black, white, white with shield, green and red.
Seventh	- Binder tape 0.012-inch thick double-faced, rubber-filled cotton tape applied helically with overlap.
Eighth	- Overall braided shield of AWG no. 34 tin coated copper. Braid angle of 30 to 35 degrees; minimum coverage of 88 percent.
Ninth	- Shield insulation of one 0.002-inch thick polyester tape applied helically with 50 percent overlap.
Tenth	- Polychloroprene jacket. Minimum thickness 0.050 inch. Cable diameter 0.500 inch minimum, 0.560-inch maximum. Surface of cable shall be embossed at approximately 3-foot intervals with the following information: The year of manufacture, type 5SS 5 CONDCT No. 18 SHLD 600 VOLTS.

FSC 6145

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/1000 feet, at 25°C, maximum.	7.15
Voltage withstand - volts, root mean square, minimum	
Conductor to shield.....	1000
Shield to shield (single shields only).....	500
Insulation resistance - megohms/1000 feet, minimum	
Conductor to shield.....	5000
Shield to shield (single shields only).....	100
Group A:	
Visual and dimensional.....	No failure
Group B:	
Physicals (unaged)	
Insulation	
Tensile strength - lbf/in^2, minimum.....	1000
Elongation - percent, minimum.....	350
Set - inch, maximum.....	3/8
Jacket	
Tensile strength - lbf/in^2, minimum.....	2400
Elongation - percent, minimum.....	325
Tensile stress - lbf/in^2, minimum at 200 percent elongation (ASTM D 470).....	700
Set - inches, maximum.....	1/4
Tear - pounds per inch thickness, minimum (ASTM D 470).....	40
Bending endurance - cycles at minus 30 ± 2°C on 4-inch maximum diameter mandrel.....	1000
Group C:	
Physicals (aged)	
Insulation	
Air pressure heat	
Tensile strength - percent of unaged, minimum.....	75
Elongation - percent of unaged, minimum..	60
Jacket	
Air pressure heat	
Tensile strength - percent of unaged, minimum.....	65
Elongation - percent of unaged, minimum..	60
Oxygen pressure	
Tensile strength - percent of unaged, minimum.....	65
Elongation - percent of unaged, minimum..	60
Shield-conformance to material coverage and construction	No failure

Source: https://assist.dla.mil -- Downloaded: 202640-16T12:16Z
Check the source to verify that this is the currenversion before use.

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B and C.

UNIT ORDERING LENGTHS:

Two thousand feet continuous lengths, except that 20 percent of total quantity may be in lengths between 1000 and 2000 feet but none less than 1000 feet.

NOTE: Cable shall be shipped on nonreturnable reels, one length per reel and the outside end of cable shall have the conductors in clockwise sequence as follows: green, red, black, white and white-shielded.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - MI
Navy - SH
Air Force - 85

Review activities:
Army - CR, ER
Navy - EC
Air Force - 99
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

Preparing activity:
Navy - SH
(Project 6145-0885-69)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.