MIL-C-915/79A
18 June 1985
SUPERSEDING
MIL-C-915/79(SH)
15 December 1976
MIL-C-915/19D
1 August 1972

MILITARY SPECIFICATION SHEET

CABLE, ELECTRICAL, TYPE TPUM-6

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this document and the latest issue of MIL-C-915.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First - A conductor consisting of 19 strands of 0.0126-inch diameter, copper-clad steel wire, in accordance with ASTM B 452, class 30A.
Second - Polypropylene insulation. Nominal wall thickness 0.025 inch. Telephone identification code applied by either method 1 or method 2.
Third - Two conductors twisted together to form a pair having a lay of 2-1/4 inches nominal.
Fourth - Six pairs of conductors cabled together. Lay shall be such as to enable the completed cable to comply with the bending endurance test. Cabling sequence shall be consecutive. Nonfibrous fillers shall be used to form a firm, well rounded assembly.
Fifth - Binder tape applied helically with overlap.
Sixth - Jacket of polyurethane, black, applied in two layers. Nominal wall thickness of each layer shall be 0.065 inch. Overall diameter shall be 0.925-inch maximum.

FSC 6145
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/1000 feet, at 25°C, maximum.	20
Voltage withstand - volts, root mean square, minimum	
Conductor to conductor.....	2000
Conductor to water.....	1000
Insulation resistance - megohms/1000 feet, minimum	
Conductor to conductor.....	100
Conductor to water.....	75
Group A:	
Visual and dimensional.....	No failure
Watertightness - in^3, maximum.....	4.0
Bending endurance - at minus 30°C, over 3-inch diameter roller, cycles, minimum.....	500
Breaking strength - pounds, minimum.....	1100
Abrasion resistance - scrapes, minimum.....	250
Group B:	
Physicals (unaged)	
Insulation conductor (stretch rate shall be 2 inches per minute)	
Tensile strength - lbf/in^2, minimum.....	3500
Elongation - percent, minimum.....	200
Jacket	
Tensile strength - lbf/in^2, minimum.....	5000
Elongation - percent, minimum.....	530
Drip - at 75 ± 1°C.....	Zero
Group C:	
Physicals (aged)	
Insulation conductor (stretch rate shall be 2 inches per minute)	
Air oven	
Tensile strength - percent of unaged, minimum.....	80
Elongation - percent of unaged, minimum..	70
Jacket	
Hot oil immersion	
Tensile strength - percent of unaged, minimum.....	60
Elongation - percent of unaged, minimum..	80
Cable filler removability.....	No failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B and C.

UNIT ORDERING LENGTHS:

1000 feet nominal; minimum acceptable length, 250 feet.

Revision letters are not used to denote changes due to the extensiveness of the changes.

NOTE: Not for Air Force use.

Custodians:
Army - MI
Navy - SH

Preparing activity:
Navy - SH
(Project 6145-0885-74)

Review activities:
Army - CR, ER
Navy - EC
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

☆U.S. GOVERNMENT PRINTING OFFICE: 1985 — 505-038/23075

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.