INCH POUND

MIL-C-915/79B
29 September 1989
SUPERSEDING
MIL-C-915/79A
18 June 1985

MILITARY SPECIFICATION SHEET

CABLE, POWER ELECTRICAL, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE TPUM-6

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation: MIL-C-915.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First - A conductor consisting of 19 strands of 0.0126-inch diameter, copper-clad steel wire, in accordance with ASTM B 452, class 30A.
Second - Polypropylene insulation. Nominal wall thickness 0.025 inch. Telephone identification code applied by either method 1 or method 2.
Third - Two conductors twisted together to form a pair having a lay of 2-1/4 inches nominal.
Fourth - Six pairs of conductors cabled together. Lay shall be such as to enable the completed cable to comply with the bending endurance test. Cabling sequence shall be consecutive. Nonfibrous fillers shall be used to form a firm, well rounded assembly.
Fifth - Binder tape applied helically with overlap.
Sixth - Jacket of polyurethane, black, applied in two layers. Nominal wall thickness of each layer shall be 0.065 inch. Overall diameter shall be 0.925-inch maximum.

AMSC N/A FSC 6145
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/1000 feet, at 25°C, maximum	20
Voltage withstand - volts, root mean square, minimum	
Conductor to conductor	2000
Conductor to water	1000
Insulation resistance - megohms/1000 feet, minimum	
Conductor to conductor	100
Conductor to water	75
Group A:	
Visual and dimensional	No failure
Watertightness - in^3, maximum	4.0
Bending endurance - at minus 30°C, over 3-inch diameter roller, cycles, minimum	500
Breaking strength - pounds, minimum	1100
Abrasion resistance - scrapes, minimum	250
Group B:	
Physicals (unaged)	
Insulation conductor (stretch rate shall be 2 inches per minute)	
Tensile strength - lbf/in^2, minimum	3500
Elongation - percent, minimum	200
Jacket	
Tensile strength - lbf/in^2, minimum	5000
Elongation - percent, minimum	530
Drip - at 75 ± 1°C	Zero
Group C:	
Physicals (aged)	
Insulation conductor (stretch rate shall be 2 inches per minute)	
Air oven	
Tensile strength - percent of unaged, minimum	80
Elongation - percent of unaged, minimum	70
Jacket	
Hot oil immersion	
Tensile strength - percent of unaged, minimum	60
Elongation - percent of unaged, minimum	80
Cable filler removability	No failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:16Z
Check the source to verify that this is the current version before use.

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B and C.

UNIT ORDERING LENGTHS:

1000 feet nominal; minimum acceptable length, 250 feet.

NOTE: Not for Air Force use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - MI
Navy - SH

Preparing activity:
Navy - SH
(Project 6145-1127-18)

Review activities:
Army - CR, ER
Navy - EC
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 202640-16T12:16Z
Check the source to verify that this is the current version before use.