MIL-A-48822(PA)
9 June 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

ADAPTER, CONNECTOR: W5F-1 AND CABLE ASSEMBLY: W6FE1

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of electrical adapter entitled Adapter, Connector: W5F-1, and electrical cable entitled Cable Assembly: W6FE1, which are used in the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8862501	- Potting Cup.
8864927	- Carton, Packing, Ammunition, for Modification Kit, Cable: M75.
8865378	- Adapter, Connector: W5F-1.
8865383	- Cable Assembly, Special Purpose, Electrical: W6FE1.
ET-8865383	- Equipment Tabulation.
8865384	- Case Assembly.

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

8865392 - Case Assembly.
8865395 - Connector.
8875816 - Carton, Packing, Ammunition, for Cable Assembly, Special Purpose, Electrical: W6FE1.
8875817 - Carton, Packing, Ammunition, for Adapter, Connector: W5F-1.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The adapter connector and cable assembly shall comply with all requirements specified on the drawing (dwgs) 8865378 and 8865383, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Continuity and circuit resistance. The resistance between electrically connected pins shall be not more than 0.25 ohms, and point to point continuity shall exist in accordance with the applicable drawing, when tested as specified in 4.4.1.

3.6 Dielectric strength. The assemblies shall show no indication of dielectric failure as evidenced by arcing between electrically isolated parts or an inability to attain or maintain an alternating current (ac) potential of 500 plus or minus (±) 50 volts root mean square (vrms) for not less than 15 seconds when tested as specified in 4.4.2.

3.7 Insulation resistance. The insulation resistance between electrically isolated circuits and between ungrounded circuits and the connector shells and case shall be not less than 20 megohms when subjected to a 500 ± 50 volts direct current (dc) potential as specified in 4.4.3.

3.8 Environmental testing. The assemblies shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The assemblies shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.1 and 4.4.3. Tests shall be conducted in the order specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.8.1 High temperature. The assemblies shall withstand a temperature of + 165 ± 5 degrees Fahrenheit (F.) for a minimum of 2 hours without evidence of distortion, cracks, swelling, or broken parts and shall comply with the requirements of 3.5, 3.6, and 3.7 after being tested as specified in 4.4.4.1.

3.8.2 Low temperature. The assemblies shall withstand a temperature of -65 ± 5 F. for a minimum of 2 hours without evidence of embrittlement, cracks, distortion, or broken parts and shall comply with the requirements of 3.5, 3.6, and 3.7 after being tested as specified in 4.4.4.2.

3.8.3 Vibration.

3.8.3.1 Transportation. The assembly shall be able to withstand vibration for the frequencies, gravity units (g.) accelerations or amplitude in inches, and for the time specified in Table I without evidence of broken or distorted parts, cracks, chips, exposure of base material, or other damage, or impairment of operations, and shall comply with the requirements of 3.5, 3.6, and 3.7 after being tested as specified in 4.4.4.3.1.

Table I

Frequency Hz	Cycles/ Minute	g. Acceleration	Double Amplitude (inches)	No. of Cycles in Each Axis
2-60	2.5		0.06 ± 0.006	1
61-300	2.5	10 ± 0.2		1
300-61	2.5	10 ± 0.2		1
60-2	2.5		0.06 ± 0.006	1

3.8.3.2 Flight. The assemblies shall withstand vibration for the frequencies, amplitude in inches or g. acceleration for the time specified in Table II without evidence of broken or distorted parts, cracks, chips, or impairment of operation. After test the assemblies shall comply with the requirements of 3.6 and 3.7 in addition, the circuits without fuses shall comply with the requirements of 3.5. Testing shall be as specified in 4.4.4.3.2.

Table II

Frequency Hz	Cycles/ Minute	g. Acceleration	Double Amplitude (inches)	No. of Cycles in Each Axis
5-55	2.5		0.02 ± 0.002	1
56-500	5.0	10 ± 0.2		1
500-56	5.0	10 ± 0.2		1
55-5	2.5		0.02 ± 0.002	1

Note: Physical damage to the fuses shall not be cause for rejection after flight vibration as long as the electrical requirements are complied with.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.9 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.10 Workmanship.

3.10.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.10.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.10.3 Burrs. Parts shall be free from burrs.

3.10.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.10.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.10.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwgs 8865378 and 8865383) for first article testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table III. Tests shall

56-500	5.0	10 ± 0.2		1
500-56	5.0	10 ± 0.2		1
55-5	2.5		0.02 ± 0.002	1

Note: Physical damage to the fuses shall not be cause for rejection after flight vibration as long as the electrical requirements are complied with.

Source: https://assist.dla.mil - Downloaded: 2021-12-21T19:41
Check the source to verify that this is the current version before use.

Table III

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Continuity and circuit resistance (see 3.5)		X
3. Dielectric strength (see 3.6)		X
4. Insulation resistance (see 3.7)		X
5. High temperature (see 3.9.1)		X
6. Low temperature (see 3.9.2)		X
7. Transportation vibration (see 3.9.3.1)	X	
8. Flight vibration (see 3.9.3.2)	X	

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table IV and Table V), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table IV
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table V
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Case assembly (see dwg 8865392 covering a detail of dwg 8865383).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Length of box	Gage
	102. Width of box	Gage
	103. Height of box	Gage
	104. Location of threaded hole in tabs	Gage
	105. Location of cover plate holes	Gage
	106. Location of the two bars	Gage
	107. Location of hole in bar	Gage
	108. Diameter of hole in bar	Gage
Minor:	None defined.	

4.3.2.1.2 Cable assembly, prior to securing connector shell and cable clamp, or prior to potting (as applicable) (see dwg 8865383).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	*101. Height of pin(s), pins of the same diameter must all appear to be within 1/16 inch in height relative to the adjacent pin	Visual/Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

**102.	Depth of socket(s), female sockets of the same diameter must all appear to be within 1/16 inch in depth relative to adjacent sockets	Visual/Gage
103.	Any pin bent	Visual
104.	Pin missing (as evidenced by empty hole in insert)	Visual
105.	Foreign matter on any pin or in any pin hole unless removable	Visual
106.	Any component cracked	Visual
107.	Portion of connector broken away (minor chips, scratches, or gouges that do not affect mating are not objectionable	Visual
108.	Deformation in any area	Visual
109.	Wire shielding or insulation damaged on individual wires (prior to installing vinyl insulation sleeving)	Visual
110.	Improper soldering (see 3.9)	Visual

Minor: None defined.

4.3.2.1.4 Cable assembly, special purpose, electrical: W6FE1, prior to potting fuse box (see dwg 8865383).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Distance from fuse box to P1 and P2 connectors	Gage
*102.	Height of pin(s), pins of the same diameter must all appear to be within 1/16 inch in height relative to the adjacent pins)	Visual/Gage
**103.	Depth of socket(s), female sockets of the same diameter must all appear to be within 1/16 inch in depth relative to the adjacent sockets	Visual/Gage
104.	Any fuse missing or damaged	Visual
105.	Improper fuse in F12, F13, or F14 locations	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

106. Improper fuse in fuse locations other than F12, F13, and F14.....Visual
107. Improper soldering (see 3.9).....Visual
108. Fuse clips not in straight line.....Visual

Minor: None defined.

4.3.2.1.5 Cable assembly, special purpose, electrical: W6FE1 (see dwg 8865383).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Indexing or polorizing groove location	Visual
102.	Cable crushed	Visual
103.	Cut or tear extending into individual lead of cable	Visual
104.	Torn or frayed insulation and bushings	Visual
105.	Marking mislocated, misleading or unidentifiable (incomplete, incorrect, superimposed or otherwise smeared)	Visual
***106.	Potting compound missing or improper	Visual
107.	Crazing or cracking of plastic housing covers in excess of 1/2 inch	Visual
108.	Any component missing or loose (loose to extent of becoming detached in subsequent handling)	Visual/Manual
109.	Flat side of fuse element not perpendicular to line of sight	Visual
110.	Transparent cover interferes with top of fuse clips	Visual/Manual
111.	Transparent cover not completely sealed to case	Visual
112.	Clamps not installed in proper position	Visual
113.	Potting compound extends into insulation sleeve or bushing	Manual
114.	Objective evidence relative to material missing or improper (see 3.1)	Visual
115.	Serialization improper or missing (see 3.4)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Evidence of poor workmanship (see 3.10).....Visual

4.3.2.1.6 Case assembly (see dwg 8865384 covering a detail of dwg 8865378).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Location of large holes	Gage
102.	Location of small holes	Gage
103.	Diameter of large holes	Gage
104.	Diameter of small holes	Gage
105.	Dip brazing improper	Visual
Minor:	None defined.	

4.3.2.1.7 Adapter connector: W5F-1, prior to potting (see dwg 8865378).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Any component missing or damaged	Visual
102.	Fuse missing or damaged	Visual
103.	Insulation missing or damaged	Visual
104.	Fuse clips not in straight	Visual
105.	Evidence of poor workmanship (see 3.10)	Visual
106.	Improper soldering (see 3.9)	Visual
Minor:	None defined.	

4.3.2.1.8 Adapter connector (see dwg 8865378).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Improper engagement of mating receptacle (or equal) with connector (2 connectors)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

*102.	Height of pin(s), pins of the same diameter must all appear to be within 1/16 inch in height relative to adjacent pins	Visual/Gage
**103.	Depth of socket(s), female sockets of the same diameter must all appear to be within 1/16 inch in depth relative to the adjacent sockets	Visual/Gage
104.	Connector mounting improper	Visual
***105.	Potting compound improper or missing	Visual
106.	Crazing or cracking of plastic housing covers in excess of 1/2 inch	Visual
107.	Marking missing, improper, or unidentifiable	Visual
108.	Transparent cover not completely sealed to case	Visual
109.	Flat side of fuse element not perpendicular to line of sight	Visual
110.	Sealing compound not applied to one or more screws (4 screws)	Visual
111.	Incorrect angle of polarizing groove in connector	Gage
112.	Depth from edge of case to fuse mounting board, min. (check prior to assembling cover)	Gage
113.	Cover assembly not in line with edges of case (including gaps between cover and inside edges of case)	Visual
114.	Objective evidence relative to material missing or improper (see 3.1)	Visual
115.	Serialization improper or missing (see 3.4)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.10)	Visual

*In the event pin(s) do not appear to be within 1/16 inch in height relative to the adjacent pins, gage (see 4.3.4.1) shall be used to determine the variation from the normal height. Reject any pin that varies by more than 0.063 inch, maximum, from the normal pin height of individual connector. The normal height of the individual connector pins

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

shall be determined by calculating the average height from measurements taken of pins adjacent to the pin that appears to be defective. The forward metal edge of the connector shall be ulitized as the reference surface for all measurements of pin heights.

**In the event socket inserts do not appear to be within 1/16 inch in depth relative to the adjacent sockets, gage (see 4.3.4.1) shall be used to determine the variation from the normal depth. Reject any insert that varies by more than 0.063 inch, maximum, from the normal socket insert depth of the individual connector. The normal depth of the individual connector sockets shall be determined by calculating the average depth from measurements taken of sockets adjacent to the socket that appears to be defective. The forward edge of the connector insert shall be utilized as the reference surface for all measurements of socket depth.

***Cracks in potting compound are permitted provided the requirements of 3.6 and 3.7 are complied with. Cracks in connector potting compound are cause for rejection.

4.3.2.1.9 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with applicable dwgs 8864927, 8875817 and 8875816	Visual
102.	Marking not in accordance with applicable dwgs 8864927, 8875817 and 8875816	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.11)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Continuity and circuit resistance	Major
b. Insulation resistance	Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

c. Dielectric strength — Major
d. Vibration (flight) W5F-1 adapter connector only — Major

Of these tests, d is considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Continuity and circuit resistance, and insulation resistance. Each assembly shall be tested in accordance with 4.4.1 and 4.4.3. If any item fails to comply with 3.5 and 3.7, the item shall be rejected and removed from the lot.

4.3.3.2 Dielectric strength, and vibration (flight). Sample assemblies shall be selected from each inspection lot in accordance with Table VI and subjected to these tests (see 4.4.2 and 4.4.3.2). For lots of 300, or less, if any assembly fails to comply with the applicable requirement, the lot shall be rejected. For lots over 300, sampling shall be in accordance with MIL-STD-105, Table II A, level S3.

Table VI

Lot Size	Sample Size
2-40	1
41-180	3
181-300	5
301-and over	MIL-STD-105 (AQL 0.25 percent)

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). Els for assemblies are listed on the Equipment Tabulation, ET-8865383. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified onthe EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Continuity and circuit resistance. The resistance of each circuit shall be measured using the four wire resistance measurement method. The test current shall be limited to 100 milliamperes (ma) maximum. For the W6FE1 cable assembly observe and record each reading (whether within or outside of acceptable limits) in ohms for all circuits. For the W5F-1 adapter connector, observe and record each reading (whether within or outside of acceptable limits) in ohms for the fused circuits only.

4.4.2 Dielectric strength. The required potential shall be applied between each isolated conductor, and between each conductor and the shell for the required time. The voltage source shall be current limited to a maximum of 5 milliamperes adequately interlocked to protect human life.

4.4.3 Insulation resistance. The insulation resistance shall be determined by utilizing an insulation resistance tester capable of reading directly in megohms and with suitable scales. The potential shall be applied for not less than 5 seconds. The current shall be limited to not more than 5 milliamperes as a safety measure.

4.4.4 Environmental testing (see 3.8).

4.4.4.1 High temperature. The assembly shall be placed in a test chamber and the chamber temperature raised to +165 ± 5°F, stabilized (see 6.4), and the assembly held at this temperature for a minimum of 2 hours. The assembly shall then be returned to ambient room temperature. No forced cooling, such as directing air on the assembly by means of a fan or by placing the assembly in refrigerated air, shall be used in returning the assembly to ambient room temperature. After completion of this test, the assembly shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

4.4.4.2 Low temperature. The assembly shall be tested as specified in 4.4.4.1 except that the chamber temperature shall be reduced to -65 ± 5°F and no forced warming shall be used in returning the assembly to ambient room temperature. After completion of this test the assembly shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

Source: https://assist.dla.mil Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.4.4.3 Vibration.

4.4.4.3.1 Transportation. The cable assembly and adapter connector shall be packed in accordance with dwg 8875816 or 8875817, as applicable, and mounted to a suitable vibration producing apparatus. The package shall be vibrated in three mutually perpendicular axes. The frequency shall be varied throughout the specified frequency range specified. After completion of this test, the assembly shall be removed from the packing and tested as specified in 4.4.1 through 4.4.3.

NOTE: If the fuses used in the assembly were tested in accordance with the flight vibration test prior to the transportation vibration, then the fuses shall be replaced prior to the transportation test.

4.4.4.3.2 Flight.

4.4.4.3.2.1 Cable assembly. The cable assembly with mating connectors attached shall be mounted to a suitable vibration producing apparatus and vibrated under the required conditions. The connectors shall be mounted to each of the mating connectors on the plate so that its principal axes is perpendicular to the plate. The fuse box shall be mounted on the plate so that one of its major axes is parallel to that of the plate. The entire assembly shall be vibrated in all three mutually perpendicular planes. The frequency shall be varied uniformly throughout the frequency range specified. After completion of this test, the cable assembly shall be tested as specified in 4.4.1 and 4.4.3 and those circuits of the cable without fuses shall be tested as specified in 4.4.1.

4.4.4.3.2.2 Adapter connector. The adapter with its connector (see dwg 8865395) attached to one end and a mating connector and potting cup (see dwg 8862501) attached to the opposite end shall be mounted by its connector (see dwg 8865395) to a suitable vibration producing apparatus and vibrated under the required conditions (the orientation of the potting cup is not significant for this test). The potting cup shall be filled with potting compound as specified on dwg 8865378. The adapter shall be vibrated in its three mutually perpendicular axis. The frequency shall be varied uniformly over the frequency range specified. After completion of this test, the adapter shall be tested as specified in 4.4.2 and 4.4.3 and those circuits of the adapter without fuses shall be tested as specified in 4.4.1.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

5.1.1.1. Level A. The assemblies shall be preserved and packaged in accordance with instructions contained in dwg 8864927.

5.1.1.2 Level C. The assemblies shall be preserved and packaged in accordance with instruction contained in dwg 8864927.

5.1.2 Packing.

5.1.2.1 Levels A and C. The assemblies shall be packed in accordance with the applicable instructions contained in dwg 8864927.

5.1.3 Marking. Marking shall be in accordance with dwg 8864927.

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The assemblies shall be packaged in accordance with dwgs 8875816 and 8875817 using the specified moisture barrier.

5.2.1.2 Level C. The assemblies shall be packaged in accordance with dwgs 8875817 and 8875816 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The assemblies shall be packed in accordance with dwgs 8875817 and 8875816.

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8875817 and 8875816.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Parts.
c. Slection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2439 (Rev. 2) dated 4 August 1965.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A203

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.