MILITARY SPECIFICATION

CIRCUIT, DEMOLITION INERT, FOR DEMOLITION KIT, CRATERING, TRAINING, XM270 ASSEMBLY AND PACKING

This specification is approved for use by US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts assembly, and packing for one type of Inert Demolition Circuit for the XM270 Demolition Cratering Kit, Training.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T02:44Z
Check the source to verify that this is the currentversion before use.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKING DRAWINGS

9331654 - Circuit, Demolition, (Inert)
9311233 - Packing and Marking for Box, Wood, Packing for Circuit Demolition Inert

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Components and assembly. The components and assembly shall comply with all requirements specified on drawing (Dwg.) 9331654, and associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be free of burrs, chips, sharp edges, cracks, crazes, unblended radii, porosity, warpage, burn marks, checks, chipped edges, blisters, excess flash, dirt, grease, rust, salt deposits, visible raised cement seams, solder splash, corrosion products and other foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspections shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. The first article sample shall consist of 25 complete sets of parts and sub-assemblies (i.e. 25 each of every component and sub-assembly, including at least five (5) items from each cavity used to produce molded parts and be so identified as to permit tracing each item to the cavity in which it was molded) and 50 loaded demolition circuit assemblies. The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be performed. See MIL-A-48078 and paragraphs 4.4.2.1 thru 4.4.2.4, testing per paragraph 4.4.3, molding inspections per paragraph 4.4.5, and Table I specified herein.

4.3.3 Rejection. MIL-A-48078 applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63373(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Circuit, Demolition, (Inert) XM270 Cratering Demolition Kit, Training				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Circuit Demolition (Inert) (Dwg. 9331654) Examination for defects	50		3.2	4.4.2.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Demolition, Circuits shall contain:

a. Parts from not more than one lot interfix number from one manufacturer.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and test tables, sampling plans with major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63373(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Circuit Demolition (Inert)		9331654
			NEXT HIGHER ASSEMBLY 9331717

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Connector damaged		0.40%	3.2	Visual
102	Wire insulation damaged		0.40%	3.2	Visual
103	Shorting plug missing		0.40%	3.2	Visual/Manual
104	Length of cable		0.40%	3.2	Gage
105	Tape missing or improperly applied		0.40%	3.2	Visual
106	Length of assembly		0.40%	3.2	Gage
107	Priming adapter improperly assembled to assembly		0.40%	3.2	Visual
108	Inert cord improperly assembled to non-electric blasting cap		0.40%	3.2	Visual/Manual
109	Crimps on non-electric blasting cap less than 360°		0.40%	3.2	Visual
110	Component missing or damaged		0.40%	3.2	Visual
Minor					
201	Color of wire		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63373(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Wooden Box, Prior to Sealing		9311233
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Assembly not dry prior to packaging		0.40%	3.2	Visual
102	Plastic bag missing or damaged		0.40%	3.2	Visual
103	Board broken or with split terminating at edge		0.40%	3.2	Visual
104	Assembly missing		0.40%	3.2	Visual
105	Contents not tight		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63373(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Sealed Wooden Box	1 OF 1	9311233
			NEXT HIGHER ASSEMBLY 9331717

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Strapping missing, broken, or loose		0.40%	3.2	Visual
102	Board broken or with split terminating at edge		0.40%	3.2	Visual
103	Contents of box exposed		0.40%	3.2	Visual
Minor					
201	Marking misleading or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.4	Visual
203	Strapping covers marking		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63373(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Box, Wood		9294601
			NEXT HIGHER ASSEMBLY 9311233

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Side joints, and/or side to base joint not glued		0.40%	3.2	Visual
Minor					
201	Cover base square		0.65%	3.2	Gage
202	Cover base thickness		0.65%	3.2	Gage
203	Long side dimension		0.65%	3.2	Gage
204	Long side thickness		0.65%	3.2	Gage
205	Side short		0.65%	3.2	Gage
206	Short side thickness		0.65%	3.2	Gage
207	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, 4.4.5.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078, and section 6.3 herein.

4.4.5 Dimensional control of molded parts. In place of normal sampling and inspections associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (see Note 1), a sample of five (5) parts (as molded) from each cavity shall be inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification, when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity curing production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4.5.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the five (5) samples one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities are moved from production because of some fault, may after working, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency, providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAA-I for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing the curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAA-M. If any new change in material, cycle time, a reworked cavity or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T02:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING.

5.1 Packaging. Packaging shall be as specified on Dwg. 9311233.

5.2 Packing and marking. Packing and marking shall be as specified on Dwg. 9311233.

6. NOTES

6.1 Intended use. This demolition circuit is used as part of the Demolition Kit, Cratering, Training: XM270 Inert.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number, and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required to Commander, ARRADCOM, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading, "US Army Armament Research and Development Command (ARRADCOM)" may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.5 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, ARRADCOM, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1375-A138

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-63373 Circuit, Demolition Inert, for Demolition Kit, Cratering Training XM270

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.