INCH-POUND

MIL-C-71083(AR)
1 June 1992

MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE, CARTRIDGE, 81mm, PA156 AND PA157 GENERAL SPECIFICATION FOR

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations and tests for Containers, Shipping and Storage, Cartridge 81mm, PA156 and PA157, hereinafter called 'the container'. The container is used for holding ammunition during usage, shipping and storage.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications , standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (see 6.2).

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods for Ferrous Surface and Pretreatment for Organic Coatings

MILITARY

MIL-W-12332	-	Welding, Resistance, Spot, Seam and Projection; for Fabricating Assemblies of Low Carbon Steel
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

MIL-W-63150	-	Weapons and Support Materiel, Standard Quality Assurance Provisions for
MIL-A-70625	-	Automated Acceptance Inspection for Non-Electronic Components, Design, Testing and Approval of

STANDARD

MILITARY

MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-171	-	Finishing of Metal and Wood Surfaces
MIL-STD-406	-	Visual Inspection Standards for Tern Plate Cans and Steel Boxes used in Small Arms Ammunition Packaging

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

Earle Naval Weapons Station, Code 5021, Colts Neck, New Jersey 20362.

6213303	-	Container, Ammunition Assembly, PA157
6213304	-	Container, Ammunition Assembly, PA156
6213320	-	Packing and Marking for Container, Ammo, PA156 and PA157 for Cartridge 81mm

(Copies of other Government documents, drawings and publications required by the contractor in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issue of documents not listed in the DODISS are the issues of the documents cited in the solicitation. (See 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B117 - Standard Test Method of Salt Spray (Fog) Testing
ASTM D3951 - Standard Practice for Commercial Packaging (DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1137.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. All materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements of drawings 6213303 and 6213304, all associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Temperature.

3.3.1 Elevated temperature (storage). The container shall not suffer permanent damage when subjected to the constant temperature of +160°F minimum (min.) for a period of 24 hours (after temperature stabilization), and shall meet the requirements of 3.4 when returned to a minimum temperature of 50°F.

3.4 Performance

3.4.1 Cover assembly. The locking hardware shall be operable manually. The cover assembly shall be removable manually without the use of exorbitant force. The gasket shall remain secure in the correct position within the cover upon removal of the cover assembly. The gasket shall not stick to, be cut or split by contact against the top edge of the body assembly. The cover shall be completely removable manually, without special tools, without the use of exorbitant force and shall be easily resealed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

3.4.2 Hasp and latch. Mating parts of the body hasp and latches shall engage without requiring deformation of any container part, and the latches shall close and open freely. When closed, the latches of the assembled container shall remain closed until manually opened.

3.5 Airtightness. The assembled container shall withstand, without leakage, a minimum air pressure differential of three pounds per square inch (PSI).

3.6 Welding procedure. Fabrication of the container shall be in accordance with the recorded welding procedure requirements of MIL-W-12332.

3.7 Protective coating.

3.7.1 Pretreatment. The cleaning method and pretreatment process used shall comply with the requirements of Drawings 6213305 and 6213309 and MIL-STD-171. The phosphate coating shall comply with finish 5.1.1 of MIL-STD-171.

3.7.2 Paint. The paint coating shall comply with the requirements of Drawings 6213305 and 6213309. In addition, the coating shall comply with the requirements of MIL-STD-406. Adhesion of the paint to the pretreated surfaces shall comply with applicable requirements of MIL-STD-171, finish 5.1.1.

3.7.3 Corrosion resistance. The exterior surfaces of the box shall show no visible evidence of paint blistering, creepage (loss of adhesion), or corrosion of base metal in excess of 1/8 inch on either side of the score marks or rusting of parts of the hardware subject to pressure or abrasion in normal use or exceeding the standards permissible in MIL-STD-406, after exposure to a 5% solution of salt spray for 80 hours.

3.8 Gasket compression. The gasket compression of the container shall be as specified by Dwgs. 6213303 and 6213304.

3.9 Weld security.

3.9.1 Hasp assembly. Each hasp of the body assembly shall comply with the weld security requirement of Dwg. 6213305 without permanent deformation or failure of a weld.

3.9.2 Handle assembly. The handles of the body assembly shall withstand a pull of 600 pounds, min., without permanent deformation of a component or failure of a weld.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

3.9.3 Latch assembly. The latch assemblies of the cover assembly shall comply with the weld security requirement of Dwg. 6213309 without breakage or permanent deformation of any of the components or welds.

3.10 Concavity and convexity.

3.10.1 Cover assembly. The cover assembly shall meet the requirements of Dwg. 6213309 for flatness.

3.10.2 Body assembly. The top edges of the body assembly shall meet the requirements of Dwg. 6213305.

3.11 First article. When specified in the contract, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.12 Workmanship. Workmanship shall be in accordance with good manufacturing practices and shall in no way impair the functional performance of the container. Containers shall be free of cracks, extraneous material, and irregularities in the surfaces. Metal parts shall not be rusted. In addition, MIL-W-63150, (Workmanship) shall apply.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated ar actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the items in sample quantities as indicated in Table I.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all examinations and tests specified in this detail specification and to any or all requirements of the applicable drawings.

4.3.3 Rejection. If any component, or assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an item or material to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS MIL-C-71083(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
	Container Assembly		6213303/6213304
			NEXT HIGHER ASSEMBLY
			6213320

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Temperature	7	3.3	4.5.1
	Performance	7	3.4	4.5.2
	Airtightness	7	3.5	4.5.3
	Pretreatment	Note 1	3.7.1	4.5.4
	Paint adhesion	7	3.7.2	4.5.5
	Corrosion resistance	7	3.7.3	4.5.6
	Gasket compression	7	3.8	4.5.7
	Weld security		3.9	4.5.8
	Hasp	7	3.9.1	
	Handle	7	3.9.2	
	Latch	7	3.9.3	
	Concavity and convexity		3.10	4.5.9
	Cover assembly	7	3.10.1	
	Body assembly	7	3.10.2	

NOTES:

1. Seven (7) standard panels per TT-C-490 shall be tested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of products selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.1.1 Lot identification. The cover and body assemblies of each container of the lot shall be identified as specified by Dwgs. 6213309 and 6213305 supplemented as directed by the procuring activity.

4.4.2 Examinations. The examinations listed herein shall be performed on inspection lots as defined in 4.4.1. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum, the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection

Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 to 500000	1250	500	200	125	50	13
500001 an over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.4). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative is equal to, or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71083 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Body Assembly		6213305
			NEXT HIGHER ASSEMBLY
			6213305/6213304

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None Defined			
MAJOR				
101	Inside width, body assembly, min	Level III	3.2	Gage
102	Inside length, body assembly, min	Level III	3.2	Gage
103	Inside depth, body assembly, min	Level III	3.2	Gage
104	Convexity or concavity top edges of body	Level III	3.10.2	Gage
105	Interior or exterior paint missing or nonconforming	Level III	3.7.2	Visual 1/
MINOR				
201	Poor workmanship	Level IV	3.12	Visual/Scale

NOTES:

1/ MIL-STD-406 shall be used as a guide to classify paint defects. In the standard, defects classified as incidental shall be considered permissible; defects classified as minor shall be considered major. Missing, damaged or incomplete paint shall be classified as a defect. Bare spots on any subassembly which do not accumulate to exceed 1/2 square inch in area or scratches which do not penetrate to the phosphate coating shall be disregarded.

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71083 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cover Assembly		6213309
			NEXT HIGHER ASSEMBLY 6213303/6213304

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None Defined			
MAJOR				
101	Width, inside cover (2 places)	Level III	3.2	Gage
102	Interior or exterior paint missing or nonconforming	Level III	3.7.2	Visual/Scale 1/
103	Missing, inverted, loose, misaligned or defective gasket	Level III	3.4.1	Visual-Manual 2/
MINOR				
201	Poor workmanship	Level IV	3.12	Visual/Scale

NOTES: 1/ MIL-STD-406 shall be used as a guide to classify paint defects. In the standard, defects classified as incidental shall be considered permissible; defects classified as minor shall be considered major. Missing, damaged or incomplete paint shall be classified as a defect. Bare spots on any subassembly which do not accumulate to exceed 1/2 square inch in area or scratches which do not penetrate to the phosphate coating shall be disregarded.

2/ If the gasket is missing, inverted, broken, split or torn, contains a gross defect in texture, fit or can be shifted horizontally within the gasket retainer by finger pressure or manually shaken off the cover assembly, the sample unit shall be classified as defective.

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71083 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.3	Container Assembly		6213303/6213304
			NEXT HIGHER ASSEMBLY 6213320

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None Defined			
MAJOR				
101	Airtightness inspection	Level II	3.5	4.5.3
102	Elevated temperature (storage) inspection	Level III	3.3	4.5.1
103	Performance inspection 1/	Level III	3.4	4.5.2
104	Gasket compression inspection	Level III	3.8	4.5.7
105	Weld security inspection	Level III	3.9	4.5.8
106	Concavity and convexity inspection	Level III	3.10	4.5.9
107	Missing, incomplete or improper assembly of component	Level III	3.2	Visual
108	Missing, incomplete or improper welds	Level III	3.2	Visual
109	Paint adhesion inspection	6, 0-1	3.7.2	4.5.5
110	Corrosion resistance inspection	6, 0-1	3.7.2	4.5.6

NOTES: 1/ The samples used for the performance inspection may also be used for airtightness, gasket compression, concavity and convexity, and the visual inspections (Major defects 107 and 108).

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71083 (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.3	Container Assembly		6213303/6213304
			NEXT HIGHER ASSEMBLY 6213320

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
MINOR				
201	Outside height	Level IV	3.2	Gage
202	Outside length	Level IV	3.2	Gage
203	Outside width	Level IV	3.2	Gage
204	Marking incorrect, incomplete, illedible or missing	Level IV	3.2	Visual
205	Poor workmanship	Level IV	3.12	Visual

NOTES:

AMSMC Form 1570a, 1 Jul 89

Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Pretreatment (see 3.7.1), major defect. Two (2) standard panels shall be prepared in accordance with TT-C-490 and processed with the cover or body assemblies. Beginning with the start of daily production and at four (4) hour intervals, maximum, thereafter, shall be inspected. If any panel fails to comply with the applicable requirements, all container sub assemblies processed since the preceding test shall be rejected.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1 and 4.5. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. When Automated Acceptance Inspection Equipment is to be used, the provisions of MIL-A-70625 shall apply. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection. (see 6.4).

4.5.1 Elevated temperature storage. The containers shall meet the requirements of 4.5.2 prior to testing. Environmentally condition the container as specified in 3.3.1. After conditioning, reinspect the container in accordance with 4.5.2 for compliance to the requirements.

4.5.2 Performance. The container shall be inspected to assure compliance with the requirements of 3.4 utilizing the following procedures:

a. Unlock and lock the cover assembly hardware by hand leverage. Note the locking and unlocking action for effectiveness and ease of operation.

b. Remove and replace the cover assembly. Note any misfit or bind with the body assembly.

c. Remove all cover assemblies. Inspect the gaskets for fit, security, cuts and splits.

d. Note any sticking of gaskets to the top edges of the body assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.5.3 Airtightness. The container shall be conditioned to a minimum temperature of 50°F and ambient pressure prior to testing. The containers shall be tested in accordance with 4.5.3.1 or with permission of the procurement agency with 4.5.3.2, to the requirements of 3.5. A wetting agent may be used to minimize air bubbles clinging to the exterior surface.

4.5.3.1 Vacuum method. The container shall be tested for leakage by immersing the closed container in the inverted position under water in a vacuum vessel and lowering the pressure in the vessel to three pounds per square inch minimum below ambient pressure. Observation for leakage of air from the container interior shall be made for a minimum of 30 seconds after reduction of pressure. A stream or recurring succession of bubbles shall constitute leakage.

4.5.3.2 Hot water method. The container shall be tested for leakage by immersing the closed container, in the inverted position, to a depth of one inch below the surface of the water. The temperature of the water and the length of time of immersion shall be that which will assure an increase in pressure to a minimum of 3 psi above ambient pressure. Observation for air leakage from the container interior shall be made during the period of pressure build-up and for 30 seconds after the 3 psi pressure differential has been reached.

4.5.4 Pretreatment. The method of test shall be as specified in TT-C-490, as applicable to the type of phosphate used.

4.5.5 Paint adhesion. The method of test shall be as specified in TT-C-490. The test shall be performed on three randomly selected surfaces of each unit of the sample.

4.5.6 Corrosion resistance. The test method shall be as specified in ASTM B117 Method of Test for Salt Spray (Fog) Testing. Using a sharp instrument, an "X" 6 to 7 inches long shall be scored on a flat surface of the cover and one side of the body of each sample container. The samples shall be supported, one with the scored "X" in the upright position for the cover test and the other sample supported with the scored "X" in the upright position for the body side test. Traces of paint blistering or corrosion spots on component edges or corners shall not be classed as protective coating failure.

4.5.7 Gasket compression. The method of test shall be specified to determine compliance to the requirement of 3.8 (see 6.7).

4.5.8 Weld security. The container and its subassemblies shall be tested to the requirements of 3.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.5.8.1 Hasp assembly. The sample body assembly resting on its bottom shall be clamped in a suitable device. The specified tensional force shall be slowly applied perpendicular to the bottom and against the underside of the offset of the hasp. The force shall be applied at a rate of .125 to .25 inch per minute and held for one minute. After removal of the force, examine the hasp for distortion and weld failure.

4.5.8.2 Handle assembly. With sample body assembly resting on its bottom or on end, attach a suitable device to each end handle. With one held, apply the specified tensional force through the other parallel to the container bottom against the ferrule of each handle. The force shall be applied at a rate of .125 to .25 inch per minute and held for one minute. After removal of the force, examine the handle and hasp for distortion and weld failure.

4.5.8.3. Latch assembly. Attach a suitable device to each latch on the cover assembly. Secure one and slowly apply a tensional force to the other parallel to the face of the cover. The force shall be applied at a rate of .125 to .25 inch per minute and held for one minute. Apply the force against the surface of the latch links exposed on the underside of each latch. After removal of the force, examine the latches, latch links, latch link retainers and cover for distortion and weld failure.

4.5.9 Concavity and convexity. The container and its subassemblies shall be tested to the requirements of 3.10.

4.5.9.1 Cover assembly. The concavity and convexity shall be measured on the sample cover assemblies along the length of the cover in the area above the cover gasket and the width adjacent to latch link retainer on the flat surface of the cover.

4.5.9.2 Body assembly. The concavity and convexity shall be measured on the sample bodies along the length and width of the top edge.

5. PACKAGING

5.1 Preparation for delivery. Packaging and packing shall be commercial as specified in Standard Practice for Commercial Packaging ASTM D3951 and meet common carrier acceptance and provide safe delivery to destination at the lowest rates.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The containers described herein are to be used for holding of 81mm ammunition during usage, shipping and storage.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Applicable stock number.

c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

d. First article sample requirements.

e. Provisions for the submission and approval of the welding procedure.

f. Requirements for quality conformance inspection sampling plan.

g. Certificate of conformance for each lot or shipment of product.

h. Packaging requirements, if other than specified in Section 5.

6.3 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423, in the contract.

6.4 Submission of alternative quality control provisions. Unless otherwise specified in the contract, proposed alternative quality control provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

6.5 Intermediate point inspection. The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations) should be scheduled to prevent premature acceptance or rejection, which could be detrimental to the attainment of optimum product quality in the end item.

6.6 Measurement for gasket compression. Three point contact of the container resting on blocks may be used to overcome any rocking motion which might be encountered with the container resting on the surface plate. However, since the measurement technique relies upon relative distances, care should be taken to assure that there is no displacement on the referenced surfaces between the reading.

6.7 Approval of equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to : Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAR-Q, Picatinny Arsenal, NJ 07806-5000. This description should include, but not be limited to, the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

6.8 Subject term (key word) listing.

Body Assembly
Concavity and convexity
Cover Assembly
Gasket compression
Hasp and latch
Paint
Phosphate
Pretreatment
Support, Foam
Support, Plywood
Support, Assembly

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 8140 - A845)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-71083 (AR)	1 June 1992

3. DOCUMENT TITLE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME US ARMY ARDEC STANDARDIZATION OFFICE	b. TELEPHONE (Include Area Code) (1) Commercial: (201) 724-6675 (2) AUTOVON: 880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL,NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.