MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, CCU-22/A ASSEMBLY

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the minimum requirements for the procurement of the CCU-22/A impulse cartridge-loaded assembly referred to herein as the cartridge assembly.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	Preservation-Packaging, Methods of
MIL-S-9479	Seat System, Upward Ejection, Aircraft, General Specification for
MIL-P-82652	Propellant, Solid, Composite
MIL-C-82662	Catapult, Aircraft Ejection Seat, CKU-5/A Assembly

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station (611), Indian Head, MD 20640, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipping and Storage
MIL-STD-414	Sampling Procedures for Inspection by Variables
MIL-STD-453	Inspection, Radiographic
MIL-STD-810	Environmental Test Methods

PUBLICATIONS

Naval Sea Systems Command (Code 10001)

WR-43	Preparation of Quality Assurance Provisions

DRAWINGS

Naval Ordnance Station, Indian Head (Code Ident 14083)

11740605	Cartridge, Impulse, CCU-22/A Assembly
11740613	Shear Pin

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 100-199	Transportation

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20462. Orders should specify "49 CFR 100-199 (latest revision)").

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT
National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associtions, Attn: Tariff Order Section, 1616 P Street, Washington, D.C. 20036).

UNIFORM CLASSIFICATION COMMITTEE, AGENT
Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606).

3. REQUIREMENTS

3.1 First article. Unless otherwise specified in the contract (see 6.2), first article samples of the cartridge assemblies are required and shall be manufactured using the methods and procedures proposed for production. The samples shall be tested as specified in Section 4 for the purposes of determining, prior to starting production, that the contractor's production methods are capable of producing cartridge assemblies that comply with the technical requirements of the contract (see 4.4).

3.2 Definitions. Definitions of various terms used herein are listed in 6.4.

3.3 Materials. All materials, parts and assemblies shall be in accordance with the applicable drawings, this specification and the documents referenced herein.

3.4 Age.

3.4.1 Explosive components. All explosive components, including but not limited to, ignition powders, primers and igniters, shall be manufactured within the 12 months prior to the contract scheduled delivery date for the cartridge assemblies lot.

3.4.2 Propellant. The propellant shall be manufactured within the 150 days prior to the contract scheduled delivery date for the cartridge assemblies lot.

3.5 Ballistic performance requirements. The cartridge assemblies shall meet the ballistic performance requirements of TABLE I when assembled into acceptable rocket catapult hardware in accordance with MIL-C-82662 and test fired using an ejected weight of 375 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

TABLE I. Ballistic Performance Requirements - 375 Pound Ejected Weight.

PARAMETER	-65°F		70°F		165°F		AQL
	MIN	MAX	MIN	MAX	MIN	MAX	
Dynamic Response Index (DRI) #	-	-	-	18.0	-	22.0	.65
Separation Velocity (ft/s)	35	-	40	-	45	-	1.0
Ignition Delay (ms)	-	30	-	30	-	30	.65
Axial Thrust (lb_f)	-	7,000	-	7,000	-	7,000	1.0

DRI is defined in MIL-S-9479 (see 6.4.3)

3.6 Propellant. The propellant shall be in accordance with MIL-P-82652.

3.7 Radiographic requirements. Each loaded cartridge assembly shall conform to the radiographic requirements of MIL-STD-453, radiographic quality level 1.

3.8 Shear pin strength. Each lot of shear pins (drawings 11740613) shall be tested in accordance with 4.5.7. Shear pins shall shear when subjected to a load of 41 ± 5 lbs applied at the rate of 0.125 inches per minute.

3.9 Protective finish. Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of contour configuration.

3.10 Environmental requirements. The cartridge assemblies shall show no evidence of disintegration of propellant or derangement of components and shall be capable of meeting the ballistic performance requirements of 3.5 when test fired in accordance with 4.4.2 after exposure to the following environmental conditions:

3.10.1 High temperature. The cartridge assembly shall be capable of withstanding the high temperature test of 4.4.1.1.

3.10.2 Vibration. The cartridge assembly shall be capable of withstanding the vibration test of 4.4.1.2.

3.10.3 Temperature-shock. The cartridge assembly shall be capable of withstanding the temperature-shock test of 4.4.1.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

3.11 Identification marking. Each cartridge assembly shall be marked in accordance with drawing 11740605.

3.11.1 Lot designation. The following lot designation system shall be used for identification marking of each cartridge assembly:

aa-xxx-cccc

where:

aa = the cumulative total of lots produced by one supplier

xxx = the letter designation (abbreviation) of the supplier

cccc = the month and year of the manufacture of the oldest propellant batch used in the cartridge assembly lot

3.12 Workmanship. The requirements for workmanship shall be as specified in the applicable drawings, referenced specifications and the following:

3.12.1 Metal defects. All components shall be free of cracks, splits, cold shots, inclusions, porosity or any similar defect.

3.12.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.12.3 Foreign matter. No part of the assembly shall contain chips, dirt, grease, rust, corrosion or other foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)

b. Quality conformance inspection (see 4.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: Room ambient 18 to 35°C (65 to 95°F)

b. Altitude: Normal ground

c. Vibration: None

d. Humidity: Room ambient to 95 percent relative, maximum

4.4 First article inspection. Unless otherwise specified in the contract (see 6.2), a first article sample of 21 cartridge assemblies, manufactured in accordance with 3.1, shall be submitted to the Naval Ordnance Station, Indian Head, Maryland 20640 for first article inspection. The first article samples shall be subjected to the quality conformance inspection of 4.5 with the exception of the test firing of 4.5.5 followed by environmental testing, radiographic examinations and static firing in the sequence specified in TABLE II. Acceptance of the first article sample shall be based on no defects in the sample. Any production of the cartridge assemblies by the contractor, prior to approval of the first article sample, shall be at the contractor's risk. First article samples shall not be included as a part of the quantity specified for delivery in the contract (see 6.2).

4.4.1 Environmental tests.

4.4.1.1 High temperature. The cartridge assembly shall be subjected to a high temperature test in accordance with Procedure I of method 501.1 of MIL-STD-810 with the exception that the test item shall be maintained at 165°F for 50 hours minimum.

4.4.1.2 Vibration. The cartridge assembly shall be subjected to random vibration in accordance with procedure IA of Method 514.2 of MIL-STD-810 for 6 hours with 2 hours on each axis. Before vibration, units shall be temperature conditioned in accordance with TABLE II. The input vibratory acceleration shall be in accordance with curve A of Figure 514.2 - 2A with a Wo factor of $0.1G^2/Hz$. If the cartridge assembly must be removed from the environmental conditioning chamber or if the temperature falls outside the specified temperature limits for a period of more than 5 minutes, the testing shall be stopped and the unit shall be reconditioned. A reconditioning time of 2 minutes for every minute the unit is outside the specified temperature envelope shall be required. A continuous temperature history of the unit shall be kept for all conditioning and testing time. Unless otherwise noted, the cartridge assembly shall be mounted on a test fixture in a manner that will simulate actual seat/aircraft installation and excited through the attachment fittings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

TABLE II. First Article Evaluation Test Program.

TEST PARA.	TEST	UNIT NUMBER																				
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
4.5.6	Radiographic Inspection	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a	a
4.4.1.1	High Temperature	b	b	b	b	b	b	b	b	b	b											
4.4.1.2	Vibration -65°F											b	b	b	b	b	b					
4.4.1.2	Vibration +165°F																	b	b	b	b	b
4.5.6	Radiographic Inspection	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c	c
4.4.1.3	Temperature Shock	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d	d
4.5.6	Radiographic Inspection	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e	e
4.4.2	Static Firing -65°F	f	f	f	f							f	f			f			f	f		
4.4.2	Static Firing +70°F					f	f										f					
4.4.2	Static Firing +165°F							f	f	f	f			f	f			f			f	f

* Letters denote sequence of testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

4.4.1.3 Temperature shock. The cartridge assembly shall be subjected to a temperature shock test in accordance with procedure I of method 503.1 of MIL-STD-810 with the exception that the duration of each cycle shall be 8 hours.

4.4.2 Static firing test. Within 30 days after completion of environmental exposure, the cartridge assemblies shall be static fired at the Naval Ordnance Station, Indian Head, Maryland 20640. The sample shall be temperature conditioned per TABLE II for a minimum of 8 hours and test fired within 10 minutes after removal from the conditioning chamber to verify conformance to the requirements of 3.5. Data specified in TABLE I, shall be analyzed in accordance with MIL-STD-414. Non conformance with TABLE I shall be cause for rejection of the first article sample.

4.5 Quality conformance inspection. The quality conformance inspection shall consist of the examinations and tests of 4.5.4 thru 4.5.7 conducted on samples selected as specified in 4.5.2. The shear pin test of 4.5.7 shall be performed prior to installation of any shear pins from the lot in question into cartridge assemblies. The contractor is responsible for assuring that all cartridge assemblies offered for acceptance meet all the requirements of the applicable drawings and specifications. Items of inspection shall be serialized and inspection data traceable to a specific serial number.

4.5.1 Test reports. When specified in the contract (see 6.2), the contractor shall furnish test reports to the procuring activity. Test reports shall include the following information:

a. Propellant description (see 3.6 and 6.3.1).

b. Static firing performance test results (see 4.5.5 and 6.3.2).

c. Summary sheet (see 6.3.3).

d. Ammunition data cards (see 6.3.4).

e. Propellant/assembly production records (see 6.3.5).

f. Certification of age of explosive components and propellant (see 3.4).

4.5.2 Sampling for quality conformance inspection.

4.5.2.1 Lot. For the purposes of identification, inspection, and shipment, a lot of loaded assemblies shall consist of 360 assemblies, maximum, inclusive of test samples. The homogeneity of inspection lot shall be retained as follows:

a. Components were produced by homogeneous process.

b. Ingredients were from the same ingredient lot when more than one cartridge batch comprises the cartridge lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

4.5.2.2 Sampling for examination. Designation of defects (critical, major, and minor) shall be in accordance with WR-43. Samples for examination shall be selected in accordance with inspection level II of MIL-STD-105.

4.5.2.3 Sampling for static firing test. A sample of 21 cartridge assemblies shall be submitted to the Naval Ordnance Station, Indian Head, Maryland 20640 for static firing in accordance with 4.5.5. Cartridge assembly samples shall not be preselected during production. Cartridge assemblies selected for samples shall not be included as a part of the quantity specified for delivery in the contract or order. Only primary components from a single primary component lot shall be used in a production lot of cartridge assemblies. One primary component lot may be used in more than one cartridge assembly production lot. The ballistic sample size shall be divided as equally as possible among cartridge batches. From each cartridge batch not represented in the 21 sample cartridge assemblies, one sample cartridge shall be selected for static firing by the contractor (see 4.5.5.1), so that at least one cartridge from each cartridge batch has been static fired.

4.5.2.4 Sampling for radiographic inspection. Each cartridge assembly shall be subjected to the radiographic inspection specified in 4.5.6.

4.5.2.5 Sampling for shear pin test. A sample of 50 shear pins from each shear pin lot shall be subjected to the shear pin strength test of 4.5.7.

4.5.3 Resubmission of rejected lot. A sample of 42 cartridge assemblies shall be selected in accordance with 4.5.2.3 and submitted when, with prior approval of the procuring activity, the contractor requests that the rejected lot be test fired under different conditions or the contractor believes a rejected lot may be reworked to meet the requirements of this specification.

4.5.4 Examination. Sample cartridge assemblies selected in accordance with 4.5.2.2 shall be examined for defects in accordance with the applicable drawings, 3.9, 3.11 and 3.12. The acceptable quality levels (AQL's) per MIL-STD-105 shall be as follows:

a. Critical defects: 0.04 percent defective

b. Major defects: 1.0 percent defective

c. Minor defects: 2.5 percent defective

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

4.5.5 Static firing test. Sample cartridge assemblies selected in accordance with 4.5.2.3 shall be static fired at the Naval Ordnance Station, Indian Head, Maryland 20640 within 30 days after submission for acceptance of the cartridge assembly lot. The samples shall be divided into 3 equal groups and one group conditioned at each temperature specified in TABLE I for a minimum of 8 hours and static fired within 10 minutes after removal from the conditioning chamber. Data specified in TABLE I shall be analyzed in accordance with MIL-STD-414. Nonconformance with TABLE I shall be cause for rejection of the lot.

4.5.5.1 Contractor static firing test. Sample cartridges selected by the contractor in accordance with 4.5.2.3 shall be static fired by the contractor as cartridge batch acceptance tests. An equal number of cartridges shall be fired at each temperature: -65°F, +70°F and +165°F. Failure of any cartridge to meet the requirements of TABLE I shall be cause for rejection of the specific batch of cartridges.

4.5.5.2 Post static firing disassembly. A post firing disassembly of all contractor tested units shall be conducted by the project engineer. Detailed observations on conditions, including marginal conditions, of individual components shall be noted. When specified in the contract (see 6.2), a disassembly findings report shall be submitted to the procuring activity.

4.5.6 Radiographic inspection. Cartridge assemblies shall be radiographically inspected in accordance with MIL-STD-453, radiographic quality level 1. Any deficiency shall be cause for rejection of the unit. Radiographs shall be capable of detecting defects and cartridge assembly components 0.03 inch in length or width, whichever is smaller. If all components cannot be shown using standard radiographic techniques, neutron radiography shall be employed to show these components. When specified in the contract (see 6.2), all radiographs taken of the cartridge assemblies or components thereof shall be forwarded to the activity designated by the procuring activity. Otherwise, all radiographs shall be inspected on-site by a designated Government representative. Acceptance of the cartridge assembly lot shall be subject to approval of the radiographs by the designated Government activity.

4.5.7 Shear pin test. A load shall be applied at a rate of 0.125 inches per minute to each sample shear pin selected in accordance with 4.5.2.5. If any shear pin fails to shear at 41 ± 5 lbs. the entire lot of shear pins shall be rejected and no pin from that lot shall be used in any catapult assembly.

4.6 Packaging inspection. The packaging, packing and marking shall be inspected to verify conformance with the requirements of section 5.

5. PACKAGING

5.1 Preservation, packaging and packing. Unless otherwise specified in the contract (see 6.2), preservation, packaging, and packing shall be level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Preservation, packaging and packing shall be in accordance with the applicable drawings and MIL-P-116, as specified in the contract (see 6.2). Containers shall conform to Uniform Freight Classification, National Motor Freight Classification, or to rules of other carriers applicable to the mode of transportation.

5.2 Marking. In addition to any special markings required by the contract (see 6.2), each container shall be marked in accordance with MIL-STD-129 and Code of Federal Regulations 49 CFR 171-179 (see 6.8.1).

6. NOTES

6.1 Intended use. The CCU-22/A impulse cartridge assembly is intended to be used with the CKU-5/A aircraft ejection seat catapult assembly in the F-15, F-16, A-10 and B-1 aircraft.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required (exclusive of first article and static firing test samples) (see 4.4 and 4.5.2.3).

c. When a first article sample is not required (see 3.1, 4.4 and 6.5).

d. Assigned activity for first article inspection and static firing tests (see 4.4, 4.4.2, 4.5.2.3, 4.5.5 and 6.7).

e. Applicable drawing number(s) and/or methods and procedures of MIL-P-116 to be used for level A packaging (see 5.1.1).

f. Packaging requirements if other than level A (see 5.1).

g. Any special markings required (see 5.2 and 6.8.1).

h. Safety precautions (see 6.8).

i. Disposition of hardware, scrap propellant and metal parts (see 6.9).

j. That the contractor retain radiographs on file (see 6.10).

k. Inspection conditions if other than as specified (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. The items of deliverable data required by this specification are cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID *
4.5.1	Test Report	-
4.5.6	Radiographs	-

*DID's (Data Item Descriptions/DD Forms 1664) for the above data requirement are documented in the applicable ADL (Authorized Data Lists). Such data will be delivered as identified on completed (numbered) DID's when specified on DD Forms 1423 (Contract Data Requirements Lists) and incorporated into applicable contracts.

6.3 Description of data. The following paragraphs are a description of data to be included in test reports per 4.5.1 when specified in the contract or order (see 6.2.2).

6.3.1 Propellant description. The following propellant information should be submitted with each production lot. The materials and components of each propellant batch should be listed with the manufacturer, lot number, and date of manufacture. The burning rates at 2500, 5000, and 7500 psi performed at -65°, 70° and 165°F for each pressure (three samples at each temperature and pressure per mix) should also be included. In addition, include the results of tensile strength and elongation tests at -65°, 70° and 165°F with a pull rate of 2 inches/minute (three samples at each temperature per mix), heat of explosion (3 samples per mix), and verification that ingredients were properly weighed and added to each mix (mix sheet (s)).

6.3.2 Static firing performance tests. All computations and data required for ballistics evaluation, generated during quality conformance inspection static firings per 4.5.5 (Government) and 4.5.5 (contractor). shall be reported including firing traces. The following information shall also be listed:

a. Grain designation, manufacture, lot number, and date of propellant manufacture

b. Type of test equipment.

c. Deviations from standard testing procedures.

d. Additional comments (malfunctions, unusual occurrences).

e. Disassembly findings report (see 4.5.5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

6.3.3 Summary sheet. A summary of the results of the tests for the parameters listed in TABLE I shall be submitted to the designated Government activity for each inspection lot. The summary shall include the sample size, number and nature of defects found, and the disposition (accepted or rejected).

6.3.4 Data cards. Data cards (DD form 1650) shall be completed for each cartridge assembly lot. Copies shall be provided in accordance with contract requirements and one copy shall be forwarded to the Commanding Officer, Naval Ordnance Station, Indian Head, MD 20640 (Code 5152).

6.3.5 Propellant/assembly production records. The contractor shall prepare and retain for the service life of the unit propellant production records including batch number, mix designation, rocket motor lot number, rocket motor serial number, cartridge lot number, and cartridge serial number.

6.4 Definitions.

6.4.1 Catapult ignition delay time. Catapult ignition delay time is the elapsed time from the shearing of the firing pin shear pin to first indication of catapult thrust.

6.4.2 Catapult separation velocity. Catapult separation velocity is defined as the average velocity of the simulated ejected weight propelled horizontally at catapult separation measured over the interval from 6 inches before to 6 inches after separation.

6.4.3 Catapult dynamic response index - (DRI). DRI is representative of the maximum dynamic compression of the vertebral column of the human body, as defined in MIL-S-9479.

6.4.4 Propellant batch. A propellant batch is a mix in which each ingredient is composed entirely of one homogeneous lot.

6.4.5 Catapult cartridge batch. A catapult cartridge batch is all cartridges cast from one propellant batch.

6.4.6 Catapult cartridge lot. A catapult cartridge lot is a group of cartridges composed of one or more cartridge batches all having the same ingredient lots.

6.4.7 Primary components. Primary components are all components containing explosive ingredients. These include the cartridge percussion primers, housing assembly, cartridge case and grain assembly and sleeve assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

6.5 First article sample waiver. First article samples submitted and approved on a recent contract (a contract remaining in production or a contract out of production for less than one year) may be accepted by the procuring activity in lieu of an additional preproduction inspection. When the first article sample is waived (see 6.2.1(c)), the procurement document should contain a statement specifying that the standards of workmanship exhibited by the previously approved first article sample shall determine the minumum requirements of the current contract or order.

6.6 Pressure transducers. Instructions for adaption of first article catapult assemblies for pressure transducers should be compatible with instrumentation that has a response of not less than 600 Hz and that is capable of detecting ignition peak pressures and unstable burning rates.

6.7 Test facility for preproduction inspection. The Naval Ordnance Station, Indian Head, Maryland is the Design Agent for the product covered by this specification. As such they are equipped to perform the first article inspection and static firing tests specified herein. Except when special conditions warrant otherwise, the Naval Ordnance Station, Indian Head should be designated as the test facility for the first article inspection and the static firing tests (see 6.2.1(d)).

6.8 Safety precautions. The safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material" (DOD 4145.26M) are applicable and should be specified in the contract or order as required by the Armed Services Procurement Regulations (ASPR) 1-323.

NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore" (OP 5) should be made applicable.

6.8.1 Explosive hazard classification. The explosive hazard classification for this cartridge assembly has been designated as:

Explosive Hazard Calssification - Class 3

Storage Compatibility Group - Group B

Department of Transportation (DOT) Hazard Class - Cl B

DOT Marking - Propellant Explosive

6.8.2 Hazard notice. The cartridge assembly described herein is flammable and/or explosive and consequently presents a hazard in manufacture, handling, storage and shipment. The contractor should recognize this hazard and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

6.9 Disposition of hardware, scrap propellant, and metal parts. The contract should specify that all items purchased become the property of the U.S. Government; no hardware, propellant, or metal parts acceptable, scrapped, or tested be disposed of without authorization of the procuring activity; all items be made available to the procuring activity upon request; and that the disposal of any tested hardware, propellant, or metal parts without authorization by the procuring activity will result in the test being declared invalid, and a retest will be required.

6.10 Retention of radiographs. The contract should specify that all radiographs of accepted lots of cartridge assemblies be retained on file by the contractor for 7 years or 1 year past the service life of the unit, whichever is longer.

6.11 Life. The rocket catapult has a design life of 7 years with and installed service life of 5 years from the date of propellant manufacture. Design life includes both the installed service life and the shelf life.

Custodian
Navy - OS

Preparing Activity
Navy - OS

Project Number:
1377-N615

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-82651(OS), Cartridge, Impulse, CCU-22/A Assembly

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DoD 316

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Ordnance Station (611)
Standardization Division
Indian Head, MD 20640

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:19Z
Check the source to verify that this is the current version before use.