MILITARY STANDARD

ELECTRONIC EQUIPMENT PARTS
SELECTED STANDARDS
MICROCIRCUITS AND SEMICONDUCTORS

TO ALL HOLDERS OF MIL-STD-242G(NAVY), PART 5:

1. THE FOLLOWING PAGES OF MIL-STD-242G(NAVY), PART 5 HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	31 August 1981	(Reprinted without change)	
vi	12 April 1985	vi	10 February 1983
Delete	----	110.1	10 February 1983
Delete	----	110.2	10 February 1983
112.1	12 April 1985	112.1	31 August 1981
112.2	12 April 1985	112.2	31 August 1981
112.3/112.4	12 April 1985	112.3	31 August 1981
113/114	12 April 1985	113	31 August 1981
115.1	12 April 1985	114	31 August 1981
115.2	12 April 1985	115.1	31 August 1981
116.1	12 April 1985	115.2	31 August 1981
116.2	12 April 1985	NONE	----
117/118	12 April 1985	116	31 August 1981
119/120	12 April 1985	117	31 August 1981
201.1	12 April 1985	NONE	----
201.2	12 April 1985	NONE	----
201.3	12 April 1985	NONE	----
201.4	12 April 1985	NONE	----
312	12 April 1985	312	31 August 1981
313	31 August 1981	(Reprinted without change)	
314	31 August 1981	(Reprinted without change)	
315	12 April 1985	315	31 August 1981

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. HOLDERS OF MIL-STD-242G(NAVY), PART 5, WILL VERIFY THAT PAGE CHANGES AND ADDITIONS INDICATED ABOVE HAVE BEEN ENTERED. THIS NOTICE PAGE WILL BE RETAINED AS A CHECK SHEET. THIS ISSUANCE, TOGETHER WITH APPENDED PAGES, IS A SEPARATE PUBLICATION. EACH NOTICE IS TO BE RETAINED BY STOCKING POINTS UNTIL THE MILITARY STANDARD IS COMPLETELY REVISED OR CANCELLED.

Review activity:
Navy - AS, SH, OS

User activities:
Navy - MC

Preparing activity:
Navy-EC

(Project NO 59GP-N049)

FSC 59GP

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

d. DEVICE CLASS. THE DEVICE CLASS IS DESIGNATED BY A SINGLE LETTER IDENTIFYING THE PRODUCT ASSURANCE LEVEL (B IS THE MINIMUM ACCEPTANCE LEVEL).

e. CASE OUTLINE. THE CASE OUTLINE IS DESIGNATED BY A SINGLE LETTER ASSIGNED TO EACH OUTLINE WITHIN EACH DETAIL SPECIFICATION.

f. LEAD FINISH. THE LEAD FINISH IS DESIGNATED BY A SINGLE LETTER AS FOLLOWS:

FINISH LETTER	LEAD FRAME MATERIAL AND FINISH
A	TYPES A OR B, WITH HOT SOLDER DIP
B	TYPES A OR B, WITH ACID TIN PLATE
C	TYPES A OR B, WITH GOLD PLATE
X	TYPES A OR B, WITH FINISHES A, B OR C

NOTES

1. THE LIST FOR MICROCIRCUITS DOES NOT SPECIFY THE FINAL TWO ELEMENTS OF THE PART NUMBER (PARAGRAPHS 5-1.e AND f.). ANY COMBINATION OF OUTLINE, AND LEAD FINISH IS APPROVED FOR USE. THE FINISH DESIGNATION "X" IS NOT MARKED ON THE MICROCIRCUIT OR ITS PACKAGING, BUT IS USED ONLY IN DRAWINGS, PARTS LISTS, PURCHASE ORDERS OR OTHER DOCUMENTS WHERE ANY OF THE LEAD FINISHES ARE CONSIDERED ACCEPTABLE AND INTERCHANGEABLE.

2. NO OUTLINE DRAWINGS ARE PROVIDED FOR THE MICROCIRCUITS BECAUSE THE PACKAGE CONFIGURATION IS INDICATED BY PART NUMBER. REFER TO THE DETAIL SPECIFICATION FOR COMPLETE CONFIGURATION INFORMATION.

Review activities:
Navy - AS, SH, OS

User activity:
Navy - MC

Preparing activity:
Navy - EC

(Project Number 59GP-N031-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SUBJECT/SECTION	PAGE
100 MICROCIRCUITS	
112 DIGITAL, LPS-TTL	112.1 THRU 112.3
114 DIGITAL, CMOS	114
115 LINEAR	115.1 THRU 115.2
116 MEMORIES	116.1 THRU 116.2
117 MICROPROCESSORS	117
119 DIGITAL LPAS-TTL	119
200 SEMICONDUCTORS, DIODES	
201 SEMICONDUCTOR, INDEX (DIODES)	201.1 THRU 201.4
205 SEMICONDUCTOR OUTLINE DRAWINGS	205.1 THRU 205.29
210 VOLTAGE-VARIABLE CAPACITORS	210
211 GENERAL PURPOSE DIODES AND RECTIFIERS	211
212 VOLTAGE REFERENCE	212
213 VOLTAGE REGULATOR	213.1 THRU 213.4
214 CURRENT REGULATOR	214
215 SWITCHING AND FAST RECOVERY RECTIFIERS	215
216 TRANSIENT VOLTAGE SUPPRESSORS	216
217 LIGHT EMITTING	217
218 OPTICALLY COUPLED ISOLATORS	218
300 SEMICONDUCTORS, TRANSISTOR	
301 SEMICONDUCTOR, INDEX (TRANSISTORS)	301.1 THRU 301.2
310 DARLINGTON	310
311 THYRISTOR(SILICON CONTROLLED RECTIFIER)	311
312 FIELD EFFECT	312
313 UNIJUNCTION	313
314 DUAL	314
315 HIGH FREQUENCY	315
316 NPN, LOW POWER(PC§ 5 WATTS @ TA=25°C) GEN PURP & SWITCH	316
317 PNP, LOW POWER(PC§ 5 WATTS @ TA=25°C) GEN PURP & SWITCH	317
318 NPN, POWER TRANSISTOR (PC† 5 WATTS)	318
319 PNP, POWER TRANSISTOR (PC† 5 WATTS)	319
320 CHOPPER	320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, LPS-TTL MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
31201B--	ADDER	DUAL FULL	54LS 83A
31202B--		4-BIT BINARY FULL, LOOKAHEAD AND CARRY	54LS283A
30801B--	ARITHMETIC	ARITH LOGIC UNIT/FUNCTION-GEN	54LS181
30201B--	BUFFER	DUAL 4-INPUT NAND BUFFER	54LS40
30202B--		QUAD, 2-INPUT NAND	54LS37
30203B--		QUAD, 2-INPUT, NAND, BUFFER, OC	54LS38
32301B--		QUAD BUS, BUFFER GATE, INVERTING	54LS125
32302B--		BUFFER, QUAD, TS OUT	54LS126
32401B--		OCTAL(SCH TRIG) INVERTING, TS	54LS240
32402B--		OCTAL(SCH TRIG) NON-INV, TS, SYN CTRLS	54LS241
32403B--		OCTAL(SCH TRIG) NON-INV, TS COM CTRLS	54LS244
32102B--	BUFFER DRIVERS	QUAD, 2-INPUT NAND, OC, TO 15V	54LS26
32201B--		HEX, TS	54LS365
32202B--		HEX, INVERTER, TS	54LS366
32203B--		HEX, TS W/2-BIT & 4-BIT SEC	54LS367
32204B--		HEX, INV,TS W/2-BIT & 4-BIT SEC	54LS368
31101B--	COMPARATOR	4-BIT	54LS85
31501B--	COUNTER	DECADE COUNTER	54LS90
31502B--		4-BIT BINARY COUNTER	54LS93
31503B--		BCD DECADE W/MR(OUTPUTS)	54LS160A
31504B--		SYN BINARY W/MR(OUTPUTS)	54LS161A
31507B--		UP/DOWN DECADE W/SEP CLKS	54LS192
31508B--		UP/DOWN BINARY W/SEP CLKS	54LS193
31509B--		UP/DOWN BINARY W/PRST & RIPPLE CLKS	54LS191
31510B--		DIVIDE BY 12	54LS92
31511B--		BCD DECADE W/MS	54LS162A
31512B--		SYN BINARY W/MR	54LS163A
31513B--		UP/DOWN DEC W/PRST & RIPPLE CLR	54LS190
32003B--		DEC ASYN W/CORNER PWR PINS	54LS290
32004B--		4-BIT BINARY COUNTER, RIPPLE	54LS293
32701B--		DUAL DECADE ASYN W/CORN PWR PINS	54LS390
32702B--		DUAL DIVIDE BY 16 W/CORN PWR PINS	54LS393
32703B--		DUAL DEC ASYN W/CORN PWR PINS & MS	54LS490
30701B--	DECODERS	SINGLE, 3-TO-8 LINE	54LS138
30702B--		DUAL, 2-TO-4 LINE DECODER/DEMUX	54LS139
30703B--		BCD TO DECIMAL	54LS42
30704B--		BCD TO SEVEN SEGMENT, AL, OC, 15V	54LS47

Supersedes Page 112.1 of 31 August 1981

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, LPS-TTL MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
32601B--	DEMULTIPLEXERS	DUAL 2-TO-4-LINE DEC/DEMUX, TP OUT	54LS155
36002B--		DUAL 2-TO-4-LINE DEC/DEMUX, TP OUT, OC	54LS156
36001B--	ENCODERS	8 INPUT PRIORITY ENCODER	54LS148
36002B--		8-TO-3 LINE PRIORITY, TS OUTPUT	54LS348
30101B--	FLIP-FLOP	DUAL "J-K", M-S, W/CLR	54LS73
30102B--		QUAD, D-TYPE, W/CLR & PRST	54LS74
30103B--		DUAL "J-K" W/CLR & PRST(NEG)	54LS112
30104B--		DUAL "J-K" W PRST(NEG)	54LS113
30105B--		DUAL "J-K" W/CLR, CLK & PRST(NRG)	54LS114
30106B--		D-TYPE HEX SINGLE OUTPUT/CLR	54LS174
30107B--		QUAD D-TYPE COMPL OUTPUT/CLR	54LS175
30108B--		DUAL J-K W/CLR(POS)	54LS107
30109B--		DUAL J-K W/PRST & CLR(POS)	54LS109
30110B--		DUAL J-K W/PRST & CLR	54LS76
32501B--		OCTAL D-TYPE, EDG TRIG, W/CLR	54LS273
32503B--		OCTAL D-TYPE EDG TRIG	54LS374
32504B--		OCTAL D-TYPE W/ENABLE	54LS377
33106B--		HEX D-TYPE, EDG TRIG W/CLR	25LS174
33107B--		QUAD D-TYPE, EDG TRIG W/CLR, COM OUT	25LS175
30001B--	GATE	NAND, QUAD, 2-INPUT	54LS00
30002B--		NAND, QUAD, 2-INPUT, OC	54LS03
30005B--		NAND, TRIPPLE, 3-INPUT	54LS10
30006B--		NAND, TRIPPLE, 3-INPUT, OC	54LS12
30007B--		NAND, DUAL, 4-INPUT	54LS20
30008B--		NAND, DUAL, 4-INPUT, OC	54LS22
30009B--		NAND, 8-INPUT	54LS30
30301B--		NOR, QUAD, 2-INPUT	54LS02
30302B--		NOR, TRIPPLE, 3-INPUT	54LS27
30303B--		EXCLUSIVE-NOR, QUAD, 2-INPUT	54LS266
30401B--		AND-OR-INVERT, DUAL, 2-WIDE	54LS51
30402B--		AND-OR-INVERT, 4-WIDE, 2-3-3-2-INPUT	54LS54
30501B--		OR, QUAD, 2-INPUT	54LS32
30502B--		EXCLUSIVE-OR, QUAD, 2-INPUT	54LS86
31005B--		AND	54LS09
31001B--		AND, TRIPPLE, 3-INPUT	54LS11
31002B--		AND, TRIPPLE, 3-INPUT, OC	54LS15
31003B--		AND, DUAL, 4-INPUT	54LS21
31004B--		AND, QUAD, 2-INPUT	54LS08
31301B--		NAND, DUAL, 4-INPUT, SCH TRG	54LS13
31303B--		NAND, QUAD, 2-INPUT, SCH TRG	54LS132

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, LPS-TTL MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
30003B--	INVERTER	HEX, 1-INPUT	54LS04
30004B--		HEX, 1-INPUT, OC	54LS05
31302B--		HEX, SCHMITT TRIGGERED	54LS14
31601B--	LATCH	QUAD, BISTABLE, COMP OUT	54LS75
31602B--		QUAD, BISTABLE, COMP OUT, SET RESET	54LS279
31603B--		8-BIT, ADDRESSABLE, W/CLR	54LS259
31604B--		QUAD, BISTABLE, COMP OUT, TRANS	54LS375
31901B--		4 X 4 REGISTER FILE	54LS670
30801B--		ALU/FUNCTION GENERATOR	54LS181
30901B--	MULTIPLEXER	8-INPUT, COMP OUT, STROBE	54LS151
30902B--		DUAL, 4-INPUT	54LS153
30903B--		QUAD, 2-INPUT	54LS157
30904B--		QUAD, 2-INPUT, COMP OUT	54LS158
30905B--		8-INPUT, COMP OUT, STROBE, TS	54LS251
30906B--		QUAD, 2-INPUT, TS, OC	54LS257
30907B--		QUAD, 2-INPUT, TS, OC, COMP OUT	54LS258
30908B--		DUAL, 4-INPUT, TS	54LS253
30909B--		QUAD, 2-INPUT, CLKD INPUT, LATCH OUT	54LS298
31401B--	MULTIVIBRATER	DUAL RETRIG, RESETTABLE	54LS123
31402B--		DUAL, MONO, SCH TRG INPUT	54LS221
31403B--		RETRIG, RESETTABLE	54LS122
32901B--	PARITY GEN	8-DATA BIT, ODD, EVEN	54LS280
30601B--	SHIFT-REGISTER	4-BIT UNIVERSAL, BI DIR	54LS194A
30602B--		4-BIT J,K, PARALLEL IN/OUT, SHFT, RGT	54LS195A
30603B--		4-BIT D-TYPE PARALLEL IN/OUT, SHFT RGT	54LS95B
30604B--		5-BIT PAR IN, SERIAL OUT	54LS96
30605B--		8-BIT GATED IN, PAST OUT	54LS164
30606B--		4-BIT, D-TYPE, PAR IN/OUT(RGT,LFT,SHFT) PS	54LS295B
30607B--		4-BIT, D-TYPE, PAR IN/OUT CASCADEABLE(TS)	54LS395A
30608B--		8-BIT, D-TYPE, PAR IN/OUT(W/CLOCK INHIBIT)	54LS165A
30609B--		8-BIT, D-TYPE, PAR IN/OUT(W/CLEAR)	54LS166
32801B--	TRANSCEIVER	QUAD, INVERTING BUS(TS)	54LS242
32802B--		QUAD, NONINVERTING BUS(TS)	54LS243
32803B--		OCTAL NONINVERTING BUS(TS)	54LS245

Supersedes Page 112.3 of 31 August 1981

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, CMOS MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
05401B--	ADDER	4-BIT	4008A
05501B--	BUFFER	HEX, INVERTER	4009A
05502B--		HEX, NON-INVERTING	4010A
05503B--		HEX, INVERTER	4049A
05504B--		HEX, NON-INVERTING	4050A
05601B--	COUNTER	DECADE COUNTER/DIVIDE	4017A
05602B--		PRESETTABLE DIVIDE BY N	4018A
05603B--		14-STAGE RIPPLE CARRY	4020A
05604B--		DIVIDE BY 8 COUNTER/DIVIDE	4022A
05605B--		7-STAGE BINARY COUNTER	4024A
05101B--	FLIP-FLOP	D-TYPE, DUAL, EDGE-TRIGGERED	4013A
05102B--		DUAL, J-K MASTER SLAVE	4027A
05001B--	GATE	QUAD, NAND, 2-INPUT	4011A
05002B--		DUAL, NAND, 4-INPUT	4012A
05003B--		TRIPPLE, NAND, 3-INPUT	4023A
05201B--		DUAL, NOR, 3-INPUT, PLUS INVERTER	4000A
05202B--		NOR, QUAD, 2-INPUT	4001A
05203B--		NOR, DUAL, 4-INPUT	4002A
05204B--		TRIPPLE, NOR, 3-INPUT	4025A
05301B--		DUAL COMPLEMENTARY PAIR PLUS INVERT	4007A
05302B--		QUAD, AND-OR SELECT	4019A
05303B--		QUAD, EXCLUSIVE-OR	4030A
17001B--		QUAD, AND, 2-OUTPUT	4081B
17002B--		DUAL, AND, 4-INPUT	4082B
17003B--		TRIPPLE, AND, 3-INPUT	4073B
17101B--		QUAD, OR, 2-INPUT	4071B
17102B--		DUAL, OR, 4-INPUT	4072B
17103B--		TRIPPLE, OR, 3-INPUT	4075B
17201B--		DUAL, AND-OR-INVERT, 2-WIDE, 2-IN	4085B
17202B--		EXPANDABLE, AND-OR-INVERTER	4086B
17203B--		QUAD, EXCLUSIVE-OR	4070B
17204B--		QUAD, EXCLUSIVE-NOR	4077B
05701B--	SHIFT REGISTER	DUAL 4-STAGE, DUAL 5-STAGE, STATIC	4006A
05702B--		8-STAGE, SYN, PARALLEL OR SERIAL IN	4014A
05703B--		DUAL 4-STAGE, SER INPUT, PAR OUTPUT	4015A
05704B--		8-STAGE, ASYN	4021A
05705B--		64-STAGE STATIC	4031A

NOTE: USE CMOS SERIES B PARTS AS THEY BECOME QUALIFIED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

LINEAR MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
10101B--	OP AMPLIFIERS	SINGLE, INTERNALLY COMP	741
10102B--		DUAL, INTERNALLY COMP	747
10103B--		SINGLE, EXTERNALLY COMP	LM101A
10104B--		SINGLE, EXTERNALLY COMP	LM108A
10105B--		OP, DUAL LM101	LH2101A
10106B--		OP,	LH2108A
10107B--		SINGLE, HIGH SPEED	LM118
10108B--		DUAL, NO COMP	1558
10601B--		OP, VOLTAGE FOLLOWER	LM102
10602B--		OP, VOLTAGE FOLLOWER(HIGH SPEED)	LM110
11001B--		QUAD OP-AMP, MEDIUM POWER	LM148
11003B--		OP, QUAD, MEDIUM POWER	4741,4156
11004B--		OP, QUAD, MEDIUM POWER	4136
11005B--		OP, LOW PWR, QUAD	LM124
11401B--		OP, GEN, FET, INPUT, LOW POWER	LF155
11402B--		OP, BI-FET(WIDE BAND)	LF156
11405B--		OP, BI-FET(WIDE BAND,HP)	LF156A
11403B--		OP, BI-FET(WIDE BAND UNDER COMP)	LF157
11406B--		OP, BI-FET(WIDE BAND, HP)	LF157A
11404B--		OP, BIPOLAR-JFET	LF155A
12202B--		HIGH SR, INTERNAL COMPENSATED	2600
12203B--		HIGH SR, EXTERNAL COMPENSATED	2620
12204B--		PRECISION HIGH SR, INTERNALLY COMP	2500
12205B--		HIGH SR, INTERNALLY COMPENSATED	2510
12206B--		HIGH SR, EXTERNALLY COMPENSATED	2520
10802B--	ARRAYS	3-ISOLATED NPN TRANS,1-NPN DIFF CON PR	3045
10304B--	COMPARATOR	HIGH SP, SINGLE	LM111
10305B--		HIGH SP, DUAL	LH2111
11201B--		QUAD, BUFFER	LM139
11301B--	CONVERTER	8-BIT, D/A(0.19% LINEARITY)	DAC-08
11302B--		8-BIT, D/A(0.10% LINEARITY)	DAC-08A
10401B--	DRIVER REC	DUAL LINE	55107
10402B--		DUAL LINE(OC)	55108
10403B--		DUAL DIFFERENTIAL DRIVER	9614
10404B--		DUAL DIFFERENTIAL RECEIVER	9615
10405B--		DIFFERENTIAL, OC, TS	55113

Supersedes Page 114 of 31 August 1981

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

LINEAR MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
10201B--	REGULATOR	PRECISION VOLTAGE	723,LM723
10701B--		5-VOLT	LM109
10703B--		12-VOLT, 500MA	LM141H-12/78M12 78M12,LM140H-12
10707B--		FIXED(+12V @ 0.5A MAX)	LM140K-12/7812
10704B--		FIXED(+15V @ 0.5A MAX)	78M15,LM140H-15
10702B--		FIXED(+5V @ 1.0A MAX)	78M05,LM140H-05
10706B--		FIXED(+5V @ 1.0A MAX)	LM140K-05
10708B--		FIXED(+15V @ 1.0A MAX)	LM140K-15
10709B--		FIXED(+24V @ 1.0A MAX)	LM140K-24
11501B--		FIXED(-5V @ 0.5A MAX)	LM120H-05
11502B--		FIXED(-12V @ 0.5A MAX)	LM120H-12,79M12
11503B--		FIXED(-15V @ 0.5A MAX)	LM120H-15,79M15
11505B--		FIXED(-5V @ 1.0A MAX)	LM120K-05
11506B--		FIXED(-12V @ 1.0A MAX)	LM120K-12
11101B--	SWITCH,ANALOG	2-SPST, 30ohm ON RES	DG181A
11102B--		2-SPST, 75ohm ON RES	DG182A
11103B--		2-DPST, 30ohm ON RES(-7.5 TO 15 SIG)	DG184A
11104B--		2-DPST, 75ohm ON RES(-10 TO 15 SIG)	DG185A
11105B--		SPDT, 50ohm ON RES(+7.5 SIG)	DG187A
11106B--		SPDT, 75ohm ON RES(-15 TO 10 SIG)	DG188A
11107B--		2-SPDT, HIGH SP	DG190A
11108B--		2-SPDT, HIGH SP	DG191A
10901B--	TIMER	SINGLE PRECISION	555

Supersedes Page 115.1 of 31 August 1981

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, MEMORIES MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
20101B--	PROM	512-BIT, 64-WORDS/8-BITS/WORD OC, TTL	54186,HPROM 512 MCM5303
20301B--		1024-BIT(256 X4), OC, S-TTL	7610, 5300-1 82S126,93417
20302B--		1024-BIT(256 X4), TS, S-TTL	7611, 5301-1, 82S129,93427
20401B--		2048-BIT(512 X4), OC, S-TTL	7620,5303-1, 82S130,93436
20402B--		2048-BIT(512 X4), TS S-TTL	7621,5306-1 82S131,93446
20601B--		4096-BIT(1024 X4), OC, S-TTL	7642,5352-1 82S136,93452
20602B--		4096-BIT(1024 X4), TS, S-TTL	7643,5353-1, 82S137,93453
20701B--		256-BIT(32 X 8), OC, S-TTL	7602,5330, 82S23
20702B--		256-BIT(32 X 8), TS, S-TTL	7603, 5331, 82S123
20801B--		4096-BIT(512 X 8), OC, S-TTL	7640,5340-1, 82S140, 93438
20802B--		4096-BIY(512 X 8), TS, S-TTL	7641,5341-1,
20902B--		2048 X 4 PROM (FUSIBLE LINK,TS)	82S185
21002B--		2048 X 8 PROM (FUSIBLE LINK,TS)	82S191
21004B--		2048 X 8 PROM (FUSIBLE LINK,TS)	93Z511 82S141,93448
20903B--		8192-BIT(1024 X 8), OC, S-TTL(LOW PWR)	82S180
20904B--		8192-BIT(1024 X 8), TS, S-TTL(LOW PWR)	7681,5381-1, 82S181,93451
20905B--		8192-BIT(1024 X 8), TS, S-TTL	82S2708, 93461
21002B--		16,384-BIT(2048 X 8), TS, S-TTL	76161, 53S1681 82S191,93511
23101B--	RAM	1024 X 1 STATIC RAM (60 ns)	93415
23102B--		1024 X 1 STATIC RAM (60ns)	93425
23103B--		1024 X 1 STATIC RAM (70ns)	93L415
23104B--		1024 X 1 STATIC RAM (70 ns)	93L425
23108B--		1024 X 1 STATIC RAM (45ns)	82S115
23112B--		256 X 1 STATIC RAM LOW POWER(75 ns)	93L422
23113B--		1024 X 1 STATIC RAM LOW POWER(50 ns)	93L425A
23115B--		256 X 1 STATIC RAM LOW POWER(55 ns,TS)	93L422A
23801B--		4096 X 1 STATIC RAM(85ns)	2147
23803B--		4096 X 1 STATIC RAM(70ns)	2147H
23805B--		1024 X 4 STATIC RAM(55ns)	2147H-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, MEMORIES MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
23806B--	PALS	1024 X 4 STATIC RAM(70ns)	2148H
23807B--		1024 X 4 STATIC RAM(45ns)	2147H-2
24001B--		16384 X 1-BIT, TS, NMOS(200ns)	2117,4116
24002B--		16384 X 1-BIT, TS, NMOS(250ns)	2117,4116
24402B--		64K X 1 DYNAMIC RAM(2ms REFRESH,TS)	4564
50301B--		OCTAL 10-INPUT AND-OR GATE ARRAY	PAL-10H8
50303B--		QUAD 14-INPUT AND-OR GATE ARRAY	PAL-14H4
50306B--		10-INPUT 8-OUTPUT AND-OR-INVERT GATE	PAL-10L8

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL,8-BIT MICROPROCESSOR MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
42001B--	MICROPROCESSOR	8-BIT,N-CHANNEL,SILICON GATE	8080A
52002B--		N-CHANNEL,SILICON GATE, 16 BIT	Z8002CPU
52004B--		N-CHANNEL,SILICON GATE, 16 BIT	Z8002ACPU
53001B--		16-BIT FIXED INSTR MICRO(5.0MHz) N-CHANNEL	8086

Supersedes Page 116 of 31 August 1981

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, LPAS-TTL MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
34001B--	GATE	TRIPLE 3-INPUT AND	54F08
34002B--		TRIPLE 3-INPUT AND	54F11
33401B--		4-2-2-2 INPUT AND-OR-INVERTER	54F64
33001B--		QUAD 2-INPUT NAND	54F00
33002B--		HEX INVERTER	54F04
33003B--		TRIPLE 3-INPUT NAND	54F10
33004B--		DUAL 4-INPUT NAND	54F20
34501B--		QUAD 2-INPUT EXCLUSIVE OR	54F86
33501B--		QUAD 2-INPUT OR	54F32
33301B--		QUAD 2-INPUT NOR	54F02
33201B--	BUFFER	OCTAL BUFFER W/ACTIVE ENABLED INV OUT	54F240
33202B--		OCTAL BUFFER W/ACTIVE ENABLED NON-INV	54F241
33203B--		OCTAL BUFFER W/ENABLE NON-INV OUTPUT(TS)	54F244
34602B--	LATCH	OCTAL TRANS LATCH W/ACTIVE ENABLE(TS)	54F533
34901B--	GENERATOR	9-BIT ODD/EVEN PARITY GENERATOR/CHECKER	54F280
33909B--	MULTIPLEXER	DUAL 4-INPUT MULTIPLIER	54F352
33702B--	DECODER	DUAL 1 TO 4 W/ACTIVE LOW OUT, ENABLE IN	54F533
34901B--	PARITY CHECKER	9-BIT ODD/EVEN PARITY GEN/CHECKER	54F280

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (DIODES)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX*1N746A-1	127	DO204	213.1
JANTX*1N747A-1	127	DO204	213.1
JANTX*1N748A-1	127	DO204	213.1
JANTX*1N749A-1	127	DO204	213.1
JANTX*1N750A-1	127	DO204	213.1
JANTX*1N751A-1	127	DO204	213.1
JANTX*1N752A-1	127	DO204	213.1
JANTX*1N753A-1	127	DO204	213.1
JANTX*1N754A-1	127	DO204	213.1
JANTX*1N755A-1	127	DO204	213.1
JANTX*1N756A-1	127	DO204	213.1
JANTX*1N757A-1	127	DO204	213.1
JANTX*1N758A-1	127	DO204	213.1
JANTX*1N759A-1	127	DO204	213.1
JANTX*1N821-1	159	DO7	212
JANTX*1N823-1	159	DO7	212
JANTX*1N825-1	159	DO7	212
JANTX*1N827-1	159	DO7	212
JANTX*1N829-1	159	DO7	212
JANTX*1N935B	156	DO7	212
JANTX*1N937B	156	DO7	212
JANTX*1N938B	156	DO7	212
JANTX*1N939B	156	DO7	212
JANTX*1N940B	156	DO7	212
JANTX 1N941B	157	DO7	212
JANTX 1N943B	157	DO7	212
JANTX 1N944B	157	DO7	212
JANTX 1N945B	157	DO7	212
JANTX 1N1186**	297	DO5	211
JANTX 1N1188**	297	DO5	211
JANTX 1N1190**	297	DO5	211
JANTX 1N1202A**	260	DO4	211
JANTX 1N1204A**	260	DO4	211
JANTX 1N1206A**	260	DO4	211
JANTX*1N2804B**	114	TO3	213.1
JANTX*1N2805B**	114	TO3	213.1
JANTX*1N2806B**	114	TO3	213.1
JANTX*1N2807B**	114	TO3	213.1
JANTX*1N2808B**	114	TO3	213.1
JANTX*1N2809B**	114	TO3	213.1
JANTX*1N2810B**	114	TO3	213.1
JANTX*1N2811B**	114	TO3	213.1
JANTX*1N2813B**	114	TO3	213.1
JANTX*1N2814B**	114	TO3	213.1
JANTX*1N2816B**	114	TO3	213.1
JANTX*1N2818B**	114	TO3	213.1
JANTX*1N2819B**	114	TO3	213.1
JANTX*1N2820B**	114	TO3	213.1
JANTX*1N2822B**	114	TO3	213.1
JANTX*1N2823B**	114	TO3	213.1
JANTX*1N2824B**	114	TO3	213.1
JANTX*1N2825B**	114	TO3	213.1
JANTX*1N2826B**	114	TO3	213.1
JANTX*1N2827B**	114	TO3	213.1
JANTX*1N2829B**	114	TO3	213.1
JANTX*1N2831B**	114	TO3	213.1
JANTX*1N2832B**	114	TO3	213.1
JANTX*1N2833B**	114	TO3	213.1
JANTX*1N2834B**	114	TO3	213.1
JANTX*1N2835B**	114	TO3	213.1
JANTX*1N2836B**	114	TO3	213.1
JANTX*1N2837B**	114	TO3	213.1
JANTX*1N2838B**	114	TO3	213.1
JANTX*1N2840B**	114	TO3	213.1
JANTX*1N2841B**	114	TO3	213.1
JANTX*1N2842B**	114	TO3	213.1
JANTX*1N2843B**	114	TO3	213.1
JANTX*1N2844B**	114	TO3	213.1
JANTX*1N2845B**	114	TO3	213.2
JANTX*1N2846B**	114	TO3	213.2
JANTX*1N2970B**	124	DO4	213.2
JANTX*1N2971B**	124	DO4	213.2
JANTX*1N2972B**	124	DO4	213.2
JANTX*1N2973B**	124	DO4	213.2
JANTX*1N2974B**	124	DO4	213.2
JANTX*1N2975B**	124	DO4	213.2
JANTX*1N2976B**	124	DO4	213.2
JANTX*1N2977B**	124	DO4	213.2
JANTX*1N2979B**	124	DO4	213.2
JANTX*1N2980B**	124	DO4	213.2
JANTX*1N2982B**	124	DO4	213.2
JANTX*1N2984B**	124	DO4	213.2
JANTX*1N2985B**	124	DO4	213.2
JANTX*1N2986B**	124	DO4	213.2
JANTX*1N2988B**	124	DO4	213.2
JANTX*1N2989B**	124	DO4	213.2
JANTX*1N2990B**	124	DO4	213.2
JANTX*1N2991B**	124	DO4	213.2
JANTX*1N2992B**	124	DO4	213.2
JANTX*1N2993B**	124	DO4	213.2
JANTX*1N2995B**	124	DO4	213.2
JANTX*1N2997B**	124	DO4	213.2
JANTX*1N2999B**	124	DO4	213.2
JANTX*1N3000B**	124	DO4	213.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (DIODES CONTINUED)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX*1N3001B**	124	DO4	213.2
JANTX*1N3002B**	124	DO4	213.2
JANTX*1N3003B**	124	DO4	213.2
JANTX*1N3004B**	124	DO4	213.2
JANTX*1N3005B**	124	DO4	213.2
JANTX*1N3007B**	124	DO4	213.2
JANTX*1N3008B**	124	DO4	213.2
JANTX*1N3009B**	124	DO4	213.2
JANTX*1N3011B**	124	DO4	213.2
JANTX*1N3012B**	124	DO4	213.2
JANTX*1N3014B**	124	DO4	213.2
JANTX*1N3015B**	124	DO4	213.2
JANTX*1N3154	158	DO7	212
JANTX*1N3155	158	DO7	212
JANTX*1N3156	158	DO7	212
JANTX*1N3157	158	DO7	212
JANTX 1N3644	279	DO204	211
JANTX 1N3645	279	DO204	211
JANTX 1N3646	279	DO204	211
JANTX 1N3647	279	DO204	211
JANTX 1N3671A**	260	DO4	211
JANTX 1N3673A**	260	DO4	211
JANTX*1N3766**	297	DO5	211
JANTX 1N3768**	297	DO5	211
JANTX*1N3891**	304	DO4	215
JANTX*1N3893**	304	DO4	215
JANTX 1N3911**	308	DO5	215
JANTX 1N3913**	308	DO5	215
JANTX 1N3993A**	272	DO4	213.2
JANTX 1N3994A**	272	DO4	213.2
JANTX 1N3995A**	272	DO4	213.2
JANTX 1N3996A**	272	DO4	213.2
JANTX 1N3997A**	272	DO4	213.3
JANTX 1N3998A**	272	DO4	213.3
JANTX*1N4148-1	116	DO204	215
JANTX*1N4150-1	231	DO204	215
JANTX*1N4153-1	337	DO35	215
JANTX 1N4370A-1	127	DO204	213.3
JANTX 1N4371A-1	127	DO204	213.3
JANTX 1N4372A-1	127	DO204	213.3
JANTX*1N4454-1	144	DO204	215
JANTX*1N4460	406	DO204	213.3
JANTX*1N4461	406	DO204	213.3
JANTX*1N4462	406	DO204	213.3
JANTX*1N4463	406	DO204	213.3
JANTX*1N4464	406	DO204	213.3
JANTX*1N4465	406	DO204	213.3
JANTX*1N4466	406	DO204	213.3
JANTX*1N4467	406	DO204	213.3
JANTX*1N4468	406	DO204	213.3
JANTX*1N4469	406	DO204	213.3
JANTX*1N4470	406	DO204	213.3
JANTX*1N4471	406	DO204	213.3
JANTX*1N4472	406	DO204	213.3
JANTX*1N4473	406	DO204	213.3
JANTX*1N4474	406	DO204	213.3
JANTX*1N4475	406	DO204	213.3
JANTX*1N4476	406	DO204	213.3
JANTX*1N4477	406	DO204	213.3
JANTX*1N4478	406	DO204	213.3
JANTX*1N4479	406	DO204	213.3
JANTX*1N4480	406	DO204	213.3
JANTX*1N4481	406	DO204	213.3
JANTX*1N4482	406	DO204	213.3
JANTX*1N4483	406	DO204	213.3
JANTX*1N4484	406	DO204	213.3
JANTX*1N4485	406	DO204	213.3
JANTX*1N4486	406	DO204	213.3
JANTX*1N4487	406	DO204	213.3
JANTX*1N4488	406	DO204	213.3
JANTX*1N4489	406	DO204	213.3
JANTX*1N4490	406	DO204	213.3
JANTX*1N4491	406	DO204	213.3
JANTX*1N4492	406	DO204	213.3
JANTX*1N4493	406	DO204	213.3
JANTX*1N4494	406	DO204	213.3
JANTX*1N4495	406	DO204	213.3
JANTX*1N4496	406	DO204	213.3
JANTX*1N4557B**	114	TO3	213.3
JANTX*1N4558B**	114	TO3	213.3
JANTX*1N4559B**	114	TO3	213.3
JANTX*1N4560B**	114	TO3	213.3
JANTX*1N4561B**	114	TO3	213.3
JANTX*1N4562B**	114	TO3	213.4
JANTX*1N4565A	452	DO7	212
JANTX*1N4566A	452	DO7	212
JANTX*1N4567A	452	DO7	212
JANTX*1N4568A	452	DO7	212
JANTX*1N4569A	452	DO7	212
JANTX*1N4570A	452	DO7	212
JANTX*1N4571A	452	DO7	212
JANTX*1N4572A	452	DO7	212
JANTX*1N4573A	452	DO7	212
JANTX*1N4574A	452	DO7	212
JANTX 1N4938-1	169	DO204	215
JANTX*1N4954	356	DO204	213.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (DIODES CONTINUED)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX*1N4955	356	DO204	213.4
JANTX*1N4956	356	DO204	213.4
JANTX*1N4957	356	DO204	213.4
JANTX*1N4958	356	DO204	213.4
JANTX*1N4959	356	DO204	213.4
JANTX*1N4960	356	DO204	213.4
JANTX*1N4961	356	DO204	213.4
JANTX*1N4962	356	DO204	213.4
JANTX*1N4963	356	DO204	213.4
JANTX*1N4964	356	DO204	213.4
JANTX*1N4965	356	DO204	213.4
JANTX*1N4966	356	DO204	213.4
JANTX*1N4967	356	DO204	213.4
JANTX*1N4968	356	DO204	213.4
JANTX*1N4969	356	DO204	213.4
JANTX*1N4970	356	DO204	213.4
JANTX*1N4971	356	DO204	213.4
JANTX*1N4972	356	DO204	213.4
JANTX*1N4973	356	DO204	213.4
JANTX*1N4974	356	DO204	213.4
JANTX*1N4975	356	DO204	213.4
JANTX*1N4976	356	DO204	213.4
JANTX*1N4977	356	DO204	213.4
JANTX*1N4978	356	DO204	213.4
JANTX*1N4979	356	DO204	213.4
JANTX*1N4980	356	DO204	213.4
JANTX*1N4981	356	DO204	213.4
JANTX*1N4982	356	DO204	213.4
JANTX*1N4983	356	DO204	213.4
JANTX*1N4984	356	DO204	213.4
JANTX*1N4985	356	DO204	213.4
JANTX*1N4986	356	DO204	213.4
JANTX*1N4987	356	DO204	213.4
JANTX*1N4988	356	DO204	213.4
JANTX*1N4989	356	DO204	213.4
JANTX*1N4990	356	DO204	213.4
JANTX*1N4991	356	DO204	213.4
JANTX*1N4992	356	DO204	213.4
JANTX*1N4993	356	DO204	213.4
JANTX*1N4994	356	DO204	213.4
JANTX*1N4995	356	DO204	213.4
JANTX*1N5139A	383	DO7	210
JANTX*1N5140A	383	DO7	210
JANTX*1N5141A	383	DO7	210
JANTX*1N5142A	383	DO7	210
JANTX*1N5143A	383	DO7	210
JANTX*1N5144A	383	DO7	210
JANTX*1N5145A	383	DO7	210
JANTX*1N5146A	383	DO7	210
JANTX*1N5147	383	DO7	210
JANTX*1N5148	383	DO7	210
JANTX*1N5283	463	DO7	214
JANTX*1N5284	463	DO7	214
JANTX*1N5285	463	DO7	214
JANTX*1N5286	463	DO7	214
JANTX*1N5287	463	DO7	214
JANTX*1N5288	463	DO7	214
JANTX*1N5289	463	DO7	214
JANTX*1N5290	463	DO7	214
JANTX*1N5291	463	DO7	214
JANTX*1N5292	463	DO7	214
JANTX*1N5293	463	DO7	214
JANTX*1N5294	463	DO7	214
JANTX*1N5295	463	DO7	214
JANTX*1N5296	463	DO7	214
JANTX*1N5297	463	DO7	214
JANTX*1N5298	463	DO7	214
JANTX*1N5299	463	DO7	214
JANTX*1N5300	463	DO7	214
JANTX*1N5301	463	DO7	214
JANTX*1N5302	463	DO7	214
JANTX*1N5303	463	DO7	214
JANTX*1N5304	463	DO7	214
JANTX*1N5305	463	DO7	214
JANTX*1N5306	463	DO7	214
JANTX*1N5307	463	DO7	214
JANTX*1N5308	463	DO7	214
JANTX*1N5309	463	DO7	214
JANTX*1N5310	463	DO7	214
JANTX*1N5311	463	DO7	214
JANTX*1N5312	463	DO7	214
JANTX*1N5313	463	DO7	214
JANTX*1N5314	463	DO7	214
JANTX*1N5417	411	DO204	215
JANTX*1N5418	411	DO204	215
JANTX*1N5419	411	DO204	215
JANTX*1N5420	411	DO204	215
JANTX 1N5473C	436	DO7	210
JANTX 1N5474C	436	DO7	210
JANTX 1N5475C	436	DO7	210
JANTX 1N5476C	436	DO7	210
JANTX*1N5551	420	DO204	211
JANTX*1N5552	420	DO204	211
JANTX*1N5553	420	DO204	211
JANTX*1N5554	420	DO204	211
JANTX*1N5616	427	DO204	211
JANTX*1N5617	429	DO204	215
JANTX*1N5618	427	DO204	211

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (DIODES CONTINUED)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER	PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX*1N5619	429	DO204	215	JANTX*1N5653A	500	DO13	216
JANTX*1N5620	427	DO204	211	JANTX*1N5654A	500	DO13	216
JANTX*1N5621	429	DO204	215	JANTX*1N5655A	500	DO13	216
JANTX*1N5622	427	DO204	211	JANTX*1N5656A	500	DO13	216
JANTX*1N5623	429	DO204	215	JANTX*1N5657A	500	DO13	216
JANTX*1N5629A	500	DO13	216	JANTX*1N5658A	500	DO13	216
JANTX*1N5630A	500	DO13	216	JANTX*1N5659A	500	DO13	216
JANTX*1N5631A	500	DO13	216	JANTX*1N5660A	500	DO13	216
JANTX*1N5632A	500	DO13	216	JANTX*1N5661A	500	DO13	216
JANTX*1N5633A	500	DO13	216	JANTX*1N5662A	500	DO13	216
JANTX*1N5634A	500	DO13	216	JANTX*1N5663A	500	DO13	216
JANTX*1N5635A	500	DO13	216	JANTX*1N5664A	500	DO13	216
JANTX*1N5636A	500	DO13	216	JANTX*1N5665A	500	DO13	216
JANTX*1N5637A	500	DO13	216	JANTX*1N5711$	444	DO204	215
JANTX*1N5638A	500	DO13	216	JANTX*1N5712$	445	DO204	215
JANTX*1N5639A	500	DO13	216	JANTX*1N5719$$	443	DO204	215
JANTX*1N5640A	500	DO13	216	JANTX*1N5804	477	AXIAL	215
JANTX*1N5641A	500	DO13	216	JANTX*1N5806	477	AXIAL	215
JANTX*1N5642A	500	DO13	216	JANTX*1N5809	477	AXIAL	215
JANTX*1N5643A	500	DO13	216	JANTX*1N5811	477	AXIAL	215
JANTX*1N5644A	500	DO13	216	JANTX*1N5814**	478	DO4	215
JANTX*1N5645A	500	DO13	216	JANTX*1N5816**	478	DO4	215
JANTX*1N5646A	500	DO13	216	JANTX*1N5907	500	DO13	216
JANTX*1N5647A	500	DO13	216	JANTX*1N6092	519	V503	217
JANTX*1N5648A	500	DO13	216	JANTX*1N6093	520	V503	217
JANTX*1N5649A	500	DO13	216	JANTX*1N6094	521	V503	217
JANTX*1N5650A	500	DO13	216	M19500/519-02	519	⚠	217
JANTX*1N5651A	500	DO13	216	M19500/520-02	520	⚠	217
JANTX*1N5652A	500	DO13	216	M19500/521-02	521	⚠	217
JANTX*4N47	548	TO99	218				
JANTX*4N48	548	TO99	218				
JANTX*4N49	548	TO99	218				

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

**--PARTS OF EITHER POLARITY ARE APPROVED FOR USE.

$--SCHOTTKY BARRIER TYPE.

$$--PIN TYPE.

⚠ --PANEL MOUNT CASE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

FIELD EFFECT MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT mW	VGSS Vdc	VDG Vdc	VDS Vdc	VGS Vdc	VGS (off) Vdc	IG mAdc	IDSS mAdc	vfs MIN / MAX umho	CISS PF
JANTX 2N3330##	378	TO72	300	20	20		20	6	10	1,3	1000 2000	32
JANTX 2N3331##	378	TO72	300	20	20		20	8	10	1,3	1000 2000	32
JANTX*2N3821#	375	TO72	300	50	50	50	50	4	10	.5,25	150 4500	6
JANTX*2N3822#	375	TO72	300	50	50	50	50	6	10	2.,10	3000 6500	6
JANTX*2N3823#	375	TO72	300	30	30	30	30	8	10	4.,20	3500 6500	6
JANTX*2N4856#	385	TO18	360		40	40	40	10	50	50		18
JANTX*2N4857#	385	TO18	360		40	40	40	6	50	20,100		18
JANTX*2N4858#	385	TO18	360		40	40	40	4	50	8.,80		18
JANTX*2N5114##	476	TO18	500	30	30	30	30	10	50	30,90		25
JANTX*2N5115##	476	TO18	500	30	30	30	30	6	50	15,60		25
JANTX*2N5116##	476	TO18	500	30	30	30	30	4	50	5,25		27

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--N CHANNEL
##--P CHANNEL

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

UNIJUNCTION MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT mW	Ie mA(rms)	VB2E Vdc	RBBO MIN OHMS	RBBO MAX OHMS	n MIN	n MAX	IB2(MOD) MIN mAdc
JANTX*2N4948	388	TO18	360	50	30	4000	1200	.55	.82	12
JANTX*2N6137**	493	TO18	300	300	40					
JANTX*2N6138**	493	TO18	300	300	100					

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--PROGRAMABLE UNIJUNCTION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

DUAL MIL-S-19500 QPL- 19500

TYPE PART NO.	SPEC	OUT DWG	PT ONE mW	PT BOTH mW	IC mAdc	VBR CBO Vdc	VBR CEO Vdc	VBR EBO Vdc	hFE MIN / MAX	hFE1 hFE2	VBE1 VBE2 mVdc	Cobo (PF)	ft MHz MIN / MAX
JANTX*2N2060	270	T077	540	600	500	100	60	7	30 90	.9-1.1	5	15	60 500
JANTX*2N2920	355	T077	300	500	30	70	60	6	150	.9-1.1	3	5	60 400
JANTX*2N3810	336	T077	500	600	50	60	60	5	150 450	.9-1.1	3	5	100 500
JANTX*2N3811	336	T077	500	600	50	60	60	5	300 900	.9-1.1	3	5	100 500
JANTX*2N4854**	421	T077	300	600	600	60	40	5	100 300			8	200 800

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--COMPLEMENTARY NPN/PNP

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

HIGH FREQUENCY MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT@ TA=25°C mW	POUT MIN MAX	POUT PIN W	POUT f W	POUT n MHz	VBR CBO %	VBR CEO	VBR EBO	hFE@ MIN MAX	IC mAdc	ft MHZ MIN
JANTX*2N918#	301	TO72	200	.030				30	15	3	20 200	3	600
JANTX*2N2857#	343	TO72	200					30	15	3	30 150	3	1000 1900
JANTX*2N3019#S	391	TO5	800					140	80	7	100 300	150	100 400
JANTX*2N3375#	341	TO212	2600	3 6	1.00	400	40	65	40	4	15 150	150	350
JANTX*2N3866#	398	TO39	1000	1 2	.15	400	45	60	30	3.5	15 200	50	500 1600
JANTX*2N4957##	426	TO72	200					30	30	3	30 150	5	1200 3600
JANTX*2N5109#	453	TO39	1000					40	20	3	40 150	50	1200 2200

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--NPN
##--PNP

U.S. GOVERNMENT PRINTING OFFICE: 1985 - 505-038/22620

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.