GGG-A-891a
AMENDMENT—3
December 26, 1963

SUPERSEDING
Interim Amendment—2,
August 1, 1962 and
Amendment—1,
May 31, 1957

FEDERAL SPECIFICATION

AWLS

This amendment, which forms a part of Federal Specification GGG-A-891a, dated June 3, 1954, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 2.1: Add the following specifications and standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

MIL-H-15424—Hand Tools; Packaging of.

MIL-STD-129—Marking for Shipment and Storage.

Page 6, paragraph 3.11.6.1: Delete and substitute the following:

3.11.6.1 *Needles.* Each awl shall be furnished with three needles having diamond-shaped points. One needle shall have a curved point for surface sewing and the other two shall be straight needles. The curved, and one straight needle shall be 2-1/8 inches ± 1/8 inch in length. The other straight needle shall be 1-3/4 inches ± 1/8 in length. The needles shall conform to the test requirements of 4.5.1.

Page 6, paragraph 3.11.6.2.1: After the last sentence add: "A steel ferrule shall be secured to the small end of the wood handle. The ferrule shall have four holes; three shall match the holes in the handle provided for the needles, and the other shall match the thread slot. Needle holes shall be sufficiently deep to prevent contact between the needles and the chuck when tightened into place.

Pages 8 and 9, paragraphs 4.1 through 4.4, and tables II and III: Delete and substitute:

4.1 Inspection responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used were examined and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

tested to determine compliance with requirements of this specification. Examinations and tests applicable to subsidiary specifications and standards shall be performed in accordance with the requirements of the referenced specifications and standards to the extent specified in the contract or order.

4.3 Inspection of the end item.

4.3.1 *Examination of the end item.* Examination of the end item shall be in accordance with the classification of defects as specified in table II. The lot size shall be expressed in units of awls or component parts for the purpose of determining the sample size in accordance with MIL-STD-105. The sample unit shall be one completely fabricated awl or component part. The inspection level shall be level S-3 using an acceptable quality level (AQL) of 1.5 for major defects and 4.0 for total defects, expressed in defects per hundred units.

TABLE II.—*Examination for visual characteristics*

Examine	Defect	Major	Minor
Design	Any characteristic not in accordance with specified requirements	X	
Finish	Indication of rust .	X	
	Scratched or marred		X
	Handle not coated as specified	X	
	Touch-up not neat .		X
	Finish tacky (not completely dry) ..		X
Construction and workmanship	Part missing or not specified type or size	X	
	Fractured, split, bowed, malformed or otherwise impaired	X	
	Sharp burr or sliver	X	
	Operation omitted or not properly performed	X	
	Functioning component that requires abnormal force to operate	X	
Construction and workmanship (cont'd)	Blades and needles not properly polished	X	
	Blades and needles not sharpened as specified	X	
	Not connected or joined as specified or poorly accomplished	X	
Marking	Missing, illegible or otherwise incorrect		X

4.3.2 *Dimensional examination.* Inspection shall be made for compliance with dimensions specified in applicable paragraphs. Any deviation therefrom shall constitute a defect. The inspection level shall be level II using an acceptable quality level (AQL) of 1.5 defects per hundred units.

4.3.3 *Testing of end item.* Testing shall be performed on each sample unit for characteristics specified in 4.5 through 4.5.3 as applicable. The inspection level shall be level S-3 using an AQL of 2.5 defects per hundred units.

4.4 Inspection of preparation for delivery. Inspection to determine compliance with the preparation for delivery requirements shall be accomplished in accordance with MIL-H-15424.

Page 9, paragraph 4.6: Delete.

Pages 9 and 10, sections 5 and 7: Delete in their entirety and substitute:

5. PREPARATION FOR DELIVERY

(Civil agencies should refer to Fed. Std. No. 102 for definitions and applications of the various levels of packaging and packing.)

5.1 Preservation, packaging, and packing shall be in accordance with the applicable requirements of MIL-H-15424 for awl, scratch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

5.2 Marking.

5.2.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 *Military agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Page 10, paragraph 6.4: Delete and substitute:

6.4 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Tools, not otherwise indexed by name.
Carload minimum weight 30,000 pounds.

Motor:

Tools, hand, other than power.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY CUSTODIANS:

Army—GL

Navy—Ships

Air Force

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.