INTERIM AMENDMENT
TO
FEDERAL SPECIFICATION

PUNCH AND DIE, KNOCKOUT

This Interim Amendment was developed by the U. S. Army Natick Laboratories (GL), Natick, Massachusetts, based on currently available technical information. This Interim Amendment has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force. It is recommended that Federal Agencies use it in procurement. The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-P-836 dated December 8, 1954 and Amendment 1, dated February 16, 1959.

Pages 5 and 6, paragraphs 4.1 through 4.3 and 4.5, including tableV—Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL-STD-105, except where otherwise indicated herein.

4.2.1 *Inspection of materials and components.* In accordance with 4.1, above, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2.2 *Inspection of the end item.* Representative samples of punches and dies shall be examined to determine compliance with this specification. A lot shall consist of punches and dies of the same type and class. The sample unit shall be one completely fabricated punch and die.

4.2.2.1 *Visual examination of the end item.* Visual examination of the end item shall be made for the defects set forth below. The inspection level shall be level I with an acceptable quality level (AQL) of 1.5 defects, expressed in terms of defects per hundred units.

Defect	*Examine*
Design	Type and class not as specified.
Construction and workmanship	Tool incomplete; component parts missing or improperly assembled.
	Evidence of sticking, binding, or excessive looseness.
	Cutting edge of punch not machined or ground properly.
	Top and bottom surfaces of die not machined smoothly.

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

Defect	*Examine*
	Drive screw not machined to required accuracy resulting in improper alignment of punch with the die (see 3.7.3).
	Operation omitted or not properly performed.
	Cracked, malformed, deep pits, *flakes or evidence of rust.*
	Drive screw head not flanged.
	Threads stripped, torn, cracked, crossed, drunken, or not perfect full threads.
	Center hole of die not smoothly machined.
Marking	Missing, incomplete, not as specified, or not readily determined or permanent.

4.2.2.2 *Dimensional examination of the end item.* Examination of the end item shall be made to determine compliance with the dimensional requirements specified in applicable paragraphs and tables. Any dimension not in accordance with requirements shall constitute a defect. The inspection level shall be level L4 with an acceptable quality level of 4.0 defects, expressed in terms of defects per hundred units.

4.2.3 *Sampling for tests.* Tests shall be performed on each sample unit in accordance with section 4.4 to determine conformance to applicable paragraphs of section 3. The inspection level shall be level L4 with an acceptable quality level (AQL) of 1.5 defects, expressed in terms of defects per hundred units for the tests specified in 4.4.1 and 4.4.3. For the tests specified in 4.4.2, the sample size shall be three drive screws from each lot. Any failure to meet the tensile strength requirements shall be cause for rejection of the lot represented by the samples. For hardness and tensile strength purposes, a lot shall consist of items heat treated as a batch under the same process and temperature control.

4.2.3.1 *Inspection of preparation for delivery.* Inspection to determine compliance with preparation for delivery requirements shall be accomplished in accordance with Specification MIL–H–15424."

Page 6, paragraph 4.4.1.1—Delete the words, "taken in accordance with table V."

Page 6, paragraph 4.4.1.2—Delete the words, "taken by the Government inspector in accordance with table V."

Page 6, paragraph 4.4.2—Delete the words, "taken in accordance with 4.1.3.2."

Page 6, paragraph 4.4.3—Delete the words,, "selected in accordance with 4.1.3.2."

Page 6, paragraph 6.1, (d)—Delete and substitute:

"(d) Level of preservation, packaging, and packing required (see section 5 and 7.2.3)."

Page 7, paragraph 6.3—Delete "Truckload weight 30,000 pounds" and substitute: "Truckload minimum weight (W) 30.2 (W), subject to Rule 115, National Motor Freight Classification."

Page 7, paragraph 7.2.1—Delete reference to "MIL–P–15424" in its entirety and substitute: "MIL–H–15424—Hand Tools, Packaging of".

Page 7, paragraph 7.2.2—To end of sentence add "as practicable".

Page 7, paragraph 7.2.3, line 3—After "marked" insert "for the level specified (see 6.1)".

Military custodians:
Army—GL
Navy—Ships
Air Force—MOA

Project No. 5110–0152

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.