INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

RULES, MEASURING

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification GGG-R-791F, dated April 5, 1967.

PAGE 2

Paragraph 2.1, insert after first sentence:

"Federal Specification:

PPP-P-40 - Packaging and Packing of Hand Tools."

Paragraph 2.1, "Federal Standard:" Delete in its entirety.

Paragraph 2.1, "Military Specification:" Delete in its entirety.

Paragraph 2.1, under "Military Standards:" Delete "MIL-STD-129 - Marking for Shipment and Storage."

Paragraph 3.2: Add to first sentence:

"and shall appear in a distinctive manner so as to be readily legible under all service conditions."

Paragraph 3.2: Add after last sentence:

"The maximum variation in width between like types of graduations and in the individual graduation shall be such that the maximum width shall not exceed the minimum width by more than 35 percent of the minimum width. Graduations shall extend to the reading edge of the rule."

PAGE 5

Paragraph 3.7.1.1: Insert after ninth sentence:

"The metal joint plates and strike plates shall be free of hazardous sharp edges and burrs."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

PAGE 6

Paragraph 3.7.2.1: Add after last sentence:

"Rules shall hold rigid in the extended position when supported edgewise between the third and fourth joints from the end of 6-foot rules and between the first joint and end of 3-foot rules. The diametrical play at each joint shall not result in a total lengthwise movement of more than 0.020 inch for 3-foot rules and 0.040 inch for 6-foot rules."

Paragraph 3.7.3.1, second sentence: After "brass" insert "or brass plated".

Paragraph 3.7.3.1: Insert between the second and third sentences:

"Rules shall hold rigid in the extended position when supported edgewise between the third and fourth joints from either end and shall not stretch more than 1/16 inch from its original length. The joints shall be free of hazardous sharp edges and burrs."

PAGE 7

Paragraph 3.8.1, sixth sentence: Before "subdivisions" insert "except for rules having numbers 1, 10, and 12 graduations,".

PAGE 9

Paragraph 3.8.1.1: Delete third sentence.

Paragraph 3.8.1.3.1, first sentence: Delete "the overall length of rules 24- and 36-inch lengths shall not vary more than plus 0.006 and minus 0.003 inch;" and substitute "the overall length of 24-inch rules shall not vary more than +0.006 and -0.003 inch; the overall length of 36-inch rules shall not vary more than -0.007 and -0.004 inch;".

Paragraph 3.8.1.4: Delete and substitute the following:

"3.8.1.4 Finish. Rules shall have a chromeplated, dull satin (nonglare) finish. Edges shall be ground, and may be with or without plating. Rule graduations and figures shall be furnished with black fill. Rules shall have a coating of oil or grease suitable for preventing corrosion in storage without affecting the material coated."

PAGE 14

Paragraph 3.12.3, first sentence: Delete "the same" and substitute "one". Add "width and depth of graduations shall be in accordance with 3.8.1."

PAGE 15

Paragraph 3.13.1.3, second sentence: After "scale" insert "error".

PAGE 16

Paragraph 3.14.2, third sentence: End sentence with "hot metals." and start fourth sentence with "As specified".

Paragraph 3.14.2, end of paragraph: Delete "as specified (see 6.1)."

PAGE 18

Add the following new paragraph:

"4.4.3.4 Looseness of joints type III, classes 2 and 3. The rule shall be suspended from one end and a 5-pound weight attached to the other end for a period of 1 minute to determine conformance with 3.7.2.1 and 3.7.2.4, or 3.7.3.1 and 3.7.3.4, as applicable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

PAGE 18 (CON.)

Paragraph 4.5: Delete and substitute the following:

"4.5 Inspection of preparation for delivery. An inspection shall be made to determine that the preservation, packaging, packing, and marking comply with the requirements of PPP-P-40."

TABLE XII: Delete in its entirety.

Section 5: Delete present section and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with PPP-P-40. The level of preservation, packaging, packing, and marking shall be A, B, or C, as specified (see 6.1)."

PAGE 19

Paragraph 6.1, (l): Delete in its entirety.

Paragraph 6.1, (m): Delete and substitute:

"(m) Kind of special finish, if required (see 3.11.2.3 and 3.12.5) or if chrome finish is required (see 3.12.5)."

Paragraph 6.2: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.