GGG-S-001333A (GSA-PSS)
October 16, 1975
SUPERSEDING
GGG-S-001333 (GSA-PSS)
January 3, 1969

INTERIM FEDERAL SPECIFICATION

SCRAPER AND SQUEEGEE, VEHICLE WINDOW

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1. Scope.. This specification covers requirements for a heavy duty ice scraper and window squeegee designed to remove ice, snow, frost or water from vehicular window glass.

1.2 Classification. This scraper-squeegee shall be one size and style.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-1183	-	Plastic molding material, Acrylonitrile-Butadiene-Styrene (ABS), Rigid.
QQ-C-320	-	Chromium Plating (Electrodeposited).
QQ-P-416	-	Plating, Cadmium (Electrodeposited).
QQ-Z-325	-	Zinc Coating, Electrodeposted, Requirements for.
TT-W-572	-	Wood Preservative; Water Repellent.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-665	-	Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676	-	Boxes; Setup.

Federal Standards:

Fed. Std. No. 123	-	Marking for Shipment (Civil Agencies).
Fed. Std. No. 601	-	Rubber: Sampling and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1363 - Measurement of Wood Moisture Content.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Standards For Aluminum Mill Products.

(Application for copies should be addressed to The Aluminum Association, 420 Lexington Avenue, New York, NY 10017.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.1), before production is commenced, a sample scraper-squeegee covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacturer of the production items.

3.2 Design. The finished scraper-squeegee shall be designed to remove ice, snow, frost or water from vehicular window glass.

3.3 Materials. Materials shall conform to the referenced specifications and requirements specified herein. Where materials are not definitely specified they shall be of quality and chemical composition normally used in the best commercial practice for the service required.

3.3.1 Wood. Wood for handles shall be thoroughly seasoned, clear, close-grained, and straight-grained wood, such as beech, birch, maple, ash or southern yellow pine. The wood shall be thoroughly seasoned so that when tested in accordance with MIL-STD-1363, it shall have a moisture content not more than 12 percent.

3.3.2 Aluminum. Frames fabricated of aluminum shall conform to a 6000 series alloy specified in the Standards for Aluminum Mill Products. Other aluminum components shall be of alloys normally used by the contractor in the best commercial practice.

3.3.3 Steel. The steel shall be a high grade of uniform quality and of sufficient thickness to prevent deformation in service. If not inherently corrosion resistant, the metal shall be coated with either cadmium plate conforming to class 1, type I of QQ-P-416; or zinc plate, conforming to type I, class 2 of QQ-Z-325. There shall be no evidence of corrosion when tested as specified in 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

3.3.4 Rubber. The rubber shall be natural or synthetic.

3.3.5 Plastic. The plastic parts of the scraper-squeegee shall exceed the property values established for type V Plastic Molding Material, Acrylonitrile-Butadiene-Styrene (ABS) Compound, Rigid, of L-P-1183, and meet or exceed the properties shown in table I. All of the plastic material shall be virgin ABS compound. Clean, unburned plastic material in the form of imperfect parts, or other scrap of the same composition as the virgin material produced in forming or finishing operations may be reground and mixed with the virgin material.

TABLE I

Property	Temperature Degrees F.	Specifications	Unit
Izod Impact (1/8" Bar Notched)	-40	2.0	ft-lbs.
Tensile Strength (1/8" thick)	-40	9200	P.S.I.
Tensile Modulus	73	320000	P.S.I.
Flexural Modulus	-40	15200	P.S.I.
Compressive Strength	73	8000	P.S.I.
Deformation under load (2000 P.S.I. - 24 hours)	122	0.52	%
Hardness	73	101	Rockwell R SCALE
Water absorption		.43	%

3.4 Details of components.

3.4.1 Handle. The handle shall be made from the wood specified in 3.3.1. It shall be uniformally cylindrical in shape and not less than 23 inches in length. It shall be not less than 3/4 inch in diameter, be free from warp greater than 1/8 inch, rounded at the gripping end and may be undercut at the opposite end for fitting into the ferrule or yoke. Evidence of decay, knots, checks, splits or slivers is not permitted.

3.4.1.1 Finish. After all machining, the handles shall be sanded smooth and finished with two coats of wax, transparent lacquer, shelac, varnish or other clear organic finish. The finished handles shall be water resistant in accordance with TT-W-572.

3.4.2 Frame. At the option of the contractor, the frame shall be made of extruded aluminum, molded plastic or formed steel, conforming to 3.3.2, 3.3.3 or 3.3.5. The frames shall be of one piece construction. All frames shall have a channel in which to mount the rubber squeegee blade. All components shall be of sufficient thickness and temper to prevent deformation in service. Metal frames shall be constructed so as to afford adequate support for the mounting of the scraper blade, and the metal frames shall be approximately 1/4 inch less than the length of the rubber and plastic blades. Plastic frames shall be constructed so as to include in their configuration one edge as an ice scraper blade. The plastic frame shall be 1/4 inch less than the length of the rubber blade. The plastic blade portion of the plastic frame shall be the same length as the frame.

3.4.3 Ferrule. The ferrule and or yoke shall be fabricated of the material specified in 3.3.2, 3.3.3 or 3.3.5. Attachment to the frame and handle shall remain fast when tested as specified in 4.4.4 and the alloy of metal or physical property of the plastic and the gage of the material shall be that which is sufficient to prevent fracturing or deformation of the component. Ferrules for metal frames shall be separate components which are fastened to the frame and handle. Ferrules for plastic frames shall be an integral part of the plastic frame and shall be fastened to the handle.

3.4.4 Rubber blade. The rubber blade shall be a minimum of 5-1/2 inches long and 3/4 inch wide and shall conform to the material specified in 3.3.4. The blade shall contain no coloring agent which will stain, bleed or run, when tested as specified in 4.4.2.1. The blade shall not become hard or soft when tested as specified in 4.4.2.2 and shall show no signs of cracking or breaking and shall return approximately to its original position when tested as specified in 4.4.2.3. There shall be no visible evidence of surface water or streaks on the glass plate when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

3.4.5 Plastic blades. Plastic blades for metal frames shall be a minimum of 5-1/2 inches long and 3/4 inch wide and conform to the material specified in 3.3.5. The underside of the blade shall have at least eleven cutting teeth to effect points of high unit pressure for scoring and breaking up hard packed snow, ice or frost. Scraper teeth shall have not less than 3/32 inch effective cutting depth when measured as indicated in figure 2. The scraper blade when positioned against a flat surface in the way generally used for scraping the window surface, shall be of such construction and straightness, so that a feeler gage of no greater thickness than 0.01 inch will fit between the edge of the scraper blade and the flat surface, at any point. Plastic blades that are integral to the plastic frame configuration shall conform to the description in 3.4.2 and be so formed as to include all of the material, and performance and design features specified for the plastic blades for metal frames described elsewhere in this paragraph, with the exception of length.

3.5 Marking for identification. Each scraper-squeegee shall be die marked in the frame with the name of the manufacturer in letters not less than 1/8 inch in height or a trademark of such known character as to make the source of manufacturer easily determined. Each shall also have die marked in the frame in the largest practical letters, not less than 1/8 inch in height, the words, "U.S. GOVERNMENT PROPERTY".

3.6 Workmanship. The scraper-squeegee shall conform to the quality and grade of product established by this specification and shall be free of defects which may affect durability, serviceability or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. The preproduction sample shall be examined for defects in 4.3.2.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactuerd, tested and inspected to insure conformance with the requirements of this specification.

4.3.2 End item inspection. Examination of the end item shall be in accordance with the classification of defects, inspection levels and acceptable quality levels set forth below. The lot size for the purpose of determining the sample size in accordance with MIL-STD-105 shall be all scraper-squeegee combinations submitted for inspection and delivery at one time. The sample unit for this inspection shall be one scraper squeegee.

4.3.2.1 Visual examination. Each sample unit shall be examined for the applicable visual defects listed in table II. Inspection level shall be S-3, and the acceptable quality level (AQL) shall be 4.0 defects per hundred units.

TABLE II. Visual examination

Examine	Defects
Design	Not as specified.
Frame, ferrule and/or yoke,	Dimensions not as specified. Rough or sharp edge, or burr or sliver which may cause injury.
Fastners	Rivets not securely set or clinched. Not corrosion-resistant coated as applicable. Malformed or fractured. Ferrule and/or yoke not securely fastened to frame or handle. Evidence of rust or corrosion.
Handle	Dimensions not as specified. Not clear hardwood.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:43Z
Check the source to verify that this is the currentversion before use.

TABLE II. Visual examination (con.)

Examine	Defects
Handle	Wet or tacky film area. Decay, knots, checks, splits, slivers, roughness. Warp or bow more than 1/8 inch when handle is rotated on flat surface.
Rubber Blade	Dimensions not as specified. Not securely mounted in frame channel.
Plastic Frame/blade	Dimensions not as specified. Less than eleven scoring teeth. Teeth have less than specified effective scoring depth. Not securely fastened to frame as applicable. Dirt or foreign matter imbedded in finish.

4.3.3 Examination of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking requirements comply with section 5.

4.3.4 Testing the end item. The end item shall be tested for applicable characteristics, as specified in 4.4. Lot size shall be the number of scraper-squeegees submitted for acceptance. Sample unit shall be one scraper-squeegee. Not more than one scraper-squeegee shall be taken from the same package.

4.4 Tests. Any scraper-squeegee failing to conform to the following test shall be considered defective and the entire lot shall be rejected.

4.4.1 Wiping test for squeegee. A glass window pane, at least 2 feet square, positioned at an angle of 45 degrees, shall be washed with clear, clean water. With the blade of the squeegee wet, and while the pane is still wet, the pane shall be wiped with not more than 2 downward strokes of the squeegee in the same area. The pane shall then be examined to determine compliance with 3.4.4.

4.4.2 Test for rubber blades.

4.4.2.1 Soaking test. A blade shall be soaked in clear, clean water at 170 degrees ± 10 degrees F., for a period of not less than 15 minutes. The blade shall then be removed and examined to determine compliance with 3.4.4.

4.4.2.2 Oxygen pressure test. Test shall be conducted as described in method 711 of Fed. Std. No. 601. The blade shall then be examined to determine compliance with 3.4.4.

4.4.2.3 Bending test. After the oxygen pressure test, each rubber blade shall be bent 90 degrees ± 10 degrees, on each side of its normal position not less than 25 times. The blade shall then be removed and examined to determine compliance with 3.4.4.

4.4.3 Corrosion test. Complete parts when fabricated of ferrous metal shall be placed in a boiling 10 percent (by weight) aqueous solution of sodium chloride for a period not less than 15 minutes. The part upon being removed form the solution shall be immediately immersed for at least one hour in 10 percent (by weight) aqueous solution of sodium chloride at room temperature of 68 to 85 degrees F. The part shall then be removed from this solution and without having the adhering liquid wiped off, allowed to dry for at least 24 hours at room temperature (68 to 85 degrees F.) and then wiped free of any residue and examined for compliance with 3.3.3.

4.4.4 Handle, frame and ferrule weight parting test. A hole not greater than 1/8 inch in diameter shall be drilled through the wood handle on an axis parallel to the frame length and approximately one inch from the handle end. A cord 24 inches in length shall be inserted into the hole and fastened end to end. this fastened cord shall result in a loop of approximately 24 inches in circumference and shall be of sufficient strength to withstand the requirements of this test. With the cord loop in place, the scraper-squeegee shall be placed on parallel platforms at least 5 feet from the floor so that the scraper-squeegee will be resting on the back of the frame and the handle is hanging freely toward the floor. A weight of at least 20 lbs. shall be attached to the cord by a ring and allowed to fall freely from a point next to the end of the wooden handle. The weight shall not be allowed to come in contact with the floor. This test shall be repeated three times, after which the scraper-squeegee shall be examined to insure compliance with 3.4.3.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A and B. Each item shall be disassembled to a minimum cubage and packaged in a box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The box shall be closed to prevent accidental spillage of the contents.

5.1.2 Level C. The item shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The item packaged as specified in 5.1 and in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant. The box shall be closed, water-proofed, and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Twenty-four unit packages shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The item shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to markings required by the contract or order the unit and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129 as specified (see 6.2).

6. NOTES

6.1 Intended use. This scraper and squeegee is intended to be used to remove ice, snow, frost or water from vehicular window glass.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) When preproduction sample is required (see 3.1).
(c) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(d) Selection of applicable marking requirements (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.