INTERIM FEDERAL SPECIFICATION

SWATTER, FLY

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 This specification covers the requirements for fly swatters.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the titles of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Fly swatters covered by this specification shall be of one type.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

Federal Specifications:
L-P-390 - Plastic, Moulding Material, Polyethylene, low or medium density.
L-P-398 - Plastic Moulding Material, Styrenebutadiene.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set Up, Paperboard.
QQ-W-461 - Wire, Steel, Carbon, SAE 1008 or 1010.

Federal Standard:
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:
MIL-P-116 - Preservation, Method of

Military Standards:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS.

3.1 Materials. Materials shall be as specified herein. Materials not definitely specified shall be of the quality regularly used by the manufacturer in his standard commercial product.

3.2 Designs. Unless otherwise specified (see 6.2), fly swatters covered by this specification shall be the manufacturer's standard design and shall consist of a blade and handle combination meeting the requirements as specified.

3.3 Construction. Fly swatter blades shall be attached to the handle in such a manner as to not separate under a test load of 25 pounds pull (see 4.4.2).

3.3.1 Blades. Blades shall be fabricated from insect screening type wire mesh or polyethylene plastic conforming to L-P-390 type I.

3.3.1.1 Blades. Blades may be of any style provided they stay within the dimensions specified herein. Blades shall not exceed 6-3/4 inches in length or 4-3/4 inches in width. The blades shall cover an area of not less than 22 or more than 33 square inches. Metal blades shall have the edges bound to prevent fraying and raveling when used.

3.3.2 Handles. Handles shall be fabricated from No. 13 gauge wire (.0915 dia.), SAE 1008 or 1010 steel wire conforming to QQ-W-460, or plastic material conforming to L-P-398, type II, type III, or type IV.

3.3.2.1 Length. Handles shall not be less than 12 inches or more than 18 inches in length, measured from the rear of the blade at the point of attachment to the handle.

3.3.3 Finish. Metal parts shall be copper, zinc plated, or painted, in accordance with the manufacturer's commercial practice.

3.3.3.1 Metal parts. Wire mesh blades and wire handles shall be treated to resist normal atmospheric corrosion by any suitable process.

3.3.3.2 Color. Unless otherwise specified (see 6.2), the color shall be at the option of the manufacturer.

3.4 Identification. Each fly swatter shall be plainly marked with the manufacturer's designation and with his name or trademark of such known character that the source of manufacture may readily be determined.

3.5 Workmanship. All parts shall be smooth and free from flash, rough edges or any irregularities which may affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for lot inspection.

4.2.1 Inspection lot. All fly swatters offered for delivery at one time shall be considered a lot for the purpose of acceptance, inspection and test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling. Sampling for examination and test. A random sample of fly swatters shall be taken by the inspector from each inspection lot of material offered, with lot acceptance based on inspection level II, with an acceptable quality level (AQL) of 6.5 in accordance with MIL-STD-105.

4.3 Visual inspection. Fly swatters selected in accordance with MIL-STD-105 shall be visually inspected for the following: blade and handle not properly joined together (see 3.3), blade length (see 3.3.11), handle length (see 3.3.2.1), and workmanship (see 3.5).

4.4 Blade and handle separation test.

4.4.1 Apparatus. Fly swatters shall be tested with a Scott Tensile Tester or any other device which will conduct the test to meet the requirements as herein specified.

4.4.2 Method. The blade shall be clamped between two steel plates in a position to allow the head joints to protrude beyond the edge of the steel clamp. The spring scale hook of the Scott Tensile Tester or other device used shall be inserted in the wire loop of the handle or hole in the hand grip end of the plastic handle. Tension force shall be exerted until the load specified in 3.3 is reached. Separation of the blade and handle below the specified load shall constitute failure of this test.

4.5 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defect shall be scored in accordance with table I. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall give the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Table I. Classification of preparation for delivery defects.

Examine	Defect
Markings	Omitted, incorrect, illegible, location.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose straping, inadequate stapling. Distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.).

5.1.1 Level A. The swatters in quantities as specified (see 6.2), shall be packaged in accordance with method IC-2 of MIL-P-116.

5.1.2 Level B. Twelve swatters shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665 or PPP-B-676.

5.1.3 Level C. The swatters shall be packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving activity for immediate use. The suppliers commercial practice will be acceptable when it fulfills the above requirements.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The swatters shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant. The boxes shall be closed and strapped in accordance with the appendix to the specification.

5.2.2 Level B. Twenty-four unit packages of swatters shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The swatters shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Standard packaging (civil agencies). The standard packaging for civil agencies shall be as specified in 5.1.2 and 5.2.2, respectively.

5.4 Marking.

5.4.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The fly swatters covered by this specification are used to kill flies, mosquitos, roaches or other crawling insects.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number and date of specification.
(b) When all metal, all plastic, or combination metal and plastic blade and handle are required (see 3.2).
(c) Color of finish required (see 3.3.3.2).
(d) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.3 Standard pack for civil agencies. The standard pack requirements in 5.3 are intended for use in procurements of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from supplier to a domestic warehouse, supply depot or intermediate storage point for temporary storage, subsequent issue or shipment to eventual user.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.