AMENDMENT TO

INTERIM FEDERAL SPECIFICATION

TWEEZERS, CRAFTSMAN'S

This amendment was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification GGG-T-00870b(GSA-FSS), dated September 15, 1966.

PAGE 1

Under type I, classes 1 and 2, design B, add: "Style 3. - Slim point.".

PAGE 3

Paragraph 3.7: Delete fourth sentence reading: "The cutting edges of type VI tweezers shall be checked for hardness by file method (see 4.4.1.1)."

Table I, column 2: Under "Overall Width" delete "(Min.)" and substitute: "$\pm$ 1/16".

PAGE 4

Table II: Delete and substitute:

Table II. - Type I, classes 1 and 2, designs A and B, style 3, slim point.

Overall Length $\pm$ 1/4 A	Overall Width $\pm$ 1/16 B	Length of Tip $\pm$ 1/8 C	Jaw Opening $\pm$ 3/16 - 1/16	E		F	
				Min.	Max.	Min.	Max.
Inches	Inch	Inches	Inch	Inch	Inch	Inch	Inch
4-1/4	5/16	1	5/16	0.020	0.030	0.030	0.050
6	3/8	2-1/2	1/4	.070	.080	.040	.050
8	3/8	2-5/8	1/4	.070	.085	.040	.050

PAGE 5

Table III, column 2: Under "Overall Width" delete "(Min.)" and substitute "$\pm$ 1/16".

Table IV, column 2: Under "Overall Width" delete "(Min.)" and substitute "$\pm$ 1/8".

PAGE 7

Table IX, columns 1 and 2: Delete and substitute:

Nominal Size	Overall Length $\pm$ 1/4
Inches	Inches
3-5/8	3-5/8

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

PAGE 8

Table X, column 3: Under "B" delete "Min." and substitute "≤ 1/16".

PAGE 10

Paragraph 4.4.1.1: Delete and substitute:

4.4.1.1 Cutting test for type VI tweezers. Each sample tweezer shall be tested for performance by making a minimum of 10 cuts of annealed solid copper wire equivalent to American Wire Gage No. 24 (0.0201). After testing, the tweezers shall show no signs of breakage or deformation of jaws.

PAGE 12

Delete section 5 and substitute:

5. PREPARATION FOR DELIVERY

5.1 Levels A, B, and C. Tweezers shall be preserved, packaged and packed for each level of protection in accordance with MIL-H-15424 (see 6.1).

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.