FEDERAL SPECIFICATION

SAW, CIRCULAR, TABLE TYPE, WOODWORKING, SINGLE TILTING ARBOR, FLOOR MOUNTED

This amendment, which forms a part of Federal Specification 00-S-236C, dated March 31, 1975, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

2.1, Under "Military Standards" delete MIL-STD-130 and its title.

PAGE 7

3.3.16, lines 2 and 3, delete "identifying the machine in accordance with MIL-STD-130".

PAGE 9

3.4.1.3, Delete and substitute:

3.4.1.3 Elevating and tilting mechanisms. The saw shall have elevating and tilting mechanisms which will support and provide manual control for depth and angle of the saw blade cutting through workpieces hand-fed across the table. The elevating mechanism shall provide vertical travel of the saw blade to the cutting depth specified in table I. The tilting mechanism shall provide a tilt range for the saw blade from vertical position, 90 degrees to the table workpiece support surface, through 45 degrees tilt. The tilting and elevating mechanism shall be so constructed that when the saw blade is manually positioned, by a handwheel control that the mechanism secures the blade in that position through sawing operations. The manual control handwheel shall easily adjust the elevating mechanism and the tilting mechanism, or a separate handwheel for each function, shall easily actuate elevation and tilting adjustments. The tilting mechanism shall include a graduated scale, in degrees to indicate the degree of saw blade tilt. The scale shall be accurate to plus or minus one degree, corresponding to the angle of saw blade tilt. Each five degrees shall be indicated with a longer scribe mark, and each 15 degrees shall be marked with the numerical value, indicating the degree of blade tilt. The elevating and tilting mechanisms shall have provisions for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

adjustments to maintain component alignment and working tolerances.

PAGE 10

3.4.1.6 Delete and substitute:

3.4.1.6 Miter attachments. Each saw shall be furnished with a miter attachment. The attachment shall consist essentially of a bar that slides in the table slots paralleling the saw blade. The bar shall support a material rest which has swivel capabilities of not less than 45 degrees right and left of the bar. The adjustment device shall securely lock the material rest in any position within the swivel range. The miter attachment shall have a scale graduated in increments not larger than one degree, that indicates the angle to the saw blade to which the material rest is swiveled. Each five degrees shall be indicated with a longer scribe mark, and each 15 degrees shall be marked with the numerical value indicating fence angle to the saw blade center line. The graduations shall have an accuracy within plus or minus one degree. With the material rest secured in adjustment for producing angular and square cuts, the miter attachment shall allow the operator to manually feed workpieces easily into the saw blade.

MILITARY CUSTODIANS:

Army - ME
Navy - SH
Air Force - 99

Review Activities:

Army - ME
Navy - YD

User Activities:

Army - AL

Preparing Activity:

DLA - IP

CIVIL AGENCIES COORDINATING ACTIVITY:

GSA - FSS

Project Number:

3220-0119

U.S. GOVERNMENT PRINTING OFFICE : 1979 - 281-173/2333

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.