FEDERAL SPECIFICATION

SCRUBBING MACHINE, FLOOR, ELECTRIC
(BATTERY POWERED)

This amendment, which forms a part of Federal Specification OO-S-255A, dated June 24, 1974, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

3.2 - Line 4, delete all after "corrosion resisting material".

PAGE 5

3.11 - Line 3 shall read as follows: "the vacuum producer shall be capable of developing 16 inches of water lift through a 7/8 inch diameter orifice."

PAGE 6

3.13.2 - Line 5, change "12 inches" to "6 inches".

PAGE 9

4.2.3.4 - Delete in its entirety and substitute the following:

"4.2.3.4 End item testing. A pre-production sample or an initial production unit for each size and type shall be tested in accordance with paragraphs 4.3.2.2.1, 4.3.2.2.3 and 4.3.2.2.6. These tests are to be performed only once for each contract except if a design change is initiated or a change of manufacturing location or process, in which case they are to be repeated prior to manufacture of the item. Any nonconformance shall be cause for rejection of the unit. The supplier shall perform tests on production lot units in accordance with paragraphs 4.3.1, 4.3.2.2, 4.3.2.2.2, 4.3.2.2.4 and 4.3.2.2.5. A random sample shall be made in accordance with MIL-STD-105, Inspection level S-3. Any of the machines failing the tests, the lot shall be rejected."

PAGE 10

4.3.2.2.6 - Lines 4 and 5 shall read as follows: "Test voltage shall correspond with the rated voltage on the machine data plate."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.