00-S-256/10A
November 16, 1978
SUPERSEDING
00-S-256/10
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINE, INDUSTRIAL;

OVEREDGE, MACHINE

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for overedge type industrial sewing machine.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type overedge 502 or 503

Class 1 - Light and medium duty

Stitch type overedge 504 or 505

Class 2 - Heavy duty

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Class 1. The class 1, machines shall be provided with a foot lifter. The machine shall operate at not less than 5,000 stitches per minute. The machine shall have a feed A mechanism. The machine shall be capable of producing the required stitch spacing as specified (see 6.2). Arrangements shall be provided for adjusting the width of the trimming bight from 1/8 to 1/4 inch (3 to 6 mm). The machine mounting shall be nonsubmerged and the lubrication for the machine shall be automatic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.2 Class 2. The class 2, machines shall meet all the requirements of class 1 above, except that the machine shall have a feed E mechanism and shall be capable of producing stitch type 504 or 505 and the required number of stitches as specified (see 6.2).

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

6. NOTES

6.1 Intended use. Classes 1 and 2 machines shall be suitable for serging the edges of trousers.

6.2 Ordering data. In addition to the ordering data of 6.2 of the general specification, the purchaser should include the following information:

(a) Title, number and date of this specification.
(b) Stitch type and class machine required (see 1.2).
(c) Specify stitch spacing (see 3.1 and 3.2).
(d) Specify the number of stitches required (see 3.2).

6.3 Deletion data. Styles A and B machine stitching classification designators were deleted in this revision.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-10

U.S. GOVERNMENT PRINTING OFFICE : 1979 - 281-173/2277

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.