OO-S-256/11A
November 16, 1978
SUPERSEDING
OO-S-256/11
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINE, INDUSTRIAL;

BLIND STITCH, MACHINES

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification OO-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for industrial type blind stitch sewing machines.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type 306 (blind, lock stitch)

Class 1 - Low speed (straight and overcasting stitching)

Stitch type 103 (blind, chain stitch)

Class 1 - High speed

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Class 1, stitch type 306. The machine shall be provided with a knee lifter. The machine shall operate up to at least 1,500 stitches per minute with 6 to 10 stitches per inch (3 to 4 stitches/cm). The machine shall have a feed A mechanism. The machine bed shall be a cylinder type with a removable work support plate. The machine shall be nonsubmerged and the machine shall be non-automatically lubricated.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

3.2 Class 1, stitch type 103. The machine shall be provided with a knee lifter. The machine shall operate up to at least 2,400 stitches per minute with 5 to 8 stitches per inch (2 to 3 stitches/cm). The machine shall have a feed J mechanism. The machine bed shall be a cylinder type with a removable work support plate. The machine shall be nonsubmerged and the machine shall be nonautomatically lubricated.

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. Stitch type 301 machines shall be capable of producing straight and overcasting stitches under collars, and bottom of coats. Stitch type 103 machines shall be suitable for blindstitching collars, lapels, facing of coats and overcoats, and bottom of trousers.

6.2 Ordering data. In addition to ordering data of 6.2 of the general specification, the purchaser should include the following information:

(a) Title, number and date of this specification.
(b) Stitch type and class machine required (see 1.2).

6.3 Deletion data. Styles A and B machine stitching classification designators were deleted in this revision.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-11

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.