INCH-POUND

OO-S-256/1A
INT. AMENDMENT-1 (Army-GL)
November 14, 1990

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION SHEET

SEWING MACHINES, INDUSTRIAL; FLATBED,

SINGLE-NEEDLE, MACHINES

This interim amendment was developed by the U.S. Army Natick Research, Development, and Engineering Center (GL), Natick, MA 01760-5017 based upon currently available information. It is recommended that Federal Agencies use it in procurement and forward all recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to OO-S-256H/GEN dated August 5, 1986.

PAGE 1

1.2, under "Stitch type 301 (lock)": Delete Classes 2 and 3 and substitute:

"Class 2 - Light duty
Class 3 - Light-medium duty"

PAGE 2

3.2: Delete and substitute:

"3.2 Class 3, stitch type 301. The machine shall be equipped with reversible type "A" feed with the capability of sewing fabrics that range from light to medium weight such as nylon, cotton duck, synthetics, various coated and laminated fabrics, light to medium weight tapes and webbing, and shall utilize metric needle sizes 80 through 60. The machine shall be suitable for use with sizes A, B, C, D, E and FF thread. The machine shall operate at speeds not less than 2000 or greater than 2200 stitches per minute. The machine shall be non-automatically lubricated. Each machine shall be supplied with a bobbin winder, knee operated presser foot lifter and thread stand. The machine shall be equipped with a horizontal axis oscillating shuttle, central bobbin and link take-up lever. The machine shall be equipped with a push down hand operated

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

reverse feed lever which is spring loaded to normally return to the forward feed position. The mounting shall be fully submerged. The machine feed dog shall have 3 rows of teeth with a minimum of 16 teeth per inch. The stitching shall be a minimum of 5 to an unlimited number of stitches per inch. The stitch length adjustment shall be made with the use of a detent knob or other lock mechanism, numerically marked rotary knob. The machine shall provide a minimum clearance of 0.25 inches under the presser foot. The presser foot shall be the hinged type. The machine shall provide a working space to the right of the needle of 10 inches minimum and 11 inches maximum. The machine shall be 18-3/4 inches by 7 inches."

3.3, line 1: Delete "foot" and substitute "knee".

3.4, line 1: Delete "knee" and substitute "hand or foot".

Third sentence, Delete and substitute: "On an "H" feed machine only, a ten speed motor with inching capacity may be furnished, if the machine head is supplied without a front or center hand wheel."

Custodian

Army - GL

Preparing activity:

Army - GL

Project 3530-A087-01

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.