00-S-256/2A
November 16, 1978
SUPERSEDING
00-S-256/2
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL; FLATBED, TWO-NEEDLE, MACHINES

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for a two-needle, flatbed, industrial sewing machine.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type 301 (lock)

Class 2 - Light and medium duty
Class 3 - Heavy duty

Stitch type 401 (chain or double locked)

Class 4 - Extra heavy duty

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

FSC 3530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Class 2, stitch type 301. The machines shall be provided with a knee lifter. The machine shall operate at not less than 3,200 stitches per minute with 7-15 stitches per inch (2-7 stitches/cm). Working space to the right of the needle shall consist of not less than 10 inches (254 mm) and not greater than 11-1/2 inches (292 mm). The machine shall have a feed G mechanism. The machine shall be nonautomatically lubricated. The mounting shall be fully submerged. The distance between needles shall be as specified (see 6.2).

3.2 Class 3, stitch type 301. The machines shall conform to table I. Feed H or I and the distance between needles shall be as specified (see 6.2). Feed I machine shall be provided with a knee lifter. The machine shall be nonautomatically lubricated, and the mounting shall be fully submerged. The distance shall be as specified (see 6.2). A ten speed motor with inching may be furnished, if the machine head is supplied without a front handwheel.

TABLE I.

Feed	Speed (not less than) stitches per minute	Stitches per inch, (stitches/cm)	Working space, inches (mm) (to the right of the needle)	Table top dimensions width x length, minimum, inches (mm)
H	1,100	3 - 10 (1 - 4)	29 - 3 (737 - 787)	20 x 66 (508 x 1676)
I	3,000	7 - 15 (3 - 6)	9 - 11 (230 - 280)	30 x 46 (762 x 1168)

3.3 Class 4, stitch type 401. The machine shall operate at a space not less than 3,600 stitches per minute with 4-8 stitches per inch (2-3 stitches/cm). Working space at the right of the needle shall consist of not less than 9-1/2 inches (241 mm) and not greater than 11 inches (279 mm). The machine shall have a feed H mechanism. The machine shall be automatically lubricated. The mounting shall be fully submerged. The distance between needles shall be as specified (see 6.2). The table top shall be not less than 20 inches wide by 48 inches long (508 x 1219 mm).

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Stitch type 301, class 2 machines shall be suitable for stitching flags, guidons, light and medium weight cotton shirts, flannel shirts, dresses, jackets, coats, trousers, and work clothing. Stitch type 301, class 3 machines shall be suitable for stitching heavy trousers and work cloths, mackinaws and sheepskin lined coats, and light and medium canvas goods. Stitch type 401, class 4 machines shall be suitable for stitching tents, and tarpaulins.

6.2 Ordering data. In addition to ordering data of the general specification, the purchaser should include the following information, as applicable.

(a) Title, number and date of this specification.
(b) Stitch type and class machine required (see 1.2).
(c) The distance between needles as required (see 3.1, 3.2 and 3.3).
(d) The feed as required (see 3.2).

6.3 Deletion data. Styles A and B stitching designations were deleted in this revision.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-2

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.