INCH-POUND

OO-S-256/3B
November 10, 1992
SUPERSEDING
OO-S-256/3A
INT. AMENDMENT-1 (Army-GL)
November 14, 1990 and
OO-S-256/3A
November 16, 1978

FEDERAL SPECIFICATION SHEET

SEWING MACHINES, INDUSTRIAL; CYLINDER BED, SINGLE-NEEDLE, MACHINES

This specification sheet is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal Agencies.

The complete requirements for procuring the sewing machines described herein shall consist of this document and the latest issue in effect of Specification OO-S-256/GEN.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for a single-needle, cylinder bed, stitch type 301 (lock), industrial sewing machine.

1.2 Classification. The sewing machines shall be of the following classes, as specified (see 6.2).

Class 2 - Heavy duty
Class 3 - Darning
Class 5 - Medium-heavy duty

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3530

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

6-1-9367 - Sewing Machine, Industrial, Darning, Single-Needle, Heavy Duty: Parachute Repair and Fabrication Test Requirements

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-UX, Natick, MA 01760-5017.)

3. REQUIREMENTS

3.1 Class 2. The machine shall be provided with a foot lifter and equipped with a bobbin winder. The diameter of the cylinder bed at the stitching end shall be not more than 2-3/4 inches. The machine shall have a nominal maximum speed of not less than 2900 stitches per minute with 8-20 stitches per inch. Working space to the right of the needle shall consist of not less than 10 inches and not greater than 11-1/2 inches. The machine shall have a type "H" feed mechanism. The machine shall be nonautomatically lubricated, and the mounting shall be nonsubmerged.

3.2 Class 3. The machine shall be suitable for darning and mending all types of medium to heavyweight materials including, cloth, vinyl, leather, canvas, denim, and various coated and laminated materials. It shall be a heavy duty, nonfeeding, single needle, 301 lock stitch machine with a cylinder bed and a hopping presser foot and a vertical access hook. The cylinder bed shall be 2-9/16 $\pm$ 1/16 inches in diameter by 10-1/2 $\pm$ 1/16 inches long. The working space to the right of the needle shall be a minimum of 10 inches. The machine shall be suitable for use with sizes A, B, C, D, and E thread, and for use with sizes 8 to 14, 18 to 20 needles. The machine shall have a nominal maximum speed of 2800 stitches per minute. The clearance under the presser foot shall be a minimum of 3/8 of an inch. The machine shall be manually lubricated. It shall be pedestal mounted with no part of the pedestal submerged. The machine shall be operated to darn and mend all of the details as shown on Drawing 6-1-9367 (see 4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.3 Class 5. The machine shall be capable of operating at a speed of up to 500 stitches per minute. The lower arm at the stitching end shall be at least 1 inch wide by 7/8 inch deep. The machine shall have a type "O" feed mechanism. A working space to the right of the needle of not less than 12 inches and not greater than 19 inches shall be provided. The machine shall be top mounted on a stand. The stand shall have a metal treadle of open grate design mounted between the legs. The machine shall be nonautomatically lubricated and the mounting shall be nonsubmerged. An electric transmitter of not less than 1/4 hp may be used to drive the machine, or when specified (see 6.2) the machine shall be driven by foot power. The belts shall be of the round leather type.

4. QUALITY ASSURANCE PROVISIONS

4.1 First article inspection. In addition to the first article tests specified in the general specification, the class 3 machine shall only be tested in accordance with 3.2. The inability of the machine to perform the stitching detailed on Drawing 6-1-9367 shall constitute a failure of this test.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. The Class 2 machine shall be suitable for stitching cuffs on heavy jackets and trousers, overcoats, leather jackets, and pile or sheepskin lined coats. The Class 3 machine shall be suitable for darning holes in socks, underwear, shirts, work clothing, blankets, sheets, coats, and trousers. The Class 5 machines shall be suitable for boot and shoe repair and other tubular work in leather and fabrics.

6.2 Ordering data. In addition to the ordering data of the general specification, the purchaser should include the following information as applicable.

a. Title, number, and date of this specification sheet.
b. Class machine required (see 1.2).
c. When a foot power drive is required (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activities

Navy - SA, MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
VA-OSS

PREPARING ACTIVITY:

Army - GL

(Project 3530-0093)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.