00-S-256/5A
November 16, 1978
SUPERSEDING
00-S-256/5
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL; ZIGZAG, SINGLE-NEEDLE, MACHINES

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for a single-needle, zigzag type, industrial sewing machine.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type 304 (lock)

Class 1 - Light duty
Class 2 - Medium duty

Stitch type 308 (lock)

Class 1 - Light and medium duty

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

FSC 3530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Classes 1 and 2, stitch type 304. The machine shall be equipped with a bobbin winder, and a knee lifter. The machine shall operate at not less than 2,000 stitches per minute with 0 to 5-1/2 stitches per inch (0 to 2 stitches/cm). Working space to the right of the needle shall consist of not less than 7 inches (178 mm) and not greater than 12 inches (3-5 mm). The machine shall be equipped with a vibrating needle bar. The needle shall vibrate equally on both sides of the center line, and a regulator shall be provided for setting the amount of needle vibration from straight away stitches to a width of 1/4 inch (6 mm). The machine shall have a feed A mechanism. The machine shall be nonautomatically lubricated and the mounting shall be fully submerged. The width of the stitch for class 2 machine shall be 5/16 inch (8 mm).

3.2 Class 1, stitch type 308. The machine shall be provided with a bobbin winder and a knee lifter. The machine shall operate at no less than 1,000 stitches per minute with 0 to 10 stitches per inch (0 to 4 stitches/cm). The machine shall be equipped with a vibrating needle bar. The needle shall vibrate equally on both sides of the center line, and a regulator shall be provided for setting the amount of needle vibration from straight away stitches to a width of 3/8 inch (10 mm). Working space to the right of the needle shall consist of not less than 10-3/8 inches (264 mm) and not greater than 11-7/8 inches (302 mm). The machine shall have a feed A mechanism. The machine shall be nonautomatically lubricated and the mounting shall be fully submerged.

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. Stitch type 304, class 1 machines shall be suitable for stitching stars on flags, and design of guidons. Stitch type 304, class 2 shall be suitable for stitching coat pads, and canvas. Stitch type 308, class 1 machines shall be suitable for stitching rope ends and loops at the ends of 1/8 inch (3 mm) to 1/4 inch (6 mm) diameter ropes.

6.2 Ordering data. In addition to ordering data of 6.2 of the general specification, the purchaser should include the following information:

(a) Title, number and date of this specification.
(b) Stitch type and class machine required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

6.3 Deletion data. Styles A and B machine stitching classification designators were deleted in this revision.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMA

Project No. 3530-0063-5

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.