00-S-256/6A
November 16, 1978
SUPERSEDING
00-S-256/6
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL; BUTTONHOLE, STRAIGHT, BARRED ENDS, MACHINE

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers the specific requirements for a light and medium duty buttonhole machine, straight barred end, 304 type stitch (lock), industrial sewing machine.

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Machine, sewing. The sewing machine shall have a K feed mechanism, and shall operate at not less than 2,000 needle stitches per minute, and shall be capable of producing buttonholes from 1/4 to 3/4 inch (6 to 19 mm), 3/8 to 1 inch (10 to 25 mm) or 3/4 to 1-1/2 inch (19 to 38 mm), as specified (see 6.2). Cutting knives for all sizes, in steps of 1/8 inch (3 mm), shall be furnished. There shall not be less than 6 stitches to each bar. An arrangement shall be provided for adjusting the width of the stitches (stitch bight) on the sides of the buttonholes and also for the width of cutting space (cutting bight) between the rows of stitches. The machine shall be nonautomatically lubricated and the machine mounting shall be nonsubmerged. The driving belt shall be round leather type.

FSC 3530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.2 Operation. The machine when operated for each cycle shall automatically stitch the buttonhole with square barred ends, cut the buttonhole opening, and automatically trim the thread ends close to the buttonhole, and come to a stop, when tested as specified in 4.1.

4. QUALITY ASSURANCE PROVISIONS

4.1 Test. Each machine head shall be operated with light and medium weight fabric for not less than five cycles. Failure of the machine to provide for stitch and cutting bight, stitch type 304, and to meet the operational requirements of 3.2 shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. The machine shall be suitable for making straight, barred and buttonholes in cotton and flannel shirts, overalls, and jumpers.

6.2 Ordering data. In addition to ordering data of the general specification, the purchaser should include the following information:

(a) Title, number and date of this specification.
(b) Specify range of sizes of buttonholes required (see 3.1).

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activity:

Navy - MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-6

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.