00-S-256/7A
November 16, 1978
SUPERSEDING
00-S-256/7
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL; BUTTONHOLES, EYELET END, MACHINE

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers the specific requirements for a cut-before-stitching buttonhole machine, eyelet end, two-thread type, industrial sewing machine.

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Machine. The sewing machine shall have an L feed mechanism, and shall operate at no less than 1,500 needle stitches per minute. An arrangement shall be provided whereby the length of the bar may be adjusted from 1/8 to 1/4 inch (3 to 6 mm). Arrangements shall be provided for adjusting the width of stitches (stitch bight) on the sides of the buttonholes and also for the width of the cutting space (cutting bight) between the rows of stitches. Each machine shall be capable of producing buttonholes in the range of cut sizes, as specified (see 6.2), and as indicated in table I. The size of the eye cutter shall be .104 inches wide x .203 inches long (3.5 x 5.5 mm) or .156 inches wide x .250 inches long (4 x 6 mm) as specified (see 6.2). The table top shall be not less than 20 inches wide x 27 inches long x 1-1/4 inches thick (508 x 686 x 32 mm) or not less than 27 inches wide x 48 inches long x 2-1/2 inches thick (686 x 1219 x 63 mm). The machine mounting shall be nonsubmerged and shall be nonautomatically lubricated. The driving belts shall be round.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Buttonhole cut sizes

With tack, inches (mm)		Without tack, inches (mm)	
1/2 to 1-1/4	(13 to 32)	1/2 to 1-1/8	(13 to 29)
5/8 to 1	(16 to 25)	5/8 to 1-9/32	(16 to 33)
5/8 to 1-3/4	(16 to 44)	1/2 to 1-1/2	(13 to 38)
5/8 to 1-1/2	(16 to 38)	5/8 to 1-19/32	(16 to 40)
5/8 to 1-3/4	(16 to 44)	5/8 to 1-3/4	(16 to 44)
3/4 to 1-7/8	(19 to 48)	3/4 to 1-31/32	(19 to 50)

3.2 Operation. The machine when operated for each cycle shall automatically clamp and spread the work, cut the buttonhole, stitch the buttonhole, raise the clamps and come to a stop when tested as specified in 4.1.

4. QUALITY ASSURANCE PROVISIONS

4.1 Test. Each machine head shall be operated with heavy weight fabric for not less than five cycles. Failure of the machine to meet the 1/8 to 1/4 inch (3 to 6 mm) bar length adjustment, stitch and cutting bight as specified in 3.1 and in addition, the operation as specified in 3.2 shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

6. NOTES

6.1 Intended use. The machine shall be suitable for making eyelet end buttonholes in front of coats, overcoats, in shoulder straps, and pocket flaps.

6.2 Ordering data. In addition to ordering data of the general specification, the purchaser should include the following information as applicable:

(a) Title, number and date of this specification.
(b) Specify size of eye cutter required for buttonhole machines (see 3.1).
(c) Specify cut sizes of buttonholes (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 99

Review Activity:

DLA - GL

User Activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS
VA - DMS

Project No. 3530-0063-7

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.