00-S-256/8A
November 16, 1978
SUPERSEDING
00-S-256/8
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL;

BUTTON-SEWING MACHINE

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for a 101 (AX) type stitch, industrial, button sewing machine.

1.2 Classification.

1.2.1 Classes. The sewing machines shall be of the following classes, as specified (see 6.2).

Class 1 - Flat buttons
Class 3 - Hand-operated (laundry)

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Class 1. The class 1 machine shall operate at not less than 1,000 stitches per minute for machines equipped with vibrating needle bar, and 1,500 stitches per minute for vibrating clamp. The machine shall be capable of sewing 20 to 45 ligne, two or four hole flat buttons on fabrics. The vibrating needle bar shall require 22 stitches and the vibrating clamp 20, 21 or 24 stitches for each button. On four hole buttons, two parallel bars or stitches shall be provided. When specified (see 6.2), the machine shall be equipped to sew on a stay button on the reverse side of the work. The machine shall have a cylinder type bed. A table top not less than 19 inches wide x 24 inches long (483 x 610 mm) shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

The machine shall be nonsubmerged and nonautomatically lubricated. The driving belts shall be round leather type. The machine shall sew buttons with the required number of stitches and stop automatically and in addition, knives or thread breaking arrangement shall be provided to trim or break thread close to the work after stitching when tested as specified in 4.4.1.2.

3.2 Class 3. The class 3 machine shall be capable of sewing 12 to 35 ligne, 2 or 4 hole buttons, on fabrics with 12 stitches to each button. On 4 hole buttons, two parallel bars of stitches shall be provided. The machines shall be mounted on a pedestal stand not less than 36 inches high (914 mm), allowing for machine and stand to be portable. The machine shall be operated by a hand wheel on the right side of the machine. By turning the hand wheel, the machine shall sew on buttons with the required number of stitches and stop automatically and in addition, a thread breaking arrangement shall be provided to break or cut the thread close to work after stitching when tested as specified in 4.4.1.2.

4.1 Test. Each machine head shall sew on the applicable required buttons for not less than five cycles. Failure of class 1 machines to meet the operational requirements of 3.1 or failure of class 3 machines to meet the operational requirements of 3.2 shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. Class 1 machine shall be suitable for sewing flat buttons on shirts, shorts, trousers, jackets of light, medium or heavy fabrics. Class 3 machines shall be suitable for sewing flat buttons on shirts, suits, and pajamas.

6.2 Ordering data. In addition to the data of the general specification, the purchaser should include the following information:

(a) Title, number and date of this specification.
(b) Class machine required (see 1.2).
(c) Specify when it is required to sew on a stay button (see 3.1).

6.3 Deletion data. In this revision, shank buttons were deleted in class 1 and also class 2 was deleted.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-8

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.