INCH-POUND

OO-V-185F
INTERIM AMENDMENT 3 (NAVY-SH)
June 7, 1993
SUPERSEDING
INTERIM AMENDMENT 2 (ARMY-GL)
March 1, 1988

FEDERAL SPECIFICATION

VEGETABLE PEELING MACHINE, ELECTRIC

This interim amendment forms a part of OO-V-185F, dated 14 June 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.1, under "Military Standards": Delete "MIL-STD-1188" and its title.

2.1, under "STANDARDS/MILITARY": Add the following:

"MIL-STD-167-1 - Mechanical Vibration of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).
MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities."

2.2, under "American Society for Testing and Materials (ASTM)": Add:

"D-3951 - Standard Practice for Commercial Packaging". (DOD adopted)

PAGE 6

3.4.1, lines 12 and 14, after "carbide": Add: ", silica quartz".

3.4.1.b, line 1, after "carbide": Add: "or silica quartz".

3.4.2, line 4, after "carbide": Add: ", silica quartz".

3.4.2.b, after "carbide": Add: "or silica quartz".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.13, *after last sentence:* Add: "When specified, requirements and test limits of class A4 for surface ships and class A5 for submarines of MIL-STD-461 apply. Shipboard equipment shall meet the emission and susceptibility requirements for CE01, CE03 and RE02."

Add as new:

"3.4.15 Human factors criteria. Human factors engineering criteria, principles, and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the vegetable peeling machine. Maintenance and operation tasks shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in sections 5.6 and 5.9 of MIL-STD-1472. Particular attention shall be given to the machine such that the hands of the 5th percentile female shall not inadvertently come in contact with any moving mechanisms. Controls and switches shall be selected and integrated into the design of the machine so as to meet the applicable requirements of sections 5.2 and 5.4 of MIL-STD-1472. Sufficient clearance or free area required around an item shall permit an individual with applicable 5th to 95th percentile body dimensions and physical capabilities to safely operate, maintain, remove, or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for the use of any tools, test equipment, or replacement parts needed. When inspecting for defects and performing tests (see section 4), the equipment shall adhere to the human factors engineering considerations listed herein.

3.4.16 Inclined operation. When specified for shipboard use, the vegetable peeling machine shall operate satisfactorily when inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of fluid or product when tested as specified in 4.4.6.

3.4.17 Environmental suitability. When specified for shipboard use (see 6.2), the vegetable peeling machine shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested as specified in 4.4.7."

Add as new:

* "3.4.18 High voltage labels. When specified for shipboard use (see 6.2), a Danger High Voltage label shall be affixed to the equipments outer case assembly, on or adjacent to each service access cover and adjacent to one of the fasteners which secures the cover. A high voltage warning label shall also be placed near the high voltage components inside the equipment. The label shall include but is not limited to the following warnings:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

a. A warning of high voltage.
b. Power supply shall be disconnected before using.
c. Access covers shall be in place during use.
d. Servicing shall be done by authorized individuals."

PAGE 11

Add as new:

"4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in qualilty conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

PAGE 13

4.2.6: third line, after "METHOD" add "CE01,".

PAGE 15

Add as new:

"4.4.6 Inclined operational test. Position the vegetable peeling machine with the base set at an angle of 15 degrees, then operate the machine for 30 seconds at each side of the vertical in each of two vertical planes at right angles to each other. At each of these positions observe for conformance with specified requirements (see 3.4.16). For the test, the vegetable peeling machine shall be loaded with potatoes until 3/4-full.

4.4.7 Shipboard environmental test. The vegetable peeling machine under normal operating conditions, shall be tested in accordance with MIL-STD-167-1, type I equipment. The vegetable peeling machine shall be secured to the test machine in the same manner that it will be secured on shipboard. Failure of the vegetable peeling machine to perform its function during and after testing, or meeting requirements of 3.4.17 shall constitute failure of this test. For the test the machine shall be loaded with potatoes until 3/4-full."

PAGE 16

5.1.2, line 2: Delete "MIL-STD-1188" and substitute "ASTM-D-3951".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

PAGE 17

5.2.3, line 2: Delete "MIL-STD-1188" and substitute "ASTM-D-3951".

PAGE 18

5.3.1 and 5.3.2, line 3: Delete "MIL-STD-1188" and substitute "ASTM-D-3951".

6.2: Add the following:

"(m) When the vegetable peeling machine is for shipboard use (see 3.4.16 and 3.4.17)."

Add as new:

"6.3.1 Technical manuals. The requirement for technical manuals should be considered when this document is cited on a contract. If technical manuals are required, a contract exhibit must be prepared to fully describe statement of work criteria and delivery instructions, and cite the applicable technical manual. The technical manuals must be acquired by separate Contract Line Item Number (CLIN) in the contract."

"The margins of this interim amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous interim amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous interim amendment."

Preparing activity:
Navy - SH
(Project 7320-N919)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.