METRIC

A-A-54847
29 March 1993

COMMERCIAL ITEM DESCRIPTION

PAPER, FILTER QUALITATIVE, FINE PRECIPITATES

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for Military Specification MIL-P-36745(1) which is cancelled.

This Commercial Item Description covers filter paper that is suitable for radioactive contamination survey swipe material in performing surveys for loose radioactive surface contamination.

Salient characteristics:

The filter paper shall contain not less than 80 percent cotton fiber or cotton linter and not more than 20 percent alpha-sulfite wood pulp. The paper shall contain no other pulps. The paper shall be composed of 100 percent fully bleached fibers.

The alpha-cellulose content shall be not less than 90 percent. The pH value of the filter paper shall be 7.0 ± 1.0. The ash content of each filter disk shall be not greater than 0.2 milligrams (mg). The total chloride content shall be not greater than 8000 parts per million (ppm) by weight. The wet bursting strength shall be 5.0 ± 2.0 points. The filter paper shall disintegrate and no fibers shall be visible to the naked eye when tested herein.

The filter paper disks shall have a diameter of 4.25 ± 0.10 centimeters (cm) and a thickness of 0.15 ±0.02 cm. The unit package shall contain not less than 100 filter papers. The surface finish shall be a smooth natural finish. Each filter paper disk shall have a uniform formation and no pinholes.

AMSC N/A FSC 6640

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Workmanship. The filter paper shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Package (PG). One package containing one hundred filter papers, as specified, constitutes one unit.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, with an AQL of 2.5 (percent defective) and an inspection level of S-II. The unit of product for examination purposes shall be the unit package.

Sampling for tests. Sampling for tests (dimensional), shall be conducted in accordance with MIL-STD-105, with an AQL of 0 (percent defective) and an inspection level of S-2. The unit of product for test purposes shall be the unit package.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics. Tests shall include, but shall not be limited to the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Fiber identification. The test for fiber identification shall be conducted in accordance with TAPPI Test Method T401 m-60.

Alpha-Cellulose. The alpha-cellulose content shall be determined in accordance with TAPPI Test Method T429 os-69.

Acidity. The pH value shall be determined in accordance with TAPPI Test Method T435 su-60.

Ash Content. The ash content shall be determined in accordance with TAPPI Test Method T413 ts-66.

Chloride Content. The total chloride content shall be determined in accordance with ASTM Designation D1161-60.

Wet Bursting strength. Clip together a pack of 5 filter paper disks and immerse the pack in distilled water at 21-24°Centigrade (°C) for not less than 5 minutes. Remove the pack from the water, allow it to drain suspended for not less than 10 seconds, then immediately determine the bursting strength in accordance with TAPPI Test Method T403 ts-63.

Disintegration. Individually sandwich 3 filter paper disks between fine screens (stainless steel having a grid opening not greater than 0.8 mm X 0.8 mm) and rigidly immerse them in deionized water in an autoclave. Increase the autoclave temperature to 260 ±10°C and maintain for 2 hours ± 1 minute. Within 30 minutes after the autoclave is cool enough to open, visually examine the screens and autoclave solutions.

Dimensions. The thickness of the filter paper disks shall be determined in accordance with TAPPI Test Method T411 os-68.

Count. The count shall be determined by weighing 10 disks and calculating the number per package, based on the weight of the total quantity in each package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Federal Food, Drug, and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction , the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug, and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered material. The offeror/contractor is encouraged to use recovered material in accordance with Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

Ordering data. Intermediate/exterior package quantities, labeling and marking must be specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document:

NSN	Item Identification
6640-00-836-6870	PAPER, FILTER, QUALITATIVE

MILITARY INTERESTS:

Custodians:

Army-MD
Navy-MS
Air Force-03

PREPARING ACTIVITY:

DoD-MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
USPHS
FDA-MPQAS

Project No. 6640-1770

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	A-A-54847	29 MARCH 1993

3 DOCUMENT TITLE

PAPER, FILTER QUALITATIVE, FINE PRECIPITATES

4 NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT. Defense Quality and Standardization Office 5203 Leesburg Pike Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:39Z
Check the source to verify that this is the current version before use.